

www.ps.bam.de/CE64/L64E00F1.PS/.TXT; linearized output
F: Output Linearization (OL) data CE64/L64E00F1.DAT in File (F)

$L^*/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)																
$W^*/Y_{intended}$	0.0	0.067	0.133	0.2	0.267	0.333	0.379	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	1.0
Y_i / Y_{max}	0.0	0.008	0.017	0.031	0.051	0.079	0.115	0.16	0.216	0.284	0.365	0.459	0.569	0.695	0.838	1.0

Picture C3: 16 visual equidistant L^* -grey steps; PS operator: 000n* setcmycolor

See for similar files: <http://www.ps.bam.de/CE64/>
Technical information: <http://www.ps.bam.de/9241>

Version 2.0, io=0.0, CIELAB, 1.0 exp

ISO 9241-test chart for four different contrast ranges
Ergonomics – Visual Displays – Field Assessment Methods

input: 000n* setcnykcolor
output: no change compared to input