

www.ps.bam.de/CE73/L73E00N1.PS/TXT; start output

N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)

$L^*/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.3/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.1/74.3	95.4/88.6
No. and Hex code	00:F	01:E	02:D	03:C	04:B	05:A	06:9	07:8	08:7	09:6	10:5	11:4	12:3	13:2	14:1	15:0
$w^* = I^*_{CIE\text{LAB}, r}$ (relative)																
$W_{intended}$	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0
Y_i / Y_{max}	0.0	0.008	0.017	0.031	0.051	0.079	0.115	0.16	0.216	0.284	0.365	0.459	0.569	0.695	0.838	1.0

Picture C3: 16 visual equidistant L^* -grey steps; PS operator: www* setrgbcolor

$L^*/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.3/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.1/74.3	95.4/88.6
No. and Hex code	00:F	01:E	02:D	03:C	04:B	05:A	06:9	07:8	08:7	09:6	10:5	11:4	12:3	13:2	14:1	15:0
$w^* = I^*_{CIE\text{LAB}, r}$ (relative)																
$W_{intended}$	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0
Y_i / Y_{max}	0.0	0.008	0.017	0.031	0.051	0.079	0.115	0.16	0.216	0.284	0.365	0.459	0.569	0.695	0.838	1.0

Picture C3: 16 visual equidistant L^* -grey steps; PS operator: www* setrgbcolor

$L^*/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.3/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.1/74.3	95.4/88.6
No. and Hex code	00:F	01:E	02:D	03:C	04:B	05:A	06:9	07:8	08:7	09:6	10:5	11:4	12:3	13:2	14:1	15:0
$w^* = I^*_{CIE\text{LAB}, r}$ (relative)																
$W_{intended}$	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0
Y_i / Y_{max}	0.0	0.008	0.017	0.031	0.051	0.079	0.115	0.16	0.216	0.284	0.365	0.459	0.569	0.695	0.838	1.0

Picture C3: 16 visual equidistant L^* -grey steps; PS operator: www* setrgbcolor

$L^*/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.3/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.1/74.3	95.4/88.6
No. and Hex code	00:F	01:E	02:D	03:C	04:B	05:A	06:9	07:8	08:7	09:6	10:5	11:4	12:3	13:2	14:1	15:0
$w^* = I^*_{CIE\text{LAB}, r}$ (relative)																
$W_{intended}$	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0
Y_i / Y_{max}	0.0	0.008	0.017	0.031	0.051	0.079	0.115	0.16	0.216	0.284	0.365	0.459	0.569	0.695	0.838	1.0

Picture C3: 16 visual equidistant L^* -grey steps; PS operator: www* setrgbcolor

ISO 9241-test chart for standard luminous contrast range

Ergonomics – Visual Displays – Field Assessment Methods

input: www* setrgbcolor

output: no change compared to input

See for similar files: <http://www.ps.bam.de/CE73/>

Technical information: <http://www.ps.bam.de/9241> Version 2.0, io=3.3, CIE LAB, 1.0 exp

BAM registration: 20040101-CE73/L73E00N1.PS/TXT
Application for achromatic display output with CIE LAB contrast range
L*:L*:n = 95.4 : 0.0
L*:L*:n = 95.4 : 0.0
L*:L*:n = 95.4 : 0.0

BAM material: code=th4ta