www.ps.bam.de/DE85/10O/O85E00FP.PS/.PDF; linearized output
F: Output Linearization (OL) data DE85/10O/O85E00FP.DAT in File (F)



Picture D4: 16 equidistant steps ***W-O, W-L, W-V*** and ***W-N***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D5: Script and Landolt-rings *N*, *O*, *L* and *V*; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D6: Landolt-rings ***W-O*** and ***W-L***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D7: Landolt-rings ***W-V*** and ***W-N***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D4: 16 equidistant steps ***W-O, W-L, W-V*** and ***W-N***; Use of PS operator *olv* setrgbcolor* (only)



Picture D5: Script and Landolt-rings *N*, *O*, *L* and *V*; Use of PS operator *olv* setrgbcolor* (only)



Picture D6: Landolt-rings ***W-O*** and ***W-L***; Use of PS operator *olv* setrgbcolor* (only)



Picture D7: Landolt-rings ***W-V*** and ***W-N***; Use of PS operator *olv* setrgbcolor* (only)

See for similar files: http://www.ps.bam.de/DE85/DE85.HTM
Information and Order: http://www.ps.bam.de Version 2.0, io=m,0; iORS; oORS, CIELAB

BAM registration: 20030101-DE85/10O/O85E00FP.PS/.PDF
application for monitors and printers
BAM material: code=rha4ta

Fig. D4 to D7 of ISO/IEC-test chart 4;
ISO/IEC 15775 and DIS ISO/IEC 19839-X;
input: mixture (m) of PS operators
output: *cmy0* / 000n* setcmykcolor*