www.ps.bam.de/DE88/10L/L88E00SP.PS/.PDF;
S: Output Linearization (OL) data DE88/10L/L88E00SP.DAT in Distiller Startup (S) Directory



Radial grating (Siemens-star) *N-W*



Radial grating (Siemens-star) *W-N*



Radial grating (Siemens-star) *N-Z*



Radial grating (Siemens-star) *W-Z*

Picture C1: Radial gratings (Siemens-stars) *N-W*, *W-N*, *N-Z* and *W-Z*; PS operator: *nnn0* setcmykcolor*



Picture C2: 5 visual equidistant *L**-grey steps + *N0* + *W1*; PS operator: *cmy0* setcmykcolor*



Picture C3: 16 visual equidistant *L**-grey steps; PS operator: *nnn0* setcmykcolor*



Picture C4: Landolt-rings *W-N*; PS operator: *nnn0* setcmykcolor*



Picture C5: Line raster under 45° (or 135°); PS operator: *nnn0* setcmykcolor*



Picture C6: Line raster under 90° (or 0°); Use of the PS operator *nnn0* setcmykcolor*

See for similar files: http://www.ps.bam.de/DE88/
Information and Order: http://www.ps.bam.de Version 2.0, io=2,2?

BAM registration: 20031201-DE88/10L/L88E00SP.PS/.PDF BAM material: code=rha4ta
Full page: application for monitors (Yr=2.5) and printers

ISO/IEC-test chart no. 3 according to ISO/IEC 15775 and DIS ISO/IEC 19839-X; input: *nnn0*lin 1.0 exp setcmykcolor* output: *Startup (S) data dependend*