See for similar files: http://www.ps.bam.de/EE86/
Information and Order: http://www.ps.bam.de Version 2.0, io=0,0; iORS, oORS, CIELAB

BAM registration: 20031201-EE86/L86E00F1.PS/.TXT
Top part of page: application for monitors (Yr=2.5) and printers
BAM material: code=ha4a



Picture C1: Radial gratings (Siemens-stars) *N-W*, *W-N*, *N-Z* and *W-Z*; PS operator: *000n* setcmykcolor*



Picture C4: Landolt-rings *W-N*; PS operator: *000n* setcmykcolor*



Picture C5: Line raster under 45° (or 135°); PS operator: *000n* setcmykcolor*



Picture C2: 5 visual equidistant *L**-grey steps + *N0* + *W1*; PS operator: *000n* setcmykcolor*



Picture C6: Line raster under 90° (or 0°); Use of the PS operator *000n* setcmykcolor*

Picture C3: 16 visual equidistant *L**-grey steps; PS operator: *nnn0* setcmykcolor*; use file www.bam.de/FE88/10L/L88E0iFA.PS or L88E0iFP.PS/.PDF (i=0,7) for PDF systems to complete the figure

ISO/IEC-test chart no. 3 according to ISO/IEC 15775 and DIS ISO/IEC 19839-X; input: *000n*lin 1.0 exp setcmykcolor* output: *cmy0* / 000n* setcmykcolor*