



Picture C1: Radial gratings (Siemens-stars) N-W, W-N, N-Z and W-Z; PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$




Picture C2: 5 visual equidistant  $L^*$ -grey steps +  $N_0$  +  $W_1$ ; PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$




Picture C3: 16 visual equidistant  $L^*$ -grey steps; PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$ ; use file www.bam.de/EE87/10S/S87E00F1.PS or /S87E00F1.PDF for DPS or PDF systems to complete the figure


ISO/IEC-test chart no. 3 according to  
ISO/IEC 15775 and input:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$   
DIS ISO/IEC 19839-X; output:  $\text{cmy0}^* / 000n^* \text{ setcmykcolor}$



Picture C4: Landolt-rings W-N; PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$



Picture C5: Line raster under 45° (or 135°); PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$



Picture C6: Line raster under 90° (or 0°); PS operator:  $w^{\text{lin}} 1.0 \exp \text{ setgray}$