www.ps.bam.de/FE96/10L/L96E03SP.PS/.PDF;
S: Output Linearization (OL) data FE96/10L/L96E03SP.DAT in Distiller Startup (S) Directory

Picture B1: Flower motif, 14 CIE-test colours and 2 + 16 grey steps (sf); PS operators *settransfer, 4 colorimage*



Picture B4: 16 equidistant steps ***W-C, W-M, W-Y*** and ***W-N***; PS operator *cmy0* / 000n* setcmykcolor*



Picture B5: Script and Landolt-rings ***N, M, C*** and ***Y***; Use of PS operator *cmy0* / 000n* setcmykcolor*



Picture B2: Radial gratings ***W-C, W-M, W-Y, W-N,*** and ***W-Z***; PS operator *cmy0* / 000n* setcmykcolor*



Picture B6: Landolt-rings ***W-C*** and ***W-M***; Use of PS operator *cmy0* / 000n* setcmykcolor*



Picture B3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator *cmy0* / 000n* setcmykcolor*



Picture B7: Landolt-rings ***W-Y*** and ***W-N***; Use of PS operator *cmy0* / 000n* setcmykcolor*

See for similar files: http://www.ps.bam.de/FE96/
Information and Order: http://www.ps.bam.de Version 2.0, io=0,0?

BAM registration: 20030101-FE96/10L/L96E03SP.PS/.PDF BAM material: code=rha4ta
application for monitors (Yr=2.5) and printers

Fig. B1 to B7 of ISO/IEC-test chart 2;
ISO/IEC 15775 and
DIS ISO/IEC 19839-X;
input: *cmy0* / 000n* setcmykcolor*
output: *Startup (S) data dependend*