



Order information of production company (e.g. Web-site) for ISO-test chart (e.g. code=rha4ra-I0(2/4))



Technical informations: (e.g. Web-site)

Layout-file version IE-OCSA498

ISO identification: 19980615-I0(2/4)

ISO-reference material: code=rha4ra-I0(2/4)



*part 1*

*Warning: Exact Position, size and distance of samples in picture B1 depend on manufacturer of ISO-test chart (intention: similar compared to picture B3!)*

- xB41 = 8,5 mm, yB41 = 34,5 mm, xdB41 = 7,0 mm
  - xB42 = 8,5 mm, yB42 = 26,0 mm, xdB42 = 7,0 mm
  - xB43 = 8,5 mm, yB43 = 17,5 mm, xdB43 = 7,0 mm
  - xB44 = 8,5 mm, yB44 = 8,5 mm, xdB44 = 7,0 mm
- xB4 = 161 mm, yB4 = 153 mm, xdB4 = 112 mm, ydB4 = 40 mm

Picture B4 or C4

xB5 = 161 mm, yB5 = 109 mm, xdB5 = 112 mm, ydB5 = 40 mm

- xB11 = 6,85 mm, yB11 = 19,85 mm, xdB11 = 7,7 mm *part 2*
  - xB12 = 6,85 mm, yB12 = 7,85 mm, xdB12 = 7,7 mm *part 3*
- xB1 = 28 mm, yB1 = 109 mm, xdB1 = 130 mm, ydB1 = 86 mm

Picture B1 or D1

xB2 = 28 mm, yB2 = 65 mm, xdB2 = 130 mm, ydB2 = 40 mm

Picture B5 or D5

xB6 = 161 mm, yB6 = 65 mm, xdB6 = 112 mm, ydB6 = 40 mm

- Recommendation: Measure larger adjacent samples!*
- xB31 = 6,85 mm, yB31 = 25,35 mm, xdB31 = 7,7 mm
  - xB32 = 6,85 mm, yB32 = 13,35 mm, xdB32 = 7,7 mm
- xB3 = 28 mm, yB3 = 21 mm, xdB3 = 130 mm, ydB3 = 40 mm

Picture B6 or D6

xB7 = 161 mm, yB7 = 21 mm, xdB7 = 112 mm, ydB7 = 40 mm

Picture B3 or D3

Picture B7 or D7

Test chart no. (2/4) for color devices according to ISO 15775: compare [www.actech.com.br/sc28](http://www.actech.com.br/sc28)

