

Order information of production company (e.g. Web-site) for ISO-test chart (e.g. code=rha4ra-I0(2/4))

Technical informations: (e.g. Web-site)

Layout-file version IE-DCSA698

ISO identification: 19980615-10(2/4)

ISO-reference material: code=rha4ra-I0(2/4)

part 1

Warning: Exact Position, size and distance of samples in picture B1 depend on manufacturer of ISO-test chart (intention: similar compared to picture B3!)

• xB11 = 6,85 mm, yB11 = 19,85 mm, xdB11 = 7,7 mm

part 2

• xB12 = 6,85 mm, yB12 = 7,85 mm, xdB12 = 7,7 mm

part 3

xB1 = 28 mm, yB1 = 109 mm, xdB1 = 130 mm, ydB1 = 86 mm

Picture B1 or D1

xB2 = 28 mm, yB2 = 65 mm, xdB2 = 130 mm, ydB2 = 40 mm

Picture B2 or D2

Recommendation: Measure larger adjacent samples!

• xB31 = 6,85 mm, yB31 = 25,35 mm, xdB31 = 7,7 mm

• xB32 = 6,85 mm, yB32 = 13,35 mm, xdB32 = 7,7 mm

xB3 = 28 mm, yB3 = 21 mm, xdB3 = 130 mm, ydB3 = 40 mm

Picture B3 or D3

Test chart no. (2/4) for color devices according to ISO 15775: compare www.actech.com.br/sc28

• xB41 = 8,5 mm, yB41 = 34,5 mm, xdB41 = 7,0 mm

• xB42 = 8,5 mm, yB42 = 26,0 mm, xdB42 = 7,0 mm

• xB43 = 8,5 mm, yB43 = 17,5 mm, xdB43 = 7,0 mm

• xB44 = 8,5 mm, yB44 = 8,5 mm, xdB44 = 7,0 mm

xB4 = 161 mm, yB4 = 153 mm, xdB4 = 112 mm, ydB4 = 40 mm

Picture B4 or C4

xB5 = 161 mm, yB5 = 109 mm, xdB5 = 112 mm, ydB5 = 40 mm

Picture B5 or D5

xB6 = 161 mm, yB6 = 65 mm, xdB6 = 112 mm, ydB6 = 40 mm

Picture B6 or D6

xB7 = 161 mm, yB7 = 21 mm, xdB7 = 112 mm, ydB7 = 40 mm

Picture B7 or D7