

Siehe ähnliche Dateien: <http://www.ps.bam.de/LG08/LG08.HTM>
Information, Bestellung: <http://www.ps.bam.de> Version 2.0, io=0, iORS, oORS, CIELAB

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	Benutzte Koordinate
01																		Umfeld
02																		Infeld
03																		C $LAB^*_{ORS18} c000^*$
04																		$LAB^*_{ORS18} 1my0^*$
05																		$LAB^*_{ORS18} 0m00^*$
06																		M $LAB^*_{ORS18} c1y0^*$
07																		$LAB^*_{ORS18} 00y0^*$
08																		Y $LAB^*_{ORS18} cm10^*$
09																		$LAB^*_{ORS18} 0my0^*$
10																		O $LAB^*_{ORS18} c110^*$
11																		$LAB^*_{ORS18} c0y0^*$
12																		L $LAB^*_{ORS18} 1m10^*$
13																		$LAB^*_{ORS18} cm00^*$
14																		V $LAB^*_{ORS18} 11y0^*$
15																		$LAB^*_{ORS18} cmy0^*$
16																		N/W $LAB^*_{ORS18} 000k^*$

16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG08: CIELAB-Stufen ISO/IEC 15775
Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe(ORS18): $LAB^*_{setcolor/cmy} * setcmy$
Ausgabe(ORS18): $cmy0^* / 000n^* setcmykcolor$

BAM-Registrierung: 2003101-LG08/L08G00F1.PS/.TXT
Anwendung für Messung von Monitor- (Y=2.5) und Druckerausgabe

BAM-Material: Code=thata