

Siehe ähnliche Dateien: <http://www.ps.bam.de/LG18/LG18.HTM>
Information, Bestellung: <http://www.ps.bam.de> Version 2.0, io=0,0

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
01																	
02																	
03																	
04																	
05																	
06																	
07																	
08																	
09																	
10																	
11																	
12																	
13																	
14																	

Benutzte Koordinate
Umfeld Infeld
C LAB^*_{TLS00} $c000^*$
 LAB^*_{TLS00} $1my0^*$
 LAB^*_{TLS00} $0m00^*$
M LAB^*_{TLS00} $c1y0^*$
 LAB^*_{TLS00} $00y0^*$
Y LAB^*_{TLS00} $cm10^*$
 LAB^*_{TLS00} $0my0^*$
O LAB^*_{TLS00} $c110^*$
 LAB^*_{TLS00} $c0y0^*$
L LAB^*_{TLS00} $1m10^*$
 LAB^*_{TLS00} $cm00^*$
V LAB^*_{TLS00} $11y0^*$
 LAB^*_{TLS00} $cmy0^*$
N/W LAB^*_{TLS00} $000k^*$

16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG18: CIELAB-Stufen ISO/IEC 15775
Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe ,TLS00,ORS18: LAB^* setcolor (2x)
Ausgabe ,TLS00: keine Änderung

BAM-Registrierung: 20030101-LG18/10S/S18G07NP.PS/.PDF BAM-Material: Code=rha4ta
Anwendung für Messung von Monitor- (Yr=2.5) und Druckerausgabe