

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	Benutzte Koordinate
01																		Umfeld
02																		Infeld
03																		C $LAB^*_{\text{TLS00}} c000^*$
04																		M $LAB^*_{\text{TLS00}} 1my0^*$
05																		$LAB^*_{\text{TLS00}} 0m00^*$
06																		Y $LAB^*_{\text{TLS00}} c1y0^*$
07																		$LAB^*_{\text{TLS00}} 00y0^*$
08																		O $LAB^*_{\text{TLS00}} cm10^*$
09																		$LAB^*_{\text{TLS00}} 0my0^*$
10																		$LAB^*_{\text{TLS00}} c110^*$
11																		L $LAB^*_{\text{TLS00}} c0y0^*$
12																		$LAB^*_{\text{TLS00}} 1m10^*$
13																		V $LAB^*_{\text{TLS00}} cm00^*$
14																		$LAB^*_{\text{TLS00}} 11y0^*$
15																		$LAB^*_{\text{TLS00}} cmy0^*$
16																		N/W $LAB^*_{\text{TLS00}} 000k^*$

16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG18: CIELAB-Stufen ISO/IEC 15775
Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe ,TLS00,ORS18: **LAB* setcolor (2x)**
Ausgabe ,TLS00: keine Änderung