

Siehe ähnliche Dateien: <http://www.ps.bam.de/LG19/LG19.HTM>
Information, Bestellung: <http://www.ps.bam.de> Version 2.0, io=0,4; iTLS; oTLS, CIELAB

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q
01																	
02																	
03																	
04																	
05																	
06																	
07																	
08																	
09																	
10																	
11																	
12																	
13																	
14																	

Benutzte Koordinate
Umfeld Infeld

*LAB*_{TLS00} *o11**

*LAB*_{TLS00} *o1v**

*LAB*_{TLS00} *111**

*LAB*_{TLS00} *o0v**

*LAB*_{TLS00} *11v**

*LAB*_{TLS00} *o10**

*LAB*_{TLS00} *11v**

*LAB*_{TLS00} *o00**

*LAB*_{TLS00} *o1v**

*LAB*_{TLS00} *o10**

*LAB*_{TLS00} *o11**

*LAB*_{TLS00} *o0v**

*LAB*_{TLS00} *o1v**

*LAB*_{TLS00} *w**

16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG19: CIELAB-Stufen ISO/IEC 15775
Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe ,TLS00,TLS00: *LAB** *setcolor* (2x)
Ausgabe ,TLS00: *lab** *setcolor*