

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:

either according to DIN 6160 with Anomaloskop of *Nagel*
or with test charts using colour points according to *Ishihara*
or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

Only for display (monitor, data projector) output:

Office workplace illumination is daylight (clouded/north sky)

underline Yes/No

PDF-file output with www.ps.bam.de/XE75/10L/L75E00NP.PDF

underline Yes/No

Comparison of contrast range of 16 steps F to 0 with test chart no. 3 of DIN 33866-1

give contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

Remark: In daylighted offices the contrast range is in many cases:

on paper between: >F:0 (highly glossy), F:0 (silk glossy) and E:0 (matte)

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: either www.ps.bam.de/XE27/10L/L27E00NP.PDF

underline Yes/No

or www.ps.bam.de/XE27/10P/P27E00NP.PDF

or underline Yes/No

PS-File: either www.ps.bam.de/XE27/10L/L27E00NA.PS

or underline Yes/No

or www.ps.bam.de/XE27/10P/P27E00NA.PS

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

underline Yes/No

If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/XE30/10L/L30E00NP.PS and transfer
of the PS-file L30E00NP.PS in PDF-file L30E00NP.PDF

underline Yes/No

If No, please describe other method: