

Ostwald optimal colours (o) of maximum (m) C _{AB} for D65, Y _N =0, Y _W =100, Y _m =520_770												
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	
0	405	32 561	58.24	−22.72	−17.88	28.91	0.5603	−0.7425	218.1	16 483	37 589	Cm
6	435	32 562	58.83	−26.76	−9.87	28.52	0.4955	−0.6033	200.2	17 486	42 610	
10	450	32 563	59.45	−33.51	4.92	33.87	0.3868	−0.3527	171.6	19 496	−1 496c	
12	460	33 565	60.35	−36.41	12.65	38.54	0.3471	−0.2259	160.8	21 505	−1 505c	
12	465	33 567	61.7	−36.61	13.23	38.93	0.3569	−0.221	160.1	21 506	−1 506c	
14	470	33 569	62.76	−38.1	19.3	42.72	0.3432	−0.1279	153.1	24 520	−1 520c	
15	475	34 573	65.32	−38.25	22.45	44.35	0.3649	−0.0919	149.5	25 528	−1 528c	Gm
16	480	36 580	69.98	−37.44	26.02	45.6	0.4153	−0.0637	145.2	27 537	−1 537c	
17	485	39 595	78.77	−32.7	30.97	45.04	0.5352	−0.0423	136.5	29 548	−1 548c	
18	490	−1 490c	93.81	−12.05	38.36	40.21	0.8219	−0.0266	107.4	33 565	11 459	max
19	495	−1 495c	92.31	−10.67	38.35	39.81	0.8347	−0.02	105.5	33 566	12 462	
20	500	−1 500c	90.43	−8.9	38.03	39.06	0.8519	−0.0149	103.1	33 567	12 464	
22	510	−1 510c	85.29	−4.15	36.45	36.68	0.9017	−0.0081	96.4	33 569	13 469	
23	520	−1 519c	82.0	−1.25	35.2	35.23	0.9351	−0.0062	92.0	34 570	14 471	Ym
25	530	−1 529c	74.07	5.15	31.98	32.4	1.02	−0.0036	80.8	34 573	15 475	
27	540	−1 539c	64.93	11.56	28.13	30.41	1.1285	−0.0023	67.6	35 577	15 478	
28	545	−1 544c	60.16	14.49	26.08	29.84	1.1913	−0.0019	60.9	35 579	15 479	
29	550	−1 549c	55.3	17.16	23.99	29.5	1.2607	−0.0017	54.4	36 582	16 480	
30	555	−1 554c	50.45	19.48	21.89	29.3	1.3365	−0.0016	48.3	36 584	16 481	
32	560	−1 560c	41.06	22.78	17.82	28.92	1.5051	−0.0016	38.0	37 589	16 483	
32	561	0 405	41.75	22.72	17.88	28.91	1.4946	−0.0073	38.1	37 589	16 483	Rm
32	562	6 435	41.16	26.76	9.87	28.52	1.6006	−0.1957	20.2	42 610	17 486	
32	563	10 450	40.54	33.51	−4.92	33.87	1.777	−0.557	351.6	−1 496c	19 496	
33	565	12 460	39.64	36.41	−12.65	38.54	1.869	−0.7546	340.8	−1 505c	21 505	
33	567	12 465	38.29	36.61	−13.23	38.93	1.9064	−0.7811	340.1	−1 506c	21 506	
33	569	14 470	37.23	38.1	−19.3	42.72	1.9738	−0.9541	333.1	−1 520c	24 520	
34	573	15 475	34.67	38.24	−22.45	44.35	2.0535	−1.083	329.5	−1 528c	25 528	Mm
36	580	16 480	30.01	37.44	−26.01	45.6	2.198	−1.3024	325.2	−1 537c	27 537	
39	595	17 485	21.22	32.7	−30.97	45.04	2.4912	−1.8948	316.5	−1 548c	29 548	
−1	490c	18 490	6.18	12.05	−38.36	40.21	2.8987	−6.6365	287.4	11 459	33 565	min
−1	495c	19 495	7.68	10.67	−38.35	39.81	2.3389	−5.4239	285.5	12 462	33 566	
−1	500c	20 500	9.57	8.9	−38.03	39.06	1.8812	−4.4101	283.1	12 464	33 567	
−1	510c	22 510	14.7	4.15	−36.45	36.68	1.2327	−2.914	276.4	13 469	33 569	
−1	519c	23 520	17.99	1.25	−35.2	35.23	1.0203	−2.3922	272.0	14 471	34 570	Bm
−1	529c	25 530	25.92	−5.15	−31.98	32.4	0.7515	−1.6692	260.8	15 475	34 573	
−1	539c	27 540	35.06	−11.56	−28.13	30.41	0.6205	−1.2379	247.6	15 478	35 577	
−1	544c	28 545	39.83	−14.49	−26.08	29.84	0.5864	−1.0905	240.9	15 479	35 579	
−1	549c	29 550	44.69	−17.16	−23.99	29.5	0.5663	−0.9724	234.4	16 480	36 582	
−1	554c	30 555	49.54	−19.48	−21.89	29.3	0.5572	−0.8774	228.3	16 481	36 584	
−1	560c	32 560	58.93	−22.78	−17.82	28.92	0.5638	−0.7379	218.0	16 483	37 589	
W0	380	770	100.0	0.0	0.0	0.01	0.9504	−0.4355	0.0			
N0	380	770	0.01	0.0	0.0	0.01	0.941	−0.4312	0.0			