

Ostwald optimal colours (o), maximum (m) C _{AB} for D50, Y _N =0, Y _W =90, Y _m =520_770																			
i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code								
1 405	32 564	53.83	−56.59	−29.05	63.62	0.5434	−0.5457	207.1	17 486	38 592	Cm								
7 435	33 565	53.61	−64.17	−13.59	65.6	0.4851	−0.4313	191.9	18 490	46 631									
10 450	33 566	54.16	−72.38	5.01	72.56	0.4294	−0.2928	176.0	19 497	−1 497c									
12 460	33 567	54.86	−77.11	17.85	79.14	0.4017	−0.1997	166.9	21 506	−1 506c									
13 465	33 568	55.56	−78.87	23.7	82.35	0.3961	−0.1592	163.2	22 512	−1 512c									
14 470	34 570	56.11	−79.85	28.57	84.81	0.3947	−0.1261	160.3	23 519	−1 519c									
15 475	34 573	58.04	−80.09	33.75	86.91	0.412	−0.0973	157.1	25 527	−1 527c	Gm								
15 480	35 578	61.49	−79.68	36.59	87.68	0.4456	−0.0919	155.3	26 532	−1 532c									
17 485	37 587	66.01	−74.12	45.14	86.79	0.5148	−0.0563	148.6	28 544	−1 544c									
18 490	44 620	79.56	−41.87	57.86	71.42	0.7534	−0.0389	125.8	32 561	−1 561c									
19 495	−1 495c	84.51	−15.51	63.16	65.04	0.8905	−0.0309	103.7	33 568	12 463	max								
20 500	−1 500c	83.07	−12.07	62.93	64.08	0.9058	−0.0268	100.8	33 569	13 466									
22 510	−1 510c	79.06	−2.65	60.89	60.94	0.9505	−0.0218	92.4	34 571	14 471									
23 520	−1 519c	76.43	3.22	59.1	59.18	0.9808	−0.0205	86.8	34 572	14 473									
25 530	−1 529c	69.95	16.52	54.23	56.7	1.0584	−0.0197	73.0	35 575	15 477	Ym								
27 540	−1 539c	62.35	30.11	48.22	56.85	1.1571	−0.0205	58.0	35 579	16 480									
28 545	−1 544c	58.33	36.43	44.97	57.87	1.2137	−0.0214	50.9	36 581	16 481									
29 550	−1 549c	54.19	42.24	41.6	59.29	1.2758	−0.0227	44.5	36 583	16 483									
30 555	−1 554c	50.01	47.36	38.19	60.84	1.3427	−0.0244	38.8	37 585	16 484									
32 560	−1 560c	41.85	54.81	31.49	63.21	1.4878	−0.0288	29.8	38 590	17 486									
32 564	1 405	46.16	56.59	29.05	63.62	1.4543	−0.078	27.1	38 592	17 486	Rm								
33 565	7 435	46.38	64.17	13.59	65.59	1.5173	−0.2126	11.9	46 631	18 490									
33 566	10 450	45.83	72.37	−5.01	72.55	1.5956	−0.3736	356.0	−1 497c	19 497									
33 567	12 460	45.13	77.09	−17.84	79.13	1.6471	−0.488	346.9	−1 506c	21 506									
33 568	13 465	44.43	78.85	−23.7	82.33	1.6737	−0.5432	343.2	−1 512c	22 512									
34 570	14 470	43.88	79.83	−28.57	84.79	1.6917	−0.5903	340.3	−1 519c	23 519									
34 573	15 475	41.95	80.07	−33.74	86.89	1.7274	−0.6516	337.1	−1 527c	25 527	Mm								
35 578	15 480	38.5	79.66	−36.57	87.65	1.7916	−0.7099	335.3	−1 532c	26 532									
37 587	17 485	33.98	74.1	−45.12	86.76	1.8361	−0.861	328.6	−1 544c	28 544									
44 620	18 490	20.43	41.86	−57.83	71.39	1.7832	−1.4618	305.8	−1 561c	32 561									
−1 495c	19 495	15.48	15.5	−63.13	65.0	1.3645	−1.9609	283.7	12 463	33 568	min								
−1 500c	20 500	16.92	12.07	−62.9	64.04	1.2492	−1.8165	280.8	13 466	33 569									
−1 510c	22 510	20.93	2.64	−60.86	60.92	1.0145	−1.4926	272.4	14 471	34 571									
−1 519c	23 520	23.56	−3.22	−59.08	59.17	0.9092	−1.3327	266.8	14 473	34 572									
−1 529c	25 530	30.04	−16.51	−54.22	56.68	0.744	−1.0518	253.0	15 477	35 575	Bm								
−1 539c	27 540	37.64	−30.11	−48.21	56.84	0.644	−0.8422	238.0	16 480	35 579									
−1 544c	28 545	41.66	−36.42	−44.97	57.87	0.6142	−0.7615	230.9	16 481	36 581									
−1 549c	29 550	45.8	−42.24	−41.6	59.29	0.595	−0.6931	224.5	16 483	36 583									
−1 554c	30 555	49.98	−47.36	−38.19	60.84	0.5849	−0.6355	218.8	16 484	37 585									
−1 560c	32 560	58.14	−54.81	−31.49	63.21	0.5869	−0.5465	209.8	17 486	38 590									
W0	380	770	90.0	0.0	0.0	0.0	0.9639	−0.3298	0.0	B _c =1,000									
N0	380	770	3.6	0.0	0.0	0.0	0.9639	−0.3298	0.0	x _c =0,000									