

Ostwald optimal colours (o), maximum (m) C_{AB} for D50, $Y_N=0, Y_W=90, Y_m=520_770$

i_1, λ_1	i_2, λ_2	Y	A_1	B_1	$C_{AB,1}$	a_1	b_1	$h_{xy,1}$	i_d, λ_d	i_c, λ_c	Code
1	405	32 564	53.83	-58.36	-29.05	65.19	0.2236	-0.5457 206.4	17 486	38 592	Cm
7	435	33 565	53.61	-60.85	-13.59	62.35	0.2032	-0.4313 192.5	18 490	46 631	
10	450	33 566	54.16	-63.04	5.01	63.24	0.1916	-0.2928 175.4	19 497	-1 497c	
12	460	33 567	54.86	-63.72	17.85	66.17	0.1926	-0.1997 164.3	21 506	-1 506c	
13	465	33 568	55.56	-63.67	23.7	67.94	0.1988	-0.1592 159.5	22 512	-1 512c	
14	470	34 570	56.11	-63.21	28.57	69.37	0.2066	-0.1261 155.6	23 519	-1 519c	Gm
15	475	34 573	58.04	-62.0	33.75	70.59	0.2299	-0.0973 151.4	25 527	-1 527c	
15	480	35 578	61.49	-60.85	36.59	71.01	0.2613	-0.0919 148.9	26 532	-1 532c	
17	485	37 587	66.01	-53.55	45.14	70.04	0.3327	-0.0563 139.8	28 544	-1 544c	
18	490	44 620	79.56	-21.36	57.86	61.68	0.5498	-0.0389 110.2	32 561	-1 561c	
19	495	-1 495c	84.51	3.56	63.16	63.26	0.674	-0.0309 86.7	33 568	12 463	max
20	500	-1 500c	83.07	6.55	62.93	63.27	0.6888	-0.0268 84.0	33 569	13 466	
22	510	-1 510c	79.06	14.38	60.89	62.56	0.73	-0.0218 76.7	34 571	14 471	
23	520	-1 519c	76.43	19.11	59.1	62.11	0.7572	-0.0205 72.0	34 572	14 473	Ym
25	530	-1 529c	69.95	29.61	54.23	61.8	0.8265	-0.0197 61.3	35 575	15 477	
27	540	-1 539c	62.35	40.06	48.22	62.69	0.9142	-0.0205 50.2	35 579	16 480	
28	545	-1 544c	58.33	44.79	44.97	63.47	0.9643	-0.0214 45.1	36 581	16 481	
29	550	-1 549c	54.19	49.04	41.6	64.31	1.0192	-0.0227 40.3	36 583	16 483	
30	555	-1 554c	50.01	52.65	38.19	65.05	1.0783	-0.0244 35.9	37 585	16 484	
32	560	-1 560c	41.85	57.44	31.49	65.51	1.2062	-0.0288 28.7	38 590	17 486	
32	564	1 405	46.16	58.36	29.05	65.19	1.1629	-0.078 26.4	38 592	17 486	Rm
33	565	7 435	46.38	60.85	13.59	62.35	1.182	-0.2126 12.5	46 631	18 490	
33	566	10 450	45.83	63.03	-5.01	63.23	1.2074	-0.3736 355.4	-1 497c	19 497	
33	567	12 460	45.13	63.7	-17.84	66.16	1.2217	-0.488 344.3	-1 506c	21 506	
33	568	13 465	44.43	63.66	-23.7	67.93	1.2302	-0.5432 339.5	-1 512c	22 512	
34	570	14 470	43.88	63.2	-28.57	69.36	1.2333	-0.5903 335.6	-1 519c	23 519	Mm
34	573	15 475	41.95	61.98	-33.74	70.57	1.2483	-0.6516 331.4	-1 527c	25 527	
35	578	15 480	38.5	60.84	-36.57	70.99	1.2893	-0.7099 328.9	-1 532c	26 532	
37	587	17 485	33.98	53.54	-45.12	70.02	1.2874	-0.861 319.8	-1 544c	28 544	
44	620	18 490	20.43	21.35	-57.83	61.65	1.0751	-1.4618 290.2	-1 561c	32 561	
-1 495c	19 495	15.48	-3.55	-63.13	63.23	0.5652	-1.9609 266.7	12 463	33 568	min	
-1 500c	20 500	16.92	-6.55	-62.9	63.24	0.5023	-1.8165 264.0	13 466	33 569		
-1 510c	22 510	20.93	-14.37	-60.86	62.54	0.3825	-1.4926 256.7	14 471	34 571		
-1 519c	23 520	23.56	-19.11	-59.08	62.09	0.3328	-1.3327 252.0	14 473	34 572	Bm	
-1 529c	25 530	30.04	-29.61	-54.22	61.78	0.2629	-1.0518 241.3	15 477	35 575		
-1 539c	27 540	37.64	-40.05	-48.21	62.68	0.2316	-0.8422 230.2	16 480	35 579		
-1 544c	28 545	41.66	-44.78	-44.97	63.46	0.2273	-0.7615 225.1	16 481	36 581		
-1 549c	29 550	45.8	-49.03	-41.6	64.31	0.229	-0.6931 220.3	16 483	36 583		
-1 554c	30 555	49.98	-52.65	-38.19	65.04	0.2358	-0.6355 215.9	16 484	37 585		
-1 560c	32 560	58.14	-57.44	-31.49	65.51	0.262	-0.5465 208.7	17 486	38 590		
W0	380	770	90.0	0.0	0.0	0.0	0.6572	-0.3298 0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	0.6572	-0.3298 0.0	$x_c=0,110$		

Ostwald optimal colours (o), maximum (m) C_{AB} for D50, $Y_N=0, Y_W=90, Y_m=520_770$

i_1, λ_1	i_2, λ_2	Y	A_2	B_2	$C_{AB,2}$	a_2	b_2	$h_{xy,2}$	i_d, λ_d	i_c, λ_c	Code
1	405	32 564	53.83	-58.36	-29.05	65.19	0.2236	-0.5457 206.4	17 486	38 592	Cm
7	435	33 565	53.61	-60.85	-13.59	62.35	0.2032	-0.4313 192.5	18 490	46 631	
10	450	33 566	54.16	-63.04	5.01	63.24	0.1916	-0.2928 175.4	19 497	-1 497c	
12	460	33 567	54.86	-63.72	17.85	66.17	0.1926	-0.1997 164.3	21 506	-1 506c	
13	465	33 568	55.56	-63.67	23.7	67.94	0.1988	-0.1592 159.5	22 512	-1 512c	
14	470	34 570	56.11	-63.21	28.57	69.37	0.2066	-0.1261 155.6	23 519	-1 519c	Gm
15	475	34 573	58.04	-62.0	33.75	70.59	0.2299	-0.0973 151.4	25 527	-1 527c	
15	480	35 578	61.49	-60.85	36.59	71.01	0.2613	-0.0919 148.9	26 532	-1 532c	
17	485	37 587	66.01	-53.55	45.14	70.04	0.3327	-0.0563 139.8	28 544	-1 544c	
18	490	44 620	79.56	-21.36	57.86	61.68	0.5498	-0.0389 110.2	32 561	-1 561c	
19	495	-1 495c	84.51	3.56	63.16	63.26	0.674	-0.0309 86.7	33 568	12 463	max
20	500	-1 500c	83.07	6.55	62.93	63.27	0.6888	-0.0268 84.0	33 569	13 466	
22	510	-1 510c	79.06	14.38	60.89	62.56	0.73	-0.0218 76.7	34 571	14 471	
23	520	-1 519c	76.43	19.11	59.1	62.11	0.7572	-0.0205 72.0	34 572	14 473	Ym
25	530	-1 529c	69.95	29.61	54.23	61.8	0.8265	-0.0197 61.3	35 575	15 477	
27	540	-1 539c	62.35	40.06	48.22	62.69	0.9142	-0.0205 50.2	35 579	16 480	
28	545	-1 544c	58.33	44.79	44.97	63.47	0.9643	-0.0214 45.1	36 581	16 481	
29	550	-1 549c	54.19	49.04	41.6	64.31	1.0192	-0.0227 40.3	36 583	16 483	
30	555	-1 554c	50.01	52.65	38.19	65.05	1.0783	-0.0244 35.9	37 585	16 484	
32	560	-1 560c	41.85	57.44	31.49	65.51	1.2062	-0.0288 28.7	38 590	17 486	
32	564	1 405	46.16	58.36	29.05	65.19	1.1629	-0.078 26.4	38 592	17 486	Rm
33	565	7 435	46.38	60.85	13.59	62.35	1.182	-0.2126 12.5	46 631	18 490	
33	566	10 450	45.83	63.03	-5.01	63.23	1.2074	-0.3736 355.4	-1 497c	19 497	
33	567	12 460	45.13	63.7	-17.84	66.16	1.2217	-0.488 344.3	-1 506c	21 506	
33	568	13 465	44.43	63.66	-23.7	67.93	1.2302	-0.5432 339.5	-1 512c	22 512	
34	570	14 470	43.88	63.2	-28.57	69.36	1.2333	-0.5903 335.6	-1 519c	23 519	Mm
34	573	15 475	41.95	61.98	-33.74	70.57	1.2483	-0.6516 331.4	-1 527c	25 527	
35	578	15 480	38.5	60.84	-36.57	70.99	1.2893	-0.7099 328.9	-1 532c	26 532	
37	587	17 485	33.98	53.54	-45.12	70.02	1.2874	-0.861 319.8	-1 544c	28 544	
44	620	18 490	20.43	21.35	-57.83	61.65	1.0751	-1.4618 290.2	-1 561c	32 561	
-1 495c	19 495	15.48	-3.55	-63.13	63.23	0.5652	-1.9609 266.7	12 463	33 568	min	
-1 500c	20 500	16.92	-6.55	-62.9	63.24	0.5023	-1.8165 264.0	13 466	33 569		
-1 510c	22 510	20.93	-14.37	-60.86	62.54	0.3825	-1.4926 256.7	14 471	34 571		
-1 519c	23 520	23.56	-19.11	-59.08	62.09	0.3328	-1.3327 252.0	14 473	34 572	Bm	
-1 529c	25 530	30.04	-29.61	-54.22	61.78	0.2629	-1.0518 241.3	15 477	35 575		
-1 539c	27 540	37.64	-40.05	-48.21	62.68	0.2316	-0.8422 230.2	16 480	35 579		
-1 544c	28 545	41.66	-44.78	-44.97	63.46	0.2273	-0.7615 225.1	16 481	36 581		
-1 549c	29 550	45.8	-49.03	-41.6	64.31	0.229	-0.6931 220.3	16 483	36 583		
-1 554c	30 555	49.98	-52.65	-38.19	65.04	0.2358	-0.6355 215.9	16 484	37 585		
-1 560c	32 560	58.14	-57.44	-31.49	65.51	0.262	-0.5465 208.7	17 486	38 590		
W0	380	770	90.0	0.0	0.0	0.0	0.6572	-0.3298 0.0	$B_c=1,000$		
N0	380	770	3.6	0.0	0.0	0.0	0.6572	-0.3298 0.0	$x_c=0,110$		

see similar files: <http://farbe.li.tu-berlin.de/AEU8/AEU8.HTM>
 technical information: <http://farbe.li.tu-berlin.de> or <http://130.149.60.45/~farbmetrik>

TUB registration: 20201101-AEU8/AEU8LONP.PDF /.PS
 application for evaluation and measurement of display or print output
 TUB material: code=rha4ta