

Eingabe: Farbmatisches Fernseh-Licht-System TL500a

mit g_{p^*} -Daten der vier Gerätefunktionen

(1 0 0)_d = Rot R_d

(1 1 0)_d = Gelb Y_d

(0 1 0)_d = Grün G_d

(0 0 1)_d = Blau B_d



TL500a: adaptierte CIECAM-Data									
L^*	a^*	b^*	C^*	h^*	L^*	a^*	b^*	C^*	h^*
R_{TL500}	50.5	76.92	64.35	100.42	49				
Y_{TL500}	92.65	-20.69	90.75	93.08	103				
G_{TL500}	83.63	-82.75	79.9	115.84	136				
B_{TL500}	86.88	-46.16	-13.55	48.12	196				
R_{TL500}	30.39	76.06	-103.59	128.52	206				
Y_{TL500}	57.3	94.35	-58.41	110.97	228				
G_{TL500}	0.01	0.0	0.0	0.0	0				
B_{TL500}	95.41	0.0	0.0	0.0	0				
R_{TL500}	29.92	58.74	27.99	65.87	25				
L_{TL500}	81.26	-2.88	71.52	71.62	92				
G_{TL500}	52.23	-82.41	13.6	44.55	162				
B_{TL500}	30.57	1.41	-85.45	45.49	272				

Ausgabe: Farbmatisches Fernseh-Licht-System TL500a

mit Funktionsnummer

$n = 01$ bis 16

01 = Rot R_d

05 = Gelb Y_d

09 = Grün G_d

13 = Blau B_d



mit Funktionsposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-306:AG40

TL500a: adaptierte CIECAM-Data									
L^*	a^*	b^*	C^*	h^*	L^*	a^*	b^*	C^*	h^*
R_{TL500}	50.5	76.92	64.35	100.42	49				
Y_{TL500}	92.65	-20.69	90.75	93.08	103				
G_{TL500}	83.63	-82.75	79.9	115.84	136				
B_{TL500}	86.88	-46.16	-13.55	48.12	196				
R_{TL500}	30.39	76.06	-103.59	128.52	206				
Y_{TL500}	57.3	94.35	-58.41	110.97	228				
G_{TL500}	0.01	0.0	0.0	0.0	0				
B_{TL500}	95.41	0.0	0.0	0.0	0				
R_{TL500}	29.92	58.74	27.99	65.87	25				
L_{TL500}	81.26	-2.88	71.52	71.62	92				
G_{TL500}	52.23	-82.41	13.6	44.55	162				
B_{TL500}	30.57	1.41	-85.45	45.49	272				

