

Eingabe: Farbmetrisches Fernsch-Licht-System TL500a

mitrgb₂-Daten der vier Gerätefunktionen

(1 0 0)_d = Rot R_d

(1 1 0)_d = Gelb Y_d

(0 1 0)_d = Grün G_d

(0 0 1)_d = Blau B_d



TL500a: adaptierte CIE1931-Daten									
L*	a*	b*	L*	a*	b*	L*	a*	b*	L*
R ₉₀	50.5	76.92	64.35	100.42	40				
Y ₉₀	92.66	-20.69	90.75	93.08	103				
G ₉₀	83.63	-82.75	79.9	115.84	136				
C ₉₀	86.88	-46.16	-13.55	48.12	196				
B ₉₀	30.39	76.06	-103.59	128.52	306				
M ₉₀	57.3	94.75	-58.41	110.97	129				
N ₉₀	0.01	0.0	0.0	0.0	0				
W ₉₀	95.41	0.0	0.0	0.0	0				
R ₂₀₀	29.92	58.74	27.99	65.87	25				
L ₂₀₀	81.26	-2.88	71.56	71.62	92				
G ₂₀₀	52.23	-42.41	13.6	44.55	162				
C ₂₀₀	30.57	1.41	-85.45	45.49	272				

Ausgabe: Farbmetrisches Fernsch-Licht-System TL500a

mit Barrennummer

n= 01 bis 16

01 = Rot R_d

05 = Gelb Y_d

09 = Grün G_d

13 = Blau B_d

mit Barrenposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-304:AG40



TL500a: adaptierte CIE1931-Daten									
L*	a*	b*	L*	a*	b*	L*	a*	b*	L*
R ₉₀	50.5	76.92	64.35	100.42	40				
Y ₉₀	92.66	-20.69	90.75	93.08	103				
G ₉₀	83.63	-82.75	79.9	115.84	136				
C ₉₀	86.88	-46.16	-13.55	48.12	196				
B ₉₀	30.39	76.06	-103.59	128.52	306				
M ₉₀	57.3	94.75	-58.41	110.97	129				
N ₉₀	0.01	0.0	0.0	0.0	0				
W ₉₀	95.41	0.0	0.0	0.0	0				
R ₂₀₀	29.92	58.74	27.99	65.87	25				
L ₂₀₀	81.26	-2.88	71.56	71.62	92				
G ₂₀₀	52.23	-42.41	13.6	44.55	162				
C ₂₀₀	30.57	1.41	-85.45	45.49	272				

