


Eingabe: Farbmimetrisches Formate-Licht-System TLS900


mit RGB-Daten der vier Elementarfarbtöne:
 (1.0.0)g = Rot R_d
 (1.1.0)g = Gelb T_d
 (0.1.0)g = Grün G_d
 (0.0.1)g = Blau B_d



ISO900 adaptierte CIE1976-Daten L^* , a^* , b^* , h^* , C_{abs} , k^*					
Rd	30.5	76.92	64.55	100.42	40
Td	92.68	-28.69	90.75	93.08	100
Gd	83.63	-83.73	76.9	115.04	136
Bd	86.88	-46.16	-13.55	68.12	196
Rd	30.39	36.08	-203.59	128.52	306
Td	57.1	94.35	-38.81	116.97	125
Gd	94.01	0.0	0.0	0.0	0
Bd	85.81	0.0	0.0	0.0	0
Rd	39.92	28.74	27.99	65.07	25
Td	81.26	-2.88	71.56	71.62	92
Gd	82.23	-42.41	13.6	64.55	162
Bd	30.57	1.41	-45.05	65.49	271

Ausgabe: Farbmimetrisches Formate-Licht-System TL900

mit Raumnummer
n= 01 bis 16



ISO900 adaptierte CIE1976-Daten L^* , a^* , b^* , h^* , C_{abs} , k^*					
Rd	30.5	76.92	64.55	100.42	40
Td	92.68	-28.69	90.75	93.08	100
Gd	83.63	-82.73	76.9	115.04	136
Bd	86.88	-46.16	-13.55	68.12	196
Rd	30.39	36.08	-203.59	128.52	306
Td	57.1	94.35	-38.81	116.97	125
Gd	94.01	0.0	0.0	0.0	0
Bd	85.81	0.0	0.0	0.0	0
Rd	39.92	28.74	27.99	65.07	25
Td	81.26	-2.88	71.56	71.62	92
Gd	82.23	-42.41	13.6	64.55	162
Bd	30.57	1.41	-45.05	65.49	271

mit Raumpositionen
(Zeile und Spalte)
von Prüffolie ISO 9241-306:AG49

