

Eingabe: Farbmétrisches Fernseh-Licht-System TL500a

mitrgb₀-Daten der vier Elementarstrahlungen

(1 0 0)₀ = Rot R₀

(1 1 0)₀ = Gelb Y₀

(0 1 0)₀ = Grün G₀

(0 0 1)₀ = Blau B₀



Die rgb₀-Daten sind berechnet für Ausgabe im Normalfeld nach ISO/IEC 15775

TL500a adaptierte CIE1931-Daten									
L*	a*	b*	C _{98,0.2}	b ₉₈	L*	a*	b*	C _{98,0.2}	b ₉₈
R ₀₀	50.5	76.92	64.55	100.42	00				
Y ₀₀	92.65	-20.69	90.75	93.08	00				
G ₀₀	83.63	-82.75	79.9	115.84	06				
C ₀₀	86.88	-46.16	-13.55	48.12	06				
B ₀₀	30.39	76.05	-103.59	120.52	06				
M ₀₀	57.3	94.75	-58.41	110.97	09				
R ₀₁	0.01	0.0	0.0	0.0	0				
Y ₀₁	95.41	0.0	0.0	0.0	0				
G ₀₁	81.26	-2.88	71.56	71.62	00				
C ₀₁	82.23	-42.41	13.6	44.55	02				
B ₀₁	30.57	1.41	-85.45	85.45	07				

Ausgabe: Farbmétrisches Fernseh-Licht-System TL500a

mit Baritznummer

n= 01 bis 16

01 = Rot R₀

05 = Gelb Y₀

09 = Grün G₀

13 = Blau B₀



mit Baritzposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-304:AG40

TL500a adaptierte CIE1931-Daten									
L*	a*	b*	C _{98,0.2}	b ₉₈	L*	a*	b*	C _{98,0.2}	b ₉₈
R ₀₀	50.5	76.92	64.55	100.42	00				
Y ₀₀	92.65	-20.69	90.75	93.08	00				
G ₀₀	83.63	-82.75	79.9	115.84	06				
C ₀₀	86.88	-46.16	-13.55	48.12	06				
B ₀₀	30.39	76.05	-103.59	120.52	06				
M ₀₀	57.3	94.75	-58.41	110.97	09				
R ₀₁	0.01	0.0	0.0	0.0	0				
Y ₀₁	95.41	0.0	0.0	0.0	0				
G ₀₁	81.26	-2.88	71.56	71.62	00				
C ₀₁	82.23	-42.41	13.6	44.55	02				
B ₀₁	30.57	1.41	-85.45	85.45	07				

