

Eingabe: Farbmetrisches Fernseh-Licht-System TL500a

mitrgb₀-Daten der vier Elementarstrahlung

(1 0 0)₀ = Rot R₀

(1 1 0)₀ = Gelb Y₀

(0 1 0)₀ = Grün G₀

(0 0 1)₀ = Blau B₀



Die rgb₀-Daten sind berechnet für Ausgabe
im Normalfeld nach ISO/IEC 15775

TL500a: adaptierte CIE1931-Daten									
L*	a*	b*	C*	h _{cb}	L*	a*	b*	C*	h _{cb}
R ₀₀	50.5	76.92	64.55	100.42	00				
Y ₀₀	92.65	-20.69	90.75	93.08	103				
G ₀₀	83.63	-82.75	79.9	115.84	136				
C ₀₀	86.88	-46.16	-13.55	48.12	196				
B ₀₀	30.39	76.05	-103.59	128.52	206				
M ₀₀	57.3	94.75	-58.41	110.97	128				
N ₀₀	0.01	0.0	0.0	0.0	0				
W ₀₀	95.41	0.0	0.0	0.0	0				
C ₀₀₀	39.92	58.74	27.99	65.87	25				
L ₀₀₀	81.26	-2.88	71.56	71.62	92				
C ₀₀₀	52.23	-82.41	13.6	44.55	162				
h ₀₀₀	30.57	1.41	-85.85	45.49	272				

Ausgabe: Farbmetrisches Fernseh-Licht-System TL500a

mit Farbnr.nummer

n= 01 bis 16

01 = Rot R₀

05 = Gelb Y₀

09 = Grün G₀

13 = Blau B₀



mit Farbzugsposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-306:AG40

TL500a: adaptierte CIE1931-Daten									
L*	a*	b*	C*	h _{cb}	L*	a*	b*	C*	h _{cb}
R ₀₀	50.5	76.92	64.55	100.42	00				
Y ₀₀	92.65	-20.69	90.75	93.08	103				
G ₀₀	83.63	-82.75	79.9	115.84	136				
C ₀₀	86.88	-46.16	-13.55	48.12	196				
B ₀₀	30.39	76.05	-103.59	128.52	206				
M ₀₀	57.3	94.75	-58.41	110.97	128				
N ₀₀	0.01	0.0	0.0	0.0	0				
W ₀₀	95.41	0.0	0.0	0.0	0				
C ₀₀₀	39.92	58.74	27.99	65.87	25				
L ₀₀₀	81.26	-2.88	71.56	71.62	92				
C ₀₀₀	52.23	-82.41	13.6	44.55	162				
h ₀₀₀	30.57	1.41	-85.85	45.49	272				

