

Eingabe: Farbmetrisches Fernseh-Licht-System TL500a

mit rgb-Daten der
vier Gerätefunktionen

(1 0 0)_d = Rot R_d

(1 1 0)_d = Gelb Y_d

(0 1 0)_d = Grün G_d

(0 0 1)_d = Blau B_d



TL500a: adaptierte CIE1931-Daten					
L*	a*	b*	C _{94,00}	M _{94,00}	S _{94,00}
R _{94,d} 50.5	76.92	64.55	100.42	49	
Y _{94,d} 92.66	-20.69	90.75	93.08	103	
G _{94,d} 83.63	-82.75	79.9	115.84	136	
B _{94,d} 86.88	-46.36	-13.55	48.12	196	
R _{94,s} 30.39	76.06	-103.59	128.52	306	
Y _{94,s} 57.3	94.75	-58.41	110.97	129	
G _{94,s} 0.01	0.0	0.0	0.0	0	
B _{94,s} 95.41	0.0	0.0	0.0	0	
R _{94,m} 39.92	58.74	27.99	65.87	25	
G _{94,m} 81.26	-2.88	71.56	71.62	92	
B _{94,m} 52.23	-42.41	13.6	44.55	162	
R _{94,v} 30.57	1.41	-45.45	45.45	273	

Ausgabe: Farbmetrisches Fernseh-Licht-System TL500a

mit Funktionsnummer

n= 01 bis 32

01 = Rot R_d

09 = Gelb Y_d

17 = Grün G_d

25 = Blau B_d

mit Funktionsposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-304:AG40



TL500a: adaptierte CIE1931-Daten					
L*	a*	b*	C _{94,00}	M _{94,00}	S _{94,00}
R _{94,d} 50.5	76.92	64.55	100.42	49	
Y _{94,d} 92.66	-20.69	90.75	93.08	103	
G _{94,d} 83.63	-82.75	79.9	115.84	136	
B _{94,d} 86.88	-46.36	-13.55	48.12	196	
R _{94,s} 30.39	76.06	-103.59	128.52	306	
Y _{94,s} 57.3	94.75	-58.41	110.97	129	
G _{94,s} 0.01	0.0	0.0	0.0	0	
B _{94,s} 95.41	0.0	0.0	0.0	0	
R _{94,m} 39.92	58.74	27.99	65.87	25	
G _{94,m} 81.26	-2.88	71.56	71.62	92	
B _{94,m} 52.23	-42.41	13.6	44.55	162	
R _{94,v} 30.57	1.41	-45.45	45.45	273	

