



see similar files: <http://farbe.li.tu-berlin.de/BEB1/BEB1LONI.TXT> /PS  
 technical information: <http://farbe.li.tu-berlin.de> or <http://color.li.tu-berlin.de>

TUB registration: 20221101-BEB1/BEB1LONI.TXT /PS  
 application for evaluation and measurement of display or print output  
 TUB material: code=madta

Ostwald optimal colours (o), maximum (m) $C_{AB}$ for D65, $Y_N=3.6$ , $Y_W=90$ , $Y_M=520.770$															
$i_1$	$\lambda_1$	$i_2$	$\lambda_2$	X	Y	Z	x	y	z	$h_{xy}$	$i_d$	$\lambda_d$	$i_c$	$\lambda_c$	Code
0	405	32	561	28.34	48.4	87.6	0.1724	0.2945	0.533	193.8	16	483	37	589	Cm
6	435	32	562	25.69	48.95	72.52	0.1746	0.3326	0.4927	178.5	17	486	42	610	
10	450	32	563	21.01	49.59	44.52	0.1829	0.4317	0.3852	141.6	19	496	-1	496c	
12	460	33	565	19.15	49.94	29.98	0.1933	0.504	0.3026	124.2	21	505	-1	505c	
12	465	33	567	20.12	51.15	29.99	0.1987	0.5051	0.2961	122.8	21	506	-1	506c	
14	470	33	569	19.94	52.23	19.06	0.2186	0.5724	0.2089	111.1	24	520	-1	520c	
15	475	34	573	21.65	54.1	15.12	0.2382	0.5953	0.1664	105.6	25	528	-1	528c	Gm
16	480	36	580	25.4	57.45	12.12	0.2674	0.6048	0.1276	99.2	27	537	-1	537c	
17	485	39	595	35.62	64.35	9.93	0.3241	0.5855	0.0903	87.4	29	548	-1	548c	
18	490	-1	490c	63.02	76.18	8.3	0.4272	0.5164	0.0562	58.5	33	565	11	459	max
19	495	-1	495c	62.98	75.01	7.04	0.4342	0.5171	0.0485	57.1	33	566	12	462	
20	500	-1	500c	62.97	73.55	6.07	0.4416	0.5158	0.0425	55.3	33	567	12	464	
22	510	-1	510c	62.87	69.55	4.8	0.4581	0.5068	0.035	50.6	33	569	13	469	
23	520	-1	519c	62.69	66.99	4.43	0.4674	0.4995	0.033	47.7	34	570	14	471	Ym
25	530	-1	529c	61.81	60.81	3.97	0.4882	0.4803	0.0314	40.7	34	573	15	475	
27	540	-1	539c	60.05	53.7	3.73	0.511	0.4571	0.0318	32.8	35	577	15	478	
28	545	-1	544c	58.8	49.99	3.67	0.5228	0.4445	0.0326	28.7	35	579	15	479	
29	550	-1	549c	57.28	46.21	3.62	0.5347	0.4313	0.0338	24.7	36	582	16	480	
30	555	-1	554c	55.49	42.43	3.6	0.5465	0.4179	0.0354	20.8	36	584	16	481	
32	560	-1	560c	51.12	35.12	3.57	0.5691	0.391	0.0397	13.6	37	589	16	483	
32	561	0	405	57.19	41.59	10.39	0.5238	0.3809	0.0951	13.8	37	589	16	483	Rm
32	562	6	435	59.84	41.04	25.47	0.4735	0.3248	0.2016	358.8	42	610	17	486	
32	563	10	450	64.52	40.4	53.74	0.4066	0.2546	0.3387	321.6	-1	496c	19	496	
33	565	12	460	66.38	40.05	68.01	0.3805	0.2295	0.3988	304.3	-1	505c	21	505	
33	567	12	465	65.41	38.84	68.01	0.3797	0.2254	0.3947	302.9	-1	506c	21	506	
33	569	14	470	65.59	37.76	78.93	0.3598	0.2071	0.433	291.1	-1	520c	24	520	
34	573	15	475	63.88	35.89	82.87	0.3497	0.1964	0.4537	285.6	-1	528c	25	528	Mm
36	580	16	480	60.13	32.54	85.87	0.3367	0.1822	0.4809	279.3	-1	537c	27	537	
39	595	17	485	49.91	25.48	88.06	0.305	0.1567	0.5382	267.4	-1	548c	29	548	
-1	490c	18	490	22.51	13.81	89.7	0.1786	0.1096	0.7117	238.5	11	459	33	565	min
-1	495c	19	495	22.55	14.98	90.95	0.1755	0.1166	0.7078	237.1	12	462	33	566	
-1	500c	20	500	22.56	16.44	91.92	0.1723	0.1256	0.702	235.4	12	464	33	567	
-1	510c	22	510	22.66	20.44	93.19	0.1662	0.1499	0.6837	230.7	13	469	33	569	
-1	519c	23	520	22.84	23.0	93.56	0.1638	0.165	0.6711	227.7	14	471	34	570	Bm
-1	529c	25	530	23.72	29.18	94.02	0.1614	0.1986	0.6399	220.7	15	475	34	573	
-1	539c	27	540	25.48	36.29	94.26	0.1633	0.2325	0.604	212.8	15	478	35	577	
-1	544c	28	545	26.73	40.0	94.33	0.1659	0.2483	0.5856	208.8	15	479	35	579	
-1	549c	29	550	28.25	43.78	94.37	0.1697	0.2631	0.567	204.7	16	480	36	582	
-1	554c	30	555	30.04	47.56	94.4	0.1746	0.2765	0.5488	200.8	16	481	36	584	
-1	560c	32	560	34.41	54.87	94.43	0.1873	0.2986	0.5139	193.6	16	483	37	589	
W0	380	770	85.53	90.0	98.0	0.3127	0.329	0.3582	0.0						
N0	380	770	3.42	3.6	3.92	0.3127	0.329	0.3582	0.0						

Ostwald optimal colours (o), maximum (m) $C_{AB}$ for D65, $Y_N=3.6$ , $Y_W=90$ , $Y_M=520.770$															
$i_1$	$\lambda_1$	$i_2$	$\lambda_2$	Y	A	B	$C_{AB}$	b	$h_{xy}$	$i_d$	$\lambda_d$	$i_c$	$\lambda_c$	Code	
0	405	32	561	48.4	-44.14	-34.88	56.26	0.5853	-0.7237	218.3	16	483	37	589	Cm
6	435	32	562	48.95	-52.06	-19.21	55.49	0.5247	-0.5924	200.2	17	486	42	610	
10	450	32	563	49.59	-65.28	9.74	66.0	0.4236	-0.3568	171.5	19	496	-1	496c	
12	460	33	565	49.94	-70.75	24.38	74.84	0.3834	-0.2401	160.9	21	505	-1	505c	
12	465	33	567	51.15	-71.21	25.7	75.7	0.3933	-0.2344	160.1	21	506	-1	506c	
14	470	33	569	52.23	-74.21	37.79	83.28	0.3818	-0.146	153.0	24	520	-1	520c	
15	475	34	573	54.1	-74.41	43.77	86.33	0.4	-0.1118	149.5	25	528	-1	528c	Gm
16	480	36	580	57.45	-72.95	50.41	88.68	0.4421	-0.0844	145.3	27	537	-1	537c	
17	485	39	595	64.35	-63.82	60.12	87.69	0.5534	-0.0617	136.7	29	548	-1	548c	
18	490	-1	490c	76.18	-23.43	74.63	78.22	0.8271	-0.0435	107.4	33	565	11	459	max
19	495	-1	495c	75.01	-20.75	74.61	77.45	0.8394	-0.0375	105.5	33	566	12	462	
20	500	-1	500c	73.55	-17.31	73.99	75.99	0.8559	-0.033	103.1	33	567	12	464	
22	510	-1	510c	69.55	-8.06	70.91	71.36	0.9037	-0.0276	96.5	33	569	13	469	
23	520	-1	519c	66.99	-2.43	68.49	68.54	0.9356	-0.0264	92.0	34	570	14	471	Ym
25	530	-1	529c	60.81	10.04	62.23	63.03	1.0161	-0.0261	80.8	34	573	15	475	
27	540	-1	539c	53.7	22.51	54.73	59.18	1.1178	-0.0276	67.6	35	577	15	478	
28	545	-1	544c	49.99	28.21	50.75	58.06	1.1758	-0.0293	60.9	35	579	15	479	
29	550	-1	549c	46.21	33.39	46.68	57.39	1.2392	-0.0314	54.4	36	582	16	480	
30	555	-1	554c	42.43	37.9	42.59	57.01	1.3074	-0.0339	48.3	36	584	16	481	
32	560	-1	560c	35.12	44.32	34.66	56.27	1.4548	-0.0406	38.0	37	589	16	483	
32	561	0	405	41.59	44.15	34.88	56.27	1.3747	-0.0999	38.3	37	589	16	483	Rm
32	562	6	435	41.04	52.06	19.21	55.49	1.4575	-0.2481	20.2	42	610	17	486	
32	563	10	450	40.4	65.27	-9.74	65.99	1.5963	-0.5318	35.15	-1	496c	19	496	
33	565	12	460	40.05	70.74	-24.38	74.82	1.6566	-0.6789	34.09	-1	505c	21	505	
33	567	12	465	38.84	71.19	-25.69	75.68	1.6832	-0.7	34.01	-1	506c	21	506	
33	569	14	470	37.76	74.18	-37.78	83.25	1.7359	-0.8356	33.30	-1	520c	24	520	
34	573	15	475	35.89	74.38	-43.76	86.3	1.7791	-0.9231	32.95	-1	528c	25	528	Mm
36	580	16	480	32.54	72.92	-50.39	88.64	1.8464	-1.0547	32.53	-1	537c	27	537	
39	595	17	485	25.48	63.8	-60.31	87.65	1.9454	-1.373	31.67	-1	548c	29	548	
-1	490c	18	490	13.81	23.41	-74.58	78.16	1.6281	-2.5947	28.74	11	459	33	565	min
-1	495c	19	495	14.98	20.74	-74.56	77.39	1.5038	-2.4259	28.55	12	462	33	566	
-1	500c	20	500	16.44	17.3	-73.95	75.94	1.3709	-2.2338	28.31	12	464	33	567	
-1	510c	22	510	20.44	8.05	-70.87	71.33	1.1078	-1.822	27.64	13	469	33	569	
-1	519c	23	520	23.0	2.43	-68.46	68.51	0.9924	-1.6259	27.20	14	471	34	570	Bm
-1	529c	25	530	29.18	-10.03	-62.21	63.01	0.8125	-1.2882	26.08	15	475	34	573	
-1	539c	27	540	36.29	-22.5	-54.72	59.16	0.702	-1.0385	24.76	15	478	35	577	
-1	544c	28	545	40.0	-28.2	-50.74	58.05	0.6681	-0.9428	24.09	15	479	35	579	
-1	549c	29	550	43.78	-33.39	-46.67	57.38	0.645	-0.8618	23.44	16	480	36	582	
-1	554c	30	555	47.56	-37.89	-42.58	57.0	0.6314	-0.7935	22.83	16	481	36	584	