

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/BGB5/BGB5.HTM>
Technische Information: <http://farbe.li.tu-berlin.de> oder <http://color.li.tu-berlin.de>

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für A00, Y _N =3,6, Y _W =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y	A ₁	B ₁	CA1B1	a ₁	b ₁	h _{xy,1}	i _d , λ _d	i _c , λ _c	Code			
1 405	34 574	45.93	-59.57	-12.24	60.82	0.3094	-0.2489	191.6	18 494	39 599	Cm			
6 435	34 574	46.09	-60.23	-8.5	60.83	0.3056	-0.2161	188.0	19 496	42 612				
9 450	34 574	46.35	-61.04	-2.79	61.11	0.3015	-0.1664	182.6	20 501	-1 501c				
12 460	35 575	46.0	-61.33	3.74	61.44	0.295	-0.1097	176.5	21 508	-1 508c				
13 465	35 575	46.26	-61.2	5.94	61.49	0.2991	-0.0909	174.4	22 512	-1 512c				
13 470	35 576	46.86	-61.21	6.15	61.51	0.3058	-0.0897	174.2	22 513	-1 513c				
14 475	35 577	47.65	-60.91	8.27	61.47	0.3169	-0.0727	172.2	23 519	-1 519c	Gm			
16 480	35 579	48.7	-59.74	11.48	60.83	0.3376	-0.0479	169.1	26 533	-1 533c				
17 485	36 582	50.33	-58.25	13.07	59.7	0.3653	-0.0383	167.3	28 540	-1 540c				
18 490	37 588	53.85	-54.96	15.14	57.01	0.42	-0.0298	164.5	29 548	-1 548c				
19 495	40 601	61.06	-44.1	18.35	47.76	0.5394	-0.022	157.4	31 559	-1 559c				
20 500	-1 500c	77.63	5.72	24.77	25.42	0.8578	-0.0146	76.9	35 576	13 469	max			
21 510	-1 509c	76.57	8.29	24.82	26.17	0.8716	-0.0126	71.5	35 576	14 472				
24 520	-1 520c	71.52	19.47	23.77	30.73	0.9372	-0.0093	50.6	35 579	16 480	Ym			
26 530	-1 530c	66.62	28.9	22.27	36.49	1.0018	-0.0085	37.6	36 582	16 484				
28 540	-1 540c	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37 585	17 487				
28 545	-1 544c	60.72	38.73	20.3	43.73	1.0834	-0.0085	27.6	37 585	17 487				
29 550	-1 549c	57.48	43.44	19.18	47.49	1.1306	-0.0087	23.8	37 586	17 489				
31 555	-1 555c	50.54	51.76	16.76	54.41	1.2379	-0.0096	17.9	38 590	18 491				
32 560	-1 560c	46.93	55.05	15.48	57.19	1.2975	-0.0102	15.7	38 593	18 492				
34 574	1 405	44.06	59.57	12.24	60.81	1.369	-0.0311	11.6	39 599	18 494	Rm			
34 574	6 435	43.9	60.23	8.5	60.83	1.3771	-0.0647	8.0	42 612	19 496				
34 574	9 450	43.64	61.04	2.79	61.1	1.3877	-0.1166	2.6	-1 501c	20 501				
35 575	12 460	43.99	61.32	-3.74	61.44	1.3858	-0.1763	356.5	-1 508c	21 508				
35 575	13 465	43.73	61.19	-5.94	61.48	1.388	-0.1966	354.4	-1 512c	22 512				
35 576	13 470	43.13	61.2	-6.15	61.5	1.3958	-0.1993	354.2	-1 513c	22 513				
35 577	14 475	42.34	60.9	-8.27	61.46	1.4036	-0.2204	352.2	-1 519c	23 519	Mm			
35 579	16 480	41.29	59.73	-11.48	60.82	1.4069	-0.2535	349.1	-1 533c	26 533				
36 582	17 485	39.66	58.24	-13.07	59.69	1.4155	-0.2741	347.3	-1 540c	28 540				
37 588	18 490	36.14	54.95	-15.13	57.0	1.4364	-0.3098	344.5	-1 548c	29 548				
40 601	19 495	28.93	44.09	-18.34	47.75	1.4379	-0.3959	337.4	-1 559c	31 559				
-1 500c	20 500	12.36	-5.72	-24.76	25.41	0.6431	-0.9436	256.9	13 469	35 576	min			
-1 509c	21 510	13.42	-8.29	-24.81	26.16	0.581	-0.8819	251.5	14 472	35 576				
-1 520c	24 520	18.47	-19.47	-23.77	30.72	0.4067	-0.6569	230.6	16 480	35 579	Bm			
-1 530c	26 530	23.37	-28.9	-22.27	36.49	0.3337	-0.5233	217.6	16 484	36 582				
-1 540c	28 540	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17 487	37 585				
-1 544c	28 545	29.27	-38.72	-20.3	43.72	0.299	-0.4197	207.6	17 487	37 585				
-1 549c	29 550	32.51	-43.44	-19.18	47.49	0.2938	-0.3783	203.8	17 489	37 586				
-1 555c	31 555	39.45	-51.76	-16.76	54.41	0.3034	-0.3122	197.9	18 491	38 590				
-1 560c	32 560	43.06	-55.06	-15.48	57.19	0.3169	-0.2861	195.7	18 492	38 593				
W0	380	770	89.99	0.0	0.0	0.0	0.8283	-0.1422	0.0	B _c =1,000				
N0	380	770	3.59	0.0	0.0	0.0	0.8283	-0.1422	0.0	x _c =0,110				

BGB50-7N

BGB51-7N

TUB-Registrierung: 20221101-BGB5/BGB5L0NA.TXT /PS TUB-Material: Code=rha4ta
Anwendung für Beurteilung und Messung von Display- oder Druck-Ausgabe