

$\log [(\Delta Y/Y) / (\Delta Y/Y)_u]$

IECsRGBu0 relative

Normfarbwertempfindlichkeit

$Y_{nc} = L^*_{wRGBnc} = 100, 52, 87, 31$

$S_r/S_{ru} = (\Delta Y/Y) / (\Delta Y/Y)_u$

$L^*_{IECsRGBu0} = 50 (Y/Y_u)^{1/2,4} \quad (Y_u = 18, Y_{nc}/100 < Y \leq Y_{nc})$

$\log[(dY/Y)/(dY/Y)_u] = - (1/2,4) \log(Y/Y_u)$

2
100

$(dY/Y)_{90}/(dY/Y)_u = 0,51, \gamma = 2,4, 1/\gamma = 1/2,4 = 0,41$

$(dY/Y)_{18}/(dY/Y)_u = 1,00, S_n = 50,00, D_n = -0,00$

$(dY/Y)_{3,6}/(dY/Y)_u = 1,95, Y_u = 18, dY_u = 4,80$

Anwendungsbereich

1
10

$\log[(dY/Y)/(dY/Y)_u] = 0, m_u = -0,41$

$L^*_u = 50, dY_u = 4,80, dY_u/Y_u = 0,2666$

-1
-2
0,1
1
10
100
Y
log(Y)
 $Y_N = 3,6$
 $Y_W = 90$