

$$\log [(\Delta Y/Y) / (\Delta Y/Y)_u]$$

IECsRGBu5 relative

Normfarbwertempfindlichkeit

$$Y_{nc} = L^*_{wRGBnc} = 100, 52, 87, 31$$

$$S_r/S_{ru} = (\Delta Y/Y) / (\Delta Y/Y)_u$$

2 100

$$T^*_{IECsRGBu5} = 50 (Y/Y_u)^{1/2,4} \quad (Y_u = 18, Y_{nc}/100 < Y \leq Y_{nc})$$

$$\log[(dY/Y)/(dY/Y)_u] = - (1/2,4) \log(Y/Y_u)$$

1 10

$$(dY/Y)_{90}/(dY/Y)_u = 0,51, \gamma = 2,4, 1/\gamma = 1/2,4 = 0,41$$

$$(dY/Y)_{18}/(dY/Y)_u = 1,00, S_n = 50,00, D_n = -0,00$$

$$(dY/Y)_{3,6}/(dY/Y)_u = 1,95, Y_u = 18, dY_u = 4,80$$

Anwendungsbereich

0 1

$$\log[(dY/Y)/(dY/Y)_u] = 0, m_u = -0,41$$

$$T^*_u = 50, dY_u = 4,80, dY_u/Y_u = 0,2666$$

0,1

1

10

100

$Y_u = 18$

Y

-1

-1

0

1

2

$Y_N = 3,6$

$Y_W = 90$

$\log(Y)$