

$\log(\Delta Y/Y)$

IECsRGBu6

Normfarbwertempfindlichkeit

$Y_{nc} = Y_{WRGBnc} = 100, 21, 72, 7$

$S_r = (\Delta Y/Y)$

2 100

$t^*_{IECsRGBu6} = 50 (Y/Y_u)^{1/2,4} (Y_u = 18, Y_{nc}/100 < Y \leq Y_{nc})$

$\log(dY/Y) = \log[2,4(Y_u/50)] - (1/2,4) \log(Y/Y_u)$

$= (1/2,4) \log[2,4(Y_u/50)] - (1/2,4) \log(Y)$

1 10

$\log(dY/Y) = -0,57, m_s = -0,41$

$t^*_u = 50, dY_u = 4,80, dY_u/Y_u = 0,2666$

Anwendungsbereich

0 1

$(dY/Y)_{90} = 0,1363, \gamma = 2,4, 1/\gamma = 1/2,4 = 0,41$

$(dY/Y)_{18} = 0,2666, S_n = 50,00, D_n = -0,00$

$(dY/Y)_{3,6} = 0,5202, Y_u = 18, dY_u = 4,80$

0,1

1

10

100

$Y_u = 18$

Y

-1

0

1

2

$Y_N = 3,6$ $Y_W = 90$ $\log(Y)$