

Ostwald optimal colours (o) of maximum (m) C_{AB,10} for P60, Y_{w,10}=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀	a* ₁₀	b* ₁₀	C* _{ab,10}	a'10	b'10	h _{ab,10}	i _d , λ _d	i _c , λ _c	Code
1 405	31 557	75.87	−65.41	−32.32	72.96	0.1811	−0.1021	206.2	15 477	37 587	Cm
7 435	31 559	76.14	−87.74	−8.84	88.18	0.169	−0.0895	185.7	16 483	−1 483c	
9 450	32 561	76.57	−98.92	7.82	99.23	0.1631	−0.0807	175.4	17 489	−1 489c	
12 460	32 563	76.94	−111.3	37.86	117.56	0.1566	−0.0648	161.2	21 505	−1 505c	
13 465	33 566	77.74	−110.42	50.03	121.23	0.1576	−0.0585	155.6	22 514	−1 514c	
14 470	34 571	79.3	−104.41	63.41	122.15	0.1617	−0.0521	148.7	24 524	−1 524c	
14 475	36 580	82.53	−90.99	68.98	114.18	0.1704	−0.0503	142.8	26 531	−1 531c	Gm
15 480	41 605	88.6	−53.73	89.54	104.43	0.191	−0.0427	120.9	30 550	−1 550c	
16 485	−1 484c	92.68	−18.78	105.89	107.54	0.2082	−0.0368	100.0	32 561	10 453	
18 490	−1 490c	91.45	−13.82	119.98	120.78	0.2104	−0.0298	96.5	32 563	11 458	max
19 495	−1 495c	90.68	−10.5	125.65	126.09	0.2119	−0.0268	94.7	32 564	12 461	
20 500	−1 500c	89.76	−6.64	130.45	130.62	0.2137	−0.0241	92.9	33 565	12 463	
21 510	−1 509c	88.69	−2.26	134.38	134.4	0.2158	−0.0216	90.9	33 566	12 464	
24 520	−1 520c	84.45	13.53	139.54	140.2	0.2237	−0.0152	84.4	34 571	13 469	Ym
26 530	−1 530c	80.77	25.33	137.01	139.34	0.2301	−0.0113	79.5	34 574	14 472	
28 540	−1 540c	76.43	37.5	131.23	136.48	0.2373	−0.0074	74.0	35 578	14 474	
29 545	−1 545c	74.04	43.46	127.47	134.68	0.2412	−0.0053	71.1	36 581	15 475	
30 550	−1 550c	71.51	49.23	123.26	132.73	0.2452	−0.003	68.2	36 583	15 476	
31 555	−1 555c	68.83	54.71	118.68	130.68	0.2494	0.0	65.2	37 586	15 476	
31 560	8 442	69.56	69.47	4.54	69.61	0.2578	−0.0822	3.7	−1 485c	17 485	
31 557	1 405	76.27	48.55	57.02	74.89	0.2434	−0.0544	49.5	37 587	15 477	Rm
31 559	7 435	76.0	60.34	9.99	61.16	0.2499	−0.0795	9.4	−1 483c	16 483	
32 561	9 450	75.56	66.35	−7.27	66.74	0.2534	−0.0887	353.7	−1 489c	17 489	
32 563	12 460	75.18	72.34	−26.17	76.93	0.2568	−0.0989	340.1	−1 505c	21 505	
33 566	13 465	74.33	74.3	−31.93	80.87	0.2583	−0.1022	336.7	−1 514c	22 514	
34 571	14 470	72.6	76.39	−38.29	85.45	0.2603	−0.1061	333.3	−1 524c	24 524	
36 580	14 475	68.54	80.1	−45.28	92.02	0.2646	−0.1112	330.5	−1 531c	26 531	Mm
41 605	15 480	58.68	74.68	−64.8	98.88	0.2673	−0.1275	319.0	−1 550c	30 550	
−1 484c	16 485	49.21	43.14	−82.96	93.51	0.2502	−0.1475	297.4	10 453	32 561	
−1 490c	18 490	52.42	29.95	−79.7	85.14	0.239	−0.1422	290.6	11 458	32 563	min
−1 495c	19 495	54.27	22.02	−77.18	80.26	0.2327	−0.1389	285.9	12 461	32 564	
−1 500c	20 500	56.3	13.42	−74.16	75.37	0.2263	−0.1353	280.2	12 463	33 565	
−1 509c	21 510	58.5	4.39	−70.73	70.87	0.2199	−0.1316	273.5	12 464	33 566	
−1 520c	24 520	65.81	−22.44	−58.7	62.84	0.2031	−0.1201	249.0	13 469	34 571	Bm
−1 530c	26 530	70.84	−36.93	−50.18	62.31	0.1955	−0.1133	233.6	14 472	34 574	
−1 540c	28 540	75.71	−47.2	−41.85	63.08	0.191	−0.1073	221.5	14 474	35 578	
−1 545c	29 545	78.02	−50.53	−37.89	63.16	0.1898	−0.1047	216.8	15 475	36 581	
−1 550c	30 550	80.22	−52.66	−34.09	62.74	0.1894	−0.1023	212.9	15 476	36 583	
−1 555c	31 555	82.32	−53.63	−30.47	61.68	0.1894	−0.1001	209.6	15 476	37 586	
8 442	31 560	81.77	−77.1	−3.3	77.17	0.1772	−0.0865	182.4	17 485	−1 485c	
380	770	95.41	0.0	0.0	0.0	0.2169	−0.0848	0.0			