

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =0, Y _W =100, Y _m =520..770														
l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀	l ₁₁	l ₁₂	l ₁₃	l ₁₄	
1	405	32	564	53.83	73.48	0.1869	0.3438	0.4692	185.2	17	486	38	592	
7	435	33	565	56.01	53.61	0.1892	0.39	0.4207	168.6	18	490	46	631	
10	450	33	566	56.26	54.16	0.1986	0.4625	0.3387	144.6	19	497	-1	497c	
12	460	33	567	57.04	54.86	0.2113	0.5259	0.2626	128.7	21	506	-1	506c	
13	465	33	568	57.01	55.56	0.2208	0.5572	0.2218	122.1	22	512	-1	512c	
14	470	34	570	57.15	56.11	0.2308	0.5846	0.1844	116.9	23	519	-1	519c Gm	
15	475	34	573	57.32	58.04	0.2489	0.6064	0.1469	111.4	25	527	-1	527c	
15	480	35	578	57.41	61.49	0.266	0.5968	0.1371	108.4	26	532	-1	532c	
17	485	37	587	58.39	66.01	0.3109	0.6039	0.0851	98.0	28	544	-1	544c	
18	490	44	620	59.95	79.56	0.407	0.5402	0.0526	71.3	32	561	-1	561c	
19	495	-1	495c	75.28	84.51	0.4525	0.5081	0.0393	54.4	33	568	12	463 max	
20	500	-1	500c	75.26	83.07	0.4591	0.5067	0.034	52.5	33	569	13	466	
22	510	-1	510c	75.16	79.06	0.4741	0.4986	0.0272	47.4	34	571	14	471	
23	520	-1	519c	74.98	76.43	0.4826	0.492	0.0253	44.2	34	572	14	473 Ym	
25	530	-1	529c	74.05	69.95	0.5021	0.4743	0.0234	36.4	35	575	15	477	
27	540	-1	539c	72.16	62.35	0.524	0.4527	0.0232	27.8	35	579	16	480	
28	545	-1	544c	70.81	58.33	0.5353	0.4409	0.0236	23.4	36	581	16	481	
29	550	-1	549c	69.15	54.19	0.5469	0.4286	0.0244	19.1	36	583	16	483	
30	555	-1	554c	67.17	50.01	0.5586	0.4159	0.0254	15.0	37	585	16	484	
32	560	-1	560c	62.28	41.85	0.5812	0.3905	0.0281	7.7	38	590	17	486	
32	564	1	405	67.15	46.16	0.5489	0.3773	0.0736	5.2	38	592	17	486 Rm	
33	565	7	435	70.4	46.38	0.4977	0.3279	0.1743	348.6	46	631	18	490	
33	566	10	450	73.15	45.83	0.452	0.2832	0.2646	324.7	-1	497c	19	497	
33	567	12	460	74.37	45.13	0.4259	0.2585	0.3155	308.7	-1	506c	21	506	
33	568	13	465	74.4	44.43	0.4151	0.2479	0.3368	302.1	-1	512c	22	512	
34	570	14	470	74.26	43.88	0.4059	0.2398	0.3541	296.9	-1	519c	23	519 Mm	
34	573	15	475	72.5	41.95	0.387	0.3965	0.2294	237.9	19.15	-1	527c	25	527
35	578	15	480	69.0	38.5	0.3836	0.3923	0.2189	208.8	19.15	-1	532c	26	532
37	587	17	485	62.42	33.98	0.368	0.2003	0.4315	278.0	-1	544c	28	544	
44	620	18	490	36.46	20.43	0.277	0.1552	0.5677	251.3	-1	561c	32	561	
-1	495c	19	495	21.14	15.48	0.7595	0.1877	0.1375	0.6746	234.2	12	463	33	568 min
-1	500c	20	500	21.15	16.92	0.7691	0.1839	0.1471	0.6688	232.5	13	466	33	569
-1	510c	22	510	21.25	20.93	0.7818	0.1765	0.1739	0.6494	227.5	14	471	34	571
-1	519c	23	520	21.44	23.56	0.7856	0.1735	0.1907	0.6357	224.2	14	473	34	572 Bm
-1	529c	25	530	22.36	30.04	0.7904	0.1701	0.2285	0.6013	216.5	15	477	35	575
-1	539c	27	540	24.25	37.64	0.7929	0.1717	0.2666	0.5615	207.8	16	480	35	579
-1	544c	28	545	25.6	41.66	0.7936	0.1746	0.2841	0.5412	203.5	16	481	36	581
-1	549c	29	550	27.26	45.8	0.7941	0.1788	0.3004	0.5207	199.2	16	483	36	583
-1	554c	30	555	29.24	49.98	0.7944	0.1843	0.315	0.5006	195.0	16	484	37	585
-1	560c	32	560	34.13	58.14	0.7947	0.1987	0.3385	0.4627	187.7	17	486	38	590
W0	380	770	96.42	100.0	82.49	0.3457	0.3585	0.2957	0.0					
N0	380	770	3.85	4.0	3.29	0.3457	0.3585	0.2957	0.0					

CGW7-7N

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =0, Y _W =100, Y _m =520..770														
l ₁	l ₂	l ₃	l ₄	l ₅	l ₆	l ₇	l ₈	l ₉	l ₁₀	l ₁₁	l ₁₂	l ₁₃	l ₁₄	
1	405	32	564	53.83	-56.59	-29.05	63.62	0.5434	-0.5457	207.7	17	486	38	592
7	435	33	565	53.61	-64.17	-13.59	65.6	0.4851	-0.4233	191.9	18	490	46	631
10	450	33	566	54.16	-72.38	50.1	72.56	0.4294	-0.2928	176.0	19	497	-1	497c
12	460	33	567	54.86	-77.11	17.85	79.14	0.4017	-0.1997	166.9	21	506	-1	506c
13	465	33	568	55.56	-78.87	23.7	82.35	0.3961	-0.1592	163.3	22	512	-1	512c
14	470	34	570	56.11	-79.85	28.57	84.81	0.3947	-0.1261	160.2	23	519	-1	519c Gm
15	475	34	573	56.94	-80.09	33.75	86.91	0.41	-0.0973	157.1	25	527	-1	527c
15	480	35	578	57.41	-79.68	36.59	87.68	0.4456	-0.0419	155.3	26	532	-1	532c
17	485	37	587	58.01	-74.12	45.14	86.79	0.5148	-0.0563	148.6	28	544	-1	544c
18	490	44	620	79.56	-41.87	57.86	71.42	0.7534	-0.0389	125.8	32	561	-1	561c
19	495	-1	495c	84.51	-15.51	63.16	65.04	0.8905	-0.0309	103.7	33	568	12	463 max
20	500	-1	500c	83.07	-12.07	62.93	64.08	0.9058	-0.0268	100.8	33	569	13	466
22	510	-1	510c	79.06	-2.65	60.89	60.94	0.9505	-0.0128	92.4	34	571	14	471
23	520	-1	519c	76.43	3.22	59.1	59.18	0.9808	-0.0205	86.8	34	572	14	473 Ym
25	530	-1	529c	69.95	16.52	54.23	56.7	1.0584	-0.0197	73.0	35	575	15	477
27	540	-1	539c	62.35	30.11	48.22	56.85	1.1571	-0.0205	58.0	35	579	16	480
28	545	-1	544c	58.33	36.43	44.97	57.87	1.2137	-0.0214	50.9	36	581	16	481
29	550	-1	549c	54.19	42.24	41.6	59.29	1.2758	-0.0227	44.5	36	583	16	483
30	555	-1	554c	50.01	47.36	38.19	60.84	1.3427	-0.0244	38.8	37	585	16	484
32	560	-1	560c	41.85	54.81	31.49	63.21	1.4878	-0.0288	29.8	38	590	17	486
32	564	1	405	46.16	66.59	29.05	63.62	1.4543	-0.078	27.1	38	592	17	486 Rm
33	565	7	435	46.38	64.17	13.59	65.59	1.5173	-0.1226	11.9	46	631	18	490
33	566	10	450	45.83	72.37	-5.01	72.55	1.5956	-0.3736	356.9	-1	497c	19	497
33	567	12	460	45.13	77.09	-17.84	79.13	1.6471	-0.4481	346.0	-1	506c	21	506
33	568	13	465	44.43	78.85	-23.7	82.33	1.6737	-0.5432	343.2	-1	512c	22	512
34	570	14	470	43.88	79.83	-28.57	84.79	1.6917	-0.5930	340.1	-1	519c	23	519 Mm
34	573	15	475	41.95	80.07	-33.74	86.89	1.7274	-0.6516	337.3	-1	527c	25	527
35	578	15	480	38.5	79.66	-36.57	87.65	1.7916	-0.7099	335.3	-1	532c	26	532
37	587	17	485	33.98	74.1	-45.12	86.76	1.8361	-0.861	328.6	-1	544c	28	544
44	620	18	490	20.43	41.86	-57.83	71.39	1.7832	-1.4618	305.8	-1	561c	32	561
-1	495c	19	495	15.48	15.5	-63.13	65.0	1.3645	-1.9609	283.7	12	463	33	568 min
-1	500c	20	500	16.92	12.07	-62.9	64.04	1.4922	-1.8165	280.8	13	466	33	569
-1	510c	22	510	20.93	2.64	-60.86	60.92	1.0145	-1.4926	272.4	14	471	34	571
-1	519c	23	520	23.56	-3.22	-59.08	59.17	0.9092	-1.3327	266.8	14	473	34	572 Bm
-1	529c	25	530	30.04	-16.51	-54.22	56.68	0.744	-1.0518	253.0	15	477	35	575
-1	539c	27	540	37.64	-30.11	-48.21	56.84	0.644	-0.8422	238.0	16	480	35	579
-1	544c	28	545	41.66	-36.42	-44.97	57.87	0.6142	-0.7615	230.9	16	481	36	581
-1	549c	29	550	45.8	-42.24	-41.6	59.29	0.595	-0.6931	224.5	16	483	36	583
-1	554c	30	555	49.98	-47.36	-38.19	60.84	0.5849	-0.6355	218.8	16	484	37	585
-1	560c	32	560	58.14	-54.81	-31.49	63.21	0.5869	-0.5465	209.8	17	486	38	590
W0	380	770	100.0	0.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	B _c =1,000			
N0	380	770	4.0	0.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	x _c =0,000			

CGW7-7N

0.000100

0.000100