

Ostwald-Optimalfarben (o), maximales (m) C_{AB} für P60, $Y_N=0$, $Y_W=100$, $Y_m=520_770$

i_1, λ_1	i_2, λ_2	Y	A_1	B_1	$C_{AB,1}$	a_1	b_1	$h_{xy,1}$	i_d, λ_d	i_c, λ_c	Code
0 405	32 563	53.56	-55.49	-37.27	66.85	0.2242	-0.6965	213.8	16 483	38 590	Cm
6 435	32 563	54.12	-58.87	-18.04	61.57	0.2036	-0.5515	197.0	17 487	44 621	
10 450	33 565	54.2	-62.77	11.55	63.82	0.1754	-0.3329	169.5	19 497	-1 497c	
11 460	33 566	55.45	-63.36	20.13	66.49	0.1816	-0.2729	162.3	20 502	-1 502c	
13 465	33 568	56.12	-63.45	33.7	71.85	0.1864	-0.1779	152.0	22 513	-1 513c	
14 470	34 570	57.09	-62.96	39.7	74.43	0.1975	-0.1399	147.7	24 521	-1 521c	Gm
15 475	34 574	59.7	-61.44	46.41	76.99	0.227	-0.1072	142.9	25 529	-1 529c	
15 480	36 580	63.87	-59.47	50.76	78.18	0.2662	-0.1002	139.5	27 535	-1 535c	
17 485	39 595	70.8	-46.88	63.39	78.84	0.3738	-0.06	126.4	29 549	-1 549c	
18 490	-1 490c	85.0	-0.59	79.98	79.98	0.6358	-0.0418	90.4	33 566	11 459	max
19 495	-1 495c	83.76	2.0	80.01	80.04	0.6482	-0.036	88.5	33 567	12 461	
20 500	-1 500c	82.2	5.18	79.42	79.59	0.6639	-0.0316	86.2	33 568	12 464	
22 510	-1 510c	77.89	13.38	76.28	77.44	0.7074	-0.0264	80.0	34 570	13 469	
24 520	-1 520c	71.91	23.5	70.72	74.53	0.7694	-0.0247	71.6	34 572	14 473	Ym
25 530	-1 529c	68.43	28.79	67.29	73.19	0.807	-0.0248	66.8	34 574	15 475	
27 540	-1 539c	60.8	38.92	59.57	71.16	0.8947	-0.0262	56.8	35 578	15 478	
29 545	-1 545c	52.69	47.47	51.21	69.83	0.999	-0.0294	47.1	36 582	16 480	
29 550	-1 549c	52.69	47.47	51.21	69.83	0.999	-0.0294	47.1	36 582	16 480	
30 555	-1 554c	48.59	50.83	46.95	69.2	1.0571	-0.0316	42.7	36 584	16 481	
32 560	-1 560c	40.5	55.2	38.52	67.31	1.1839	-0.0376	34.9	37 589	16 483	
32 563	0 405	46.43	55.49	37.27	66.85	1.1167	-0.097	33.8	38 590	16 483	Rm
32 563	6 435	45.87	58.87	18.04	61.57	1.152	-0.2608	17.0	44 621	17 487	
33 565	10 450	45.79	62.76	-11.55	63.81	1.1869	-0.519	349.5	-1 497c	19 497	
33 566	11 460	44.54	63.35	-20.13	66.47	1.2076	-0.5989	342.3	-1 502c	20 502	
33 568	13 465	43.87	63.44	-33.69	71.83	1.217	-0.7253	332.0	-1 513c	22 513	
34 570	14 470	42.9	62.94	-39.69	74.41	1.2255	-0.7882	327.7	-1 521c	24 521	Mm
34 574	15 475	40.29	61.42	-46.39	76.97	1.2483	-0.8786	322.9	-1 529c	25 529	
36 580	15 480	36.12	59.44	-50.74	78.16	1.2969	-0.9799	319.5	-1 535c	27 535	
39 595	17 485	29.19	46.85	-63.36	78.8	1.2808	-1.2864	306.4	-1 549c	29 549	
-1 490c	18 490	14.99	0.59	-79.92	79.92	0.6546	-2.5507	270.4	11 459	33 566	min
-1 495c	19 495	16.23	-2.0	-79.96	79.99	0.5892	-2.3881	268.5	12 461	33 567	
-1 500c	20 500	17.79	-5.17	-79.37	79.54	0.5223	-2.2019	266.2	12 464	33 568	
-1 510c	22 510	22.1	-13.37	-76.24	77.41	0.3966	-1.7979	260.0	13 469	34 570	
-1 520c	24 520	28.08	-23.49	-70.7	74.5	0.304	-1.4253	251.6	14 473	34 572	Bm
-1 529c	25 530	31.56	-28.78	-67.27	73.17	0.2738	-1.2706	246.8	15 475	34 574	
-1 539c	27 540	39.19	-38.91	-59.55	71.14	0.2415	-1.0259	236.8	15 478	35 578	
-1 545c	29 545	47.3	-47.46	-51.2	69.82	0.2372	-0.8511	227.1	16 480	36 582	
-1 549c	29 550	47.3	-47.46	-51.2	69.82	0.2372	-0.8511	227.1	16 480	36 582	
-1 554c	30 555	51.4	-50.83	-46.94	69.19	0.2431	-0.7834	222.7	16 481	36 584	
-1 560c	32 560	59.49	-55.19	-38.52	67.31	0.2676	-0.6771	214.9	16 483	37 589	
W0 380	770	99.99	0.0	0.0	0.0	0.6386	-0.4181	0.0	$B_c=1,000$		
N0 380	770	3.99	0.0	0.0	0.0	0.6386	-0.4181	0.0	$x_c=0,110$		