

http://farbe.li.tu-berlin.de/DEJ2/DEJ2L0N1.TXT /PS; only vector graphic VG; start output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 1/1

see similar files: <http://farbe.li.tu-berlin.de/DEJ2/DEJ2L0N1.TXT>
technical information: <http://farbe.li.tu-berlin.de> or <http://color.li.tu-berlin.de>

Oswald optimal colours (o), maximum (m) CAB_{10} for D65, $Y_N=3.6$, $Y_{W10}=90$, $Y_m=520..770$												
i	λ_i	i_2	λ_{i2}	Y_{10}	$A_{1,10}$	$B_{1,10}$	$CAB_{10,10}$	$b_{1,10}$	$b_{y,1,10}$	$d_{1,10}$	i_c	Code
0	405	31	556	47.1	-47.62	-35.74	59.54	0.2111	-0.7327	216.8	15 476	37 585 Cm
6	435	31	557	47.93	-50.44	-17.05	53.25	0.1946	-0.5715	198.6	16 480	44 621
10	450	31	559	48.21	-52.98	12.08	54.34	0.1759	-0.3289	167.1	18 492	-1 492c
11	460	32	562	49.33	-53.01	20.46	56.82	0.1857	-0.2632	158.8	19 498	-1 498c
12	465	33	565	50.4	-52.67	28.07	59.69	0.1975	-0.2064	151.9	21 506	-1 506c
14	470	34	570	52.1	-49.89	39.97	63.93	0.2325	-0.1223	141.3	24 522	-1 522c
15	475	35	579	56.8	-44.6	48.5	65.89	0.3015	-0.0876	132.5	26 534	-1 534c Gm
16	480	41	606	66.9	-24.01	61.91	66.4	0.472	-0.059	111.2	30 550	-1 550c
16	485	-1	484c	75.01	1.34	70.61	70.62	0.6227	-0.0526	88.9	32 560	10 454
18	490	-1	490c	72.49	6.44	71.04	71.33	0.6511	-0.0372	84.8	32 562	11 459 max
19	495	-1	495c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461
19	500	-1	499c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461
22	510	-1	510c	64.74	20.42	65.21	68.33	0.7417	-0.0263	72.6	33 566	13 466
23	520	-1	519c	62.19	24.38	62.72	67.29	0.7724	-0.0258	68.7	33 568	13 468 Ym
26	530	-1	530c	53.14	35.99	53.41	64.41	0.8865	-0.0271	56.0	34 573	14 472
27	540	-1	539c	49.82	39.36	49.91	63.57	0.9316	-0.0284	51.7	35 576	14 473
28	545	-1	544c	46.42	42.31	46.31	62.73	0.9801	-0.0302	47.5	35 578	14 474
29	550	-1	549c	42.99	44.75	42.64	61.81	1.0319	-0.0324	43.6	36 580	15 475
31	555	-1	555c	36.18	47.74	35.35	59.41	1.1433	-0.0384	36.5	37 586	15 476
32	560	10	451	34.36	52.93	-11.75	54.22	1.2318	-0.566	34.74	-1 491c	18 491
31	556	0	405	42.89	47.63	35.74	59.55	1.0597	-0.0958	36.8	37 585	15 476 Rm
31	557	6	435	42.06	50.44	17.05	53.25	1.0952	-0.267	18.6	44 621	16 480
31	559	10	450	41.78	52.97	-12.08	54.34	1.1227	-0.5448	34.71	-1 492c	18 492
32	562	11	460	40.66	53.0	-20.46	56.81	1.1369	-0.6304	33.88	-1 498c	19 498
33	565	12	465	39.59	52.66	-28.07	59.67	1.1476	-0.7128	33.19	-1 506c	21 506
34	570	14	470	37.89	49.88	-39.95	63.91	1.142	-0.8509	32.13	-1 522c	24 522
35	575	15	475	33.19	44.58	-44.89	65.87	1.1529	-1.0135	31.25	-1 534c	26 534 Mm
41	606	16	480	23.09	24.0	-61.88	66.37	1.0313	-1.5009	29.12	-1 550c	30 550
-1	484c	16	485	14.98	-1.34	-70.56	70.57	0.5796	-2.3126	268.9	10 454	32 560
-1	490c	18	490	17.5	-6.44	-71.0	71.29	0.4682	-2.0519	264.8	11 459	32 562 min
-1	495c	19	495	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563
-1	499c	19	500	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563
-1	510c	22	510	25.25	-20.41	-65.19	68.31	0.2921	-1.4619	252.6	13 466	33 566
-1	519c	23	520	27.8	-24.37	-62.7	67.27	0.2648	-1.3312	248.7	13 468	33 568 Bm
-1	530c	26	530	36.85	-35.98	-53.4	64.39	0.225	-1.0087	236.0	14 472	34 573
-1	539c	27	540	40.17	-39.36	-49.9	63.56	0.2237	-0.926	231.7	14 473	35 576
-1	544c	28	545	43.57	-42.3	-46.3	62.72	0.2271	-0.8543	227.5	14 474	35 578
-1	549c	29	550	47.0	-44.74	-42.63	61.81	0.2348	-0.792	223.6	15 475	36 580
-1	555c	31	555	53.81	-47.74	-35.35	59.4	0.2607	-0.6919	216.5	15 476	37 586
10	451	32	560	55.63	-52.94	-11.75	54.23	0.2349	-0.4447	167.4	18 491	-1 491c
W0	380	770	90.0	0.0	0.0	0.0	0.0	0.6155	-0.4292	0.0	$B_c=1,000$	
N0	380	770	3.6	0.0	0.0	0.0	0.0	0.6155	-0.4292	0.0	$x_c=0,110$	

Oswald optimal colours (o), maximum (m) CAB_{10} for D65, $Y_N=3.6$, $Y_{W10}=90$, $Y_m=520..770$												
i	λ_i	i_2	λ_{i2}	Y_{10}	$A_{2,10}$	$B_{2,10}$	$CAB_{2,10}$	$a_{2,10}$	$b_{2,10}$	$b_{y,2,10}$	i_c	Code
0	405	31	556	47.1	-47.62	-28.59	55.55	0.2111	-0.7327	210.9	15 476	37 585 Cm
6	435	31	557	47.93	-50.44	-13.64	52.26	0.1946	-0.5715	195.1	16 480	44 621
10	450	31	559	48.21	-52.98	9.66	53.86	0.1759	-0.3289	169.6	18 492	-1 492c
11	460	32	562	49.33	-53.01	16.37	55.48	0.1857	-0.2632	162.8	19 498	-1 498c
12	465	33	565	50.4	-52.67	22.46	57.26	0.1975	-0.2064	156.9	21 506	-1 506c
14	470	34	570	52.1	-49.89	31.97	59.26	0.2325	-0.1223	147.3	24 522	-1 522c
15	475	35	579	56.8	-44.6	38.8	59.12	0.3015	-0.0876	138.9	26 534	-1 534c Gm
16	480	41	606	66.9	-24.01	49.52	55.04	0.472	-0.059	111.2	30 550	-1 550c
16	485	-1	484c	75.01	1.34	56.48	56.5	0.6227	-0.0526	88.6	32 560	10 454
18	490	-1	490c	72.49	6.44	56.83	57.2	0.6511	-0.0372	83.5	32 562	11 459 max
19	495	-1	495c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32 563	12 461
19	500	-1	499c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32 563	12 461
22	510	-1	510c	64.74	20.42	52.17	56.02	0.7417	-0.0263	68.6	33 566	13 466
23	520	-1	519c	62.19	24.38	50.17	55.79	0.7724	-0.0258	64.0	33 568	13 468 Ym
26	530	-1	530c	53.14	35.99	42.73	55.87	0.8865	-0.0271	49.8	34 573	14 472
27	540	-1	539c	49.82	39.36	39.93	56.07	0.9316	-0.0284	45.4	35 576	14 473
28	545	-1	544c	46.42	42.31	37.04	56.24	0.9801	-0.0302	41.2	35 578	14 474
29	550	-1	549c	42.99	44.75	34.11	56.27	1.0319	-0.0324	37.3	36 580	15 475
31	555	-1	555c	36.18	47.74	28.28	55.49	1.1433	-0.0384	30.6	37 586	15 476
32	560	10	451	34.36	52.93	-9.4	53.76	1.2318	-0.566	34.99	-1 491c	18 491
31	556	0	405	42.89	47.63	28.59	55.55	1.0597	-0.0958	30.9	37 585	15 476 Rm
31	557	6	435	42.06	50.44	13.64	52.26	1.0952	-0.267	15.1	44 621	16 480
31	559	10	450	41.78	52.97	-9.66	53.85	1.1227	-0.5448	34.96	-1 492c	18 492
32	562	11	460	40.66	53.0	-16.36	55.47	1.1369	-0.6304	34.28	-1 498c	19 498
33	565	12	465	39.59	52.66	-22.45	57.25	1.1476	-0.7128	33.69	-1 506c	21 506
34	570	14	470	37.89	49.88	-31.96	59.24	1.142	-0.8509	32.73	-1 522c	24 522
35	575	15	475	33.19	44.58	-38.79	59.09	1.1529	-1.0135	31.89	-1 534c	26 534 Mm
41	606	16	480	23.09	24.0	-49.45	55.01	1.0313	-1.5009	295.8	-1 550c	30 550
-1	484c	16	485	14.98	-1.34	-56.45	56.46	0.5796	-2.3126	268.6	10 454	32 560
-1	490c	18	490	17.5	-6.44	-56.8	57.17	0.4682	-2.0519	263.5	11 459	32 562 min
-1	495c	19	495	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12 461	32 563
-1	499c	19	500	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12 461	32 563
-1	510c	22	510	25.25	-20.41	-52.15	56.0	0.2921	-1.4619	248.6	13 466	33 566
-1	519c	23	520	27.8	-24.37	-50.16	55.77	0.2648	-1.3312	244.0	13 468	33 568 Bm
-1	530c	26	530	36.85	-35.98	-42.72	55.86	0.225	-1.0087	229.8	14 472	34 573
-1	539c	27	540	40.17	-39.36	-39.92	56.06	0.2237	-0.926	225.4	14 473	35 576
-1	544c	28	545	43.57	-42.3	-37.04	56.23	0.2271	-0.8543	221.2	14 474	35 578
-1	549c	29	550	47.0	-44.74	-34.11	56.26	0.2348	-0.792	217.3	15 475	36 580
-1	555c	31	555	53.81	-47.74	-28.28	55.48	0.2607	-0.6919	210.6	15 476	37 586
10	451	32	560	55.63	-52.94	9.4	53.77	0.2349	-0.3447	169.9	18 491	-1 491c
W0	380	770	90.0	0.0	0.0	0.0	0.0	0.6155	-0.3433	0.0	$B_c=0,800$	
N0	380	770	3.6	0.0	0.0	0.0	0.0	0.6155	-0.3433	0.0	$x_c=0,110$	

TUB-test chart DEJ2; Oswald optimal colours, $Y_N=3.6$, $Y_W=90$, illuminant D65, CIE-02-degree
Table data: $YA_1B_1CAB_1$, $iHAB_1$ and $YA_2B_2CAB_2$, $iHAB_2$ with different wavelength ranges

TUB registration: 20221101-DEJ2/DEJ2L0N1.TXT /PS
application for evaluation and measurement of display or print output
TUB material: code=thadta