

Oswald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =3,6, Y _W =90, Y _m =520_770															
i ₁	λ ₁	i ₂	λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d	λ _d	i _c	λ _c	Code
1	405	32	564	26.33	48.45	66.13	0.1869	0.3438	0.4692	185.2	17	486	38	592	Cm
7	435	33	565	23.41	48.25	52.04	0.1892	0.39	0.4207	168.6	18	490	46	631	
10	450	33	566	20.93	48.75	35.69	0.1986	0.4625	0.3387	144.6	19	497	-1	497c	
12	460	33	567	19.83	49.37	24.66	0.2113	0.5259	0.2626	128.7	21	506	-1	506c	
13	465	33	568	19.81	50.0	19.91	0.2208	0.5572	0.2218	122.1	22	512	-1	512c	
14	470	34	570	19.94	50.5	15.93	0.2308	0.5846	0.1844	116.9	23	519	-1	519c	
15	475	34	573	21.53	52.24	12.71	0.2489	0.604	0.1469	111.4	25	527	-1	527c	Gm
15	480	35	578	24.67	55.34	12.71	0.266	0.5968	0.1371	108.4	26	532	-1	532c	
17	485	37	587	30.59	59.41	8.37	0.3109	0.6039	0.0851	98.0	28	544	-1	544c	
18	490	44	620	53.95	71.6	6.98	0.407	0.5402	0.0526	71.3	32	561	-1	561c	
19	495	-1	495c	67.75	76.06	5.88	0.4525	0.5081	0.0393	54.4	33	568	12	463	max
20	500	-1	500c	67.73	74.76	5.02	0.4591	0.5067	0.034	52.5	33	569	13	466	
22	510	-1	510c	67.65	71.15	3.88	0.4741	0.4986	0.0272	47.4	34	571	14	471	
23	520	-1	519c	67.48	68.78	3.54	0.4826	0.492	0.0253	44.2	34	572	14	473	Ym
25	530	-1	529c	66.65	62.96	3.11	0.5021	0.4743	0.0234	36.4	35	575	15	477	
27	540	-1	539c	64.95	56.11	2.88	0.524	0.4527	0.0232	27.8	35	579	16	480	
28	545	-1	544c	63.73	52.49	2.81	0.5353	0.4409	0.0236	23.4	36	581	16	481	
29	550	-1	549c	62.23	48.77	2.77	0.5469	0.4286	0.0244	19.1	36	583	16	483	
30	555	-1	554c	60.45	45.01	2.74	0.5586	0.4159	0.0254	15.0	37	585	16	484	
32	560	-1	560c	56.05	37.66	2.71	0.5812	0.3905	0.0281	7.7	38	590	17	486	
32	564	1	405	60.44	41.54	8.11	0.5489	0.3773	0.0736	5.2	38	592	17	486	Rm
33	565	7	435	63.36	41.74	22.19	0.4977	0.3279	0.1743	348.6	46	631	18	490	
33	566	10	450	65.84	41.24	38.54	0.452	0.2832	0.2646	324.7	-1	497c	19	497	
33	567	12	460	66.94	40.62	49.58	0.4259	0.2585	0.3155	308.7	-1	506c	21	506	
33	568	13	465	66.96	39.99	54.33	0.4151	0.2479	0.3368	302.1	-1	512c	22	512	
34	570	14	470	66.83	39.49	58.3	0.4059	0.2398	0.3541	296.9	-1	519c	23	519	
34	573	15	475	65.25	37.75	61.53	0.3965	0.2294	0.3739	291.5	-1	527c	25	527	Mm
35	578	15	480	62.1	34.65	61.52	0.3923	0.2189	0.3887	288.5	-1	532c	26	532	
37	587	17	485	56.18	30.58	65.87	0.368	0.2003	0.4315	278.0	-1	544c	28	544	
44	620	18	490	32.82	18.39	67.26	0.277	0.1552	0.5677	251.3	-1	561c	32	561	
-1	495c	19	495	19.02	13.93	68.36	0.1877	0.1375	0.6746	234.4	12	463	33	568	min
-1	500c	20	500	19.04	15.23	69.22	0.1839	0.1471	0.6688	232.5	13	466	33	569	
-1	510c	22	510	19.13	18.84	70.36	0.1765	0.1739	0.6494	227.5	14	471	34	571	
-1	519c	23	520	19.29	21.21	70.7	0.1735	0.1907	0.6357	224.2	14	473	34	572	Bm
-1	529c	25	530	20.12	27.03	71.13	0.1701	0.2285	0.6013	216.5	15	477	35	575	
-1	539c	27	540	21.82	33.88	71.36	0.1717	0.2666	0.5615	207.8	16	480	35	579	
-1	544c	28	545	23.04	37.75	71.42	0.1746	0.2841	0.5412	203.5	16	481	36	581	
-1	549c	29	550	24.54	41.22	71.47	0.1788	0.3004	0.5207	199.2	16	483	36	583	
-1	554c	30	555	26.32	44.98	71.49	0.1843	0.315	0.5006	195.0	16	484	37	585	
-1	560c	32	560	30.72	52.33	71.52	0.1987	0.3385	0.4627	187.7	17	486	38	590	
W0	380	770	86.78	90.0	74.24	0.3457	0.3585	0.2957	0.0						
N0	380	770	3.47	3.6	2.96	0.3457	0.3585	0.2957	0.0						

DGF4-7N

Oswald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =3,6, Y _W =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y	A	b	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code			
1 405 32 564	48.45	-50.93	-26.15	57.25	0.5434	-0.5457	207.1	17 486 38 592	Cm					
7 435 33 565	48.25	-57.75	-12.23	59.04	0.4851	-0.4313	191.9	18 490 46 631						
10 450 33 566	48.75	-65.15	45.51	65.3	0.4294	-0.2928	176.0	19 497 -1 497c						
12 460 33 567	49.37	-69.39	16.06	71.23	0.4017	-0.1997	166.9	21 506 -1 506c						
13 465 33 568	50.0	-70.98	21.33	74.12	0.3961	-0.1592	163.2	22 512 -1 512c						
14 470 34 570	50.5	-71.87	25.72	76.33	0.3947	-0.1261	160.3	23 519 -1 519c						
15 475 34 573	52.24	-72.08	30.37	78.22	0.412	-0.0973	157.1	25 527 -1 527c	Gm					
15 480 35 578	55.34	-71.71	32.93	78.91	0.4456	-0.0919	155.3	26 532 -1 532c						
17 485 37 587	59.41	-66.71	40.63	78.11	0.5148	-0.0563	148.6	28 544 -1 544c						
18 490 44 620	71.6	-37.69	52.07	64.28	0.7534	-0.0389	125.8	32 561 -1 561c						
19 495 -1 495c	76.06	-13.96	56.84	58.53	0.8905	-0.0309	103.7	33 568 12 463	max					
20 500 -1 500c	74.76	-10.86	56.63	57.67	0.9058	-0.0268	100.8	33 569 13 466						
22 510 -1 510c	71.15	-2.38	54.4	54.85	0.9505	-0.0128	92.4	34 571 14 471						
23 520 -1 519c	68.78	2.89	53.19	53.27	0.9808	-0.0205	86.8	34 572 14 473	Ym					
25 530 -1 529c	62.96	14.87	48.81	51.03	1.0584	-0.0197	73.0	35 575 15 477						
27 540 -1 539c	56.11	27.1	43.4	51.17	1.1571	-0.0205	58.0	35 579 16 480						
28 545 -1 544c	52.49	32.78	40.47	52.09	1.2137	-0.0214	50.9	36 581 16 481						
29 550 -1 549c	48.77	38.02	37.44	53.36	1.2758	-0.0227	44.5	36 583 16 483						
30 555 -1 554c	45.01	42.62	34.37	54.76	1.3427	-0.0244	38.8	37 585 16 484						
32 560 -1 560c	37.66	49.33	28.34	56.89	1.4878	-0.0288	29.8	38 590 17 486						
32 564 1 405	41.54	50.93	26.15	57.26	1.4543	-0.078	27.1	38 592 17 486	Rm					
33 565 7 435	41.74	57.75	12.23	59.03	1.5173	-0.2126	11.9	46 631 18 490						
33 566 10 450	41.24	65.14	-4.51	65.29	1.5956	-0.3736	356.0	-1 497c 19 497						
33 567 12 460	40.62	69.38	-16.06	71.22	1.6471	-0.488	346.9	-1 506c 21 506						
33 568 13 465	39.99	70.96	-21.33	74.1	1.6737	-0.5432	343.2	-1 512c 22 512						
34 570 14 470	39.49	71.85	-25.71	76.31	1.6917	-0.5903	340.1	-1 519c 23 519						
34 573 15 475	37.75	72.06	-30.36	78.2	1.7274	-0.6516	337.1	-1 527c 25 527	Mm					
35 578 15 480	34.65	71.69	-32.92	78.89	1.7916	-0.7099	335.3	-1 532c 26 532						
37 587 17 485	30.58	66.69	-40.61	78.08	1.8361	-0.861	328.6	-1 544c 28 544						
44 620 18 490	18.39	37.67	-52.05	64.25	1.7832	-1.4618	305.8	-1 561c 32 561						
-1 495c 19 495	13.93	13.95	-56.81	58.5	1.3645	-1.9609	283.7	12 463 33 568	min					
-1 500c 20 500	15.23	10.86	-56.61	57.64	1.2492	-1.8165	280.8	13 466 33 569						
-1 510c 22 510	18.84	2.38	-54.78	54.83	1.0145	-1.4926	272.4	14 471 34 571						
-1 519c 23 520	21.21	-2.89	-53.17	53.25	0.9092	-1.3327	266.8	14 473 34 572	Bm					
-1 529c 25 530	27.03	-14.86	-48.8	51.01	0.744	-1.0518	253.0	15 477 35 575						
-1 539c 27 540	33.88	-27.1	-43.39	51.16	0.644	-0.8422	238.0	16 480 35 579						
-1 544c 28 545	37.5	-32.78	-40.47	52.08	0.6142	-0.7615	230.9	16 481 36 581						
-1 549c 29 550	41.22	-38.02	-37.44	53.36	0.595	-0.6931	224.5	16 483 36 583						
-1 554c 30 555	44.98	-42.62	-34.37	54.75	0.5849	-0.6355	218.8	16 484 37 585						
-1 560c 32 560	52.33	-49.32	-28.34	56.89	0.5869	-0.5465	209.8	17 486 38 590						
W0 380 770 90.0	0.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	B _c =1,000						
N0 380 770 3.6	0.0	0.0	0.0	0.0	0.9639	-0.3298	0.0	x _c =0,000						