

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/DGJ2/DGJ2.HTM>
Technische Information: <http://farbe.li.tu-berlin.de> oder <http://color.li.tu-berlin.de>

Ostwald-Optimalfarben (o), maximales (m) C _{AB,10} für D65, Y _{N,10} =3,6, Y _{W,10} =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀	A _{1,10}	B _{1,10}	C _{A1B1,10}	a _{1,10}	b _{1,10}	h _{xy,1,10}	i _d , λ _d	i _c , λ _c	Code			
0 405 31 556	47.1	-47.62	-35.74	59.54	0.2111	-0.7327	216.8	15 476	37 585	Cm				
6 435 31 557	47.93	-50.44	-17.05	53.25	0.1946	-0.5715	198.6	16 480	44 621					
10 450 31 559	48.21	-52.98	12.08	54.34	0.1759	-0.3289	167.1	18 492	-1 492c					
11 460 32 562	49.33	-53.01	20.46	56.82	0.1857	-0.2632	158.8	19 498	-1 498c					
12 465 33 565	50.4	-52.67	28.07	59.69	0.1975	-0.2064	151.9	21 506	-1 506c					
14 470 34 570	52.1	-49.89	39.97	63.93	0.2325	-0.1223	141.3	24 522	-1 522c					
15 475 35 579	56.8	-44.6	48.5	65.89	0.3015	-0.0876	132.5	26 534	-1 534c	Gm				
16 480 41 606	66.9	-24.01	61.91	66.4	0.472	-0.059	111.2	30 550	-1 550c					
16 485 -1 484c	75.01	1.34	70.61	70.62	0.6227	-0.0526	88.9	32 560	10 454					
18 490 -1 490c	72.49	6.44	71.04	71.33	0.6511	-0.0372	84.8	32 562	11 459	max				
19 495 -1 495c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461					
19 500 -1 499c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461					
22 510 -1 510c	64.74	20.42	65.21	68.33	0.7417	-0.0263	72.6	33 566	13 466					
23 520 -1 519c	62.19	24.38	62.72	67.29	0.7724	-0.0258	68.7	33 568	13 468	Ym				
26 530 -1 530c	53.14	35.99	53.41	64.41	0.8865	-0.0271	56.0	34 573	14 472					
27 540 -1 539c	49.82	39.36	49.91	63.57	0.9316	-0.0284	51.7	35 576	14 473					
28 545 -1 544c	46.42	42.31	46.31	62.73	0.9801	-0.0302	47.5	35 578	14 474					
29 550 -1 549c	42.99	44.75	42.64	61.81	1.0319	-0.0324	43.6	36 580	15 475					
31 555 -1 555c	36.18	47.74	35.35	59.41	1.1433	-0.0384	36.5	37 586	15 476					
32 560 10 451	34.36	52.93	-11.75	54.22	1.2318	-0.566	347.4	-1 491c	18 491					
31 556 0 405	42.89	47.63	35.74	59.55	1.0597	-0.0958	36.8	37 585	15 476	Rm				
31 557 6 435	42.06	50.44	17.05	53.25	1.0952	-0.267	18.6	44 621	16 480					
31 559 10 450	41.78	52.97	-12.08	54.34	1.1227	-0.5448	347.1	-1 492c	18 492					
32 562 11 460	40.66	53.0	-20.46	56.81	1.1369	-0.6304	338.8	-1 498c	19 498					
33 565 12 465	39.59	52.66	-28.07	59.67	1.1476	-0.7128	331.9	-1 506c	21 506					
34 570 14 470	37.89	49.88	-39.95	63.91	1.142	-0.8509	321.3	-1 522c	24 522					
35 579 15 475	33.19	44.58	-48.49	65.87	1.1529	-1.0135	312.5	-1 534c	26 534	Mm				
41 606 16 480	23.09	24.0	-61.88	66.37	1.0313	-1.5009	291.2	-1 550c	30 550					
-1 484c 16 485	14.98	-1.34	-70.56	70.57	0.5796	-2.3126	268.9	10 454	32 560					
-1 490c 18 490	17.5	-6.44	-71.0	71.29	0.4682	-2.0519	264.8	11 459	32 562	min				
-1 495c 19 495	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563					
-1 499c 19 500	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563					
-1 510c 22 510	25.25	-20.41	-65.19	68.31	0.2921	-1.4619	252.6	13 466	33 566					
-1 519c 23 520	27.8	-24.37	-62.7	67.27	0.2648	-1.3312	248.7	13 468	33 568	Bm				
-1 530c 26 530	36.85	-35.98	-53.4	64.39	0.225	-1.0087	236.0	14 472	34 573					
-1 539c 27 540	40.17	-39.36	-49.9	63.56	0.2237	-0.926	231.7	14 473	35 576					
-1 544c 28 545	43.57	-42.3	-46.3	62.72	0.2271	-0.8543	227.5	14 474	35 578					
-1 549c 29 550	47.0	-44.74	-42.63	61.81	0.2348	-0.792	223.6	15 475	36 580					
-1 555c 31 555	53.81	-47.74	-35.35	59.4	0.2607	-0.6919	216.5	15 476	37 586					
10 451 32 560	55.63	-52.94	11.75	54.23	0.2349	-0.3447	167.4	18 491	-1 491c					
W0 380 770	90.0	0.0	0.0	0.0	0.6155	-0.4292	0.0	B _c =1,000						
N0 380 770	3.6	0.0	0.0	0.0	0.6155	-0.4292	0.0	x _c =0,110						

DGJ20-7N

Ostwald-Optimalfarben (o), maximales (m) C _{AB,10} für D65, Y _{N,10} =3,6, Y _{W,10} =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀	A _{2,10}	B _{2,10}	C _{A2B2,10}	a _{2,10}	b _{2,10}	h _{xy,2,10}	i _d , λ _d	i _c , λ _c	Code			
0 405 31 556	47.1	-47.62	-28.59	55.55	0.2111	-0.7327	210.9	15 476	37 585	Cm				
6 435 31 557	47.93	-50.44	-13.64	52.26	0.1946	-0.5715	195.1	16 480	44 621					
10 450 31 559	48.21	-52.98	9.66	53.86	0.1759	-0.3289	169.6	18 492	-1 492c					
11 460 32 562	49.33	-53.01	16.37	55.48	0.1857	-0.2632	162.8	19 498	-1 498c					
12 465 33 565	50.4	-52.67	22.46	57.26	0.1975	-0.2064	156.9	21 506	-1 506c					
14 470 34 570	52.1	-49.89	31.97	59.26	0.2325	-0.1223	147.3	24 522	-1 522c					
15 475 35 579	56.8	-44.6	38.8	59.12	0.3015	-0.0876	138.9	26 534	-1 534c	Gm				
16 480 41 606	66.9	-24.01	49.52	55.04	0.472	-0.059	115.8	30 550	-1 550c					
16 485 -1 484c	75.01	1.34	56.48	56.5	0.6227	-0.0526	88.6	32 560	10 454					
18 490 -1 490c	72.49	6.44	56.83	57.2	0.6511	-0.0372	83.5	32 562	11 459	max				
19 495 -1 495c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32 563	12 461					
19 500 -1 499c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32 563	12 461					
22 510 -1 510c	64.74	20.42	52.17	56.02	0.7417	-0.0263	68.6	33 566	13 466					
23 520 -1 519c	62.19	24.38	50.17	55.79	0.7724	-0.0258	64.0	33 568	13 468	Ym				
26 530 -1 530c	53.14	35.99	42.73	55.87	0.8865	-0.0271	49.8	34 573	14 472					
27 540 -1 539c	49.82	39.36	39.93	56.07	0.9316	-0.0284	45.4	35 576	14 473					
28 545 -1 544c	46.42	42.31	37.04	56.24	0.9801	-0.0302	41.2	35 578	14 474					
29 550 -1 549c	42.99	44.75	34.11	56.27	1.0319	-0.0324	37.3	36 580	15 475					
31 555 -1 555c	36.18	47.74	28.28	55.49	1.1433	-0.0384	30.6	37 586	15 476					
32 560 10 451	34.36	52.93	-9.4	53.76	1.2318	-0.566	349.9	-1 491c	18 491					
31 556 0 405	42.89	47.63	28.59	55.55	1.0597	-0.0958	30.9	37 585	15 476	Rm				
31 557 6 435	42.06	50.44	13.64	52.26	1.0952	-0.267	15.1	44 621	16 480					
31 559 10 450	41.78	52.97	-9.66	53.85	1.1227	-0.5448	349.6	-1 492c	18 492					
32 562 11 460	40.66	53.0	-16.36	55.47	1.1369	-0.6304	342.8	-1 498c	19 498					
33 565 12 465	39.59	52.66	-22.45	57.25	1.1476	-0.7128	336.9	-1 506c	21 506					
34 570 14 470	37.89	49.88	-31.96	59.24	1.142	-0.8509	327.3	-1 522c	24 522					
35 579 15 475	33.19	44.58	-38.79	59.09	1.1529	-1.0135	318.9	-1 534c	26 534	Mm				
41 606 16 480	23.09	24.0	-49.5	55.01	1.0313	-1.5009	295.8	-1 550c	30 550					
-1 484c 16 485	14.98	-1.34	-56.45	56.46	0.5796	-2.3126	268.6	10 454	32 560					
-1 490c 18 490	17.5	-6.44	-56.8	57.17	0.4682	-2.0519	263.5	11 459	32 562	min				
-1 495c 19 495	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12 461	32 563					
-1 499c 19 500	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12 461	32 563					
-1 510c 22 510	25.25	-20.41	-52.15	56.0	0.2921	-1.4619	248.6	13 466	33 566					
-1 519c 23 520	27.8	-24.37	-50.16	55.77	0.2648	-1.3312	244.0	13 468	33 568	Bm				
-1 530c 26 530	36.85	-35.98	-42.72	55.86	0.225	-1.0087	229.8	14 472	34 573					
-1 539c 27 540	40.17	-39.36	-39.92	56.06	0.2237	-0.926	225.4	14 473	35 576					
-1 544c 28 545	43.57	-42.3	-37.04	56.23	0.2271	-0.8543	221.2	14 474	35 578					
-1 549c 29 550	47.0	-44.74	-34.11	56.26	0.2348	-0.792	217.3	15 475	36 580					
-1 555c 31 555	53.81	-47.74	-28.28	55.48	0.2607	-0.6919	210.6	15 476	37 586					
10 451 32 560	55.63	-52.94	9.4	53.77	0.2349	-0.3447	169.9	18 491	-1 491c					
W0 380 770	90.0	0.0	0.0	0.0	0.6155	-0.3433	0.0	B _c =0,800						
N0 380 770	3.6	0.0	0.0	0.0	0.6155	-0.3433	0.0	x _c =0,110						