

Colorimetric data of Television Luminous System TLS11 for CIE lightness $L^*_N=11$ of black

System:

TLS11

Monitor:

LCD

Color	$r=olv*_1$	$g=olv*_2$	$b=olv*_3$	$L^*=LAB^*_{1c}$	$a^*=LAB^*_{2c}$	$b^*=LAB^*_{3c}$	$C^*_{ab,c}=LAB^*_{rc}$	$h_{ab,c}$	$X_c=XYZ^*_{1c}$	$Y_c=XYZ^*_{2c}$	$Z_c=XYZ^*_{3c}$	x_c	y_c	$Y_c/88.59$
00 o00y	1.0	0.0	0.0	54.21	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503
01 o13y	1.0	0.125	0.0	54.91	76.45	59.02	96.58	38	42.42	22.84	3.44	0.6174	0.3325	0.2579
02 o25y	1.0	0.25	0.0	57.87	68.1	61.12	91.5	42	43.91	25.83	3.96	0.5958	0.3505	0.2916
03 o38y	1.0	0.375	0.0	62.22	56.16	64.44	85.47	49	46.26	30.66	4.75	0.5664	0.3754	0.3461
04 o50y	1.0	0.5	0.0	67.48	42.42	68.19	80.31	58	49.48	37.27	5.91	0.534	0.4022	0.4207
05 o63y	1.0	0.625	0.0	73.63	27.43	72.96	77.94	70	53.85	46.12	7.39	0.5016	0.4296	0.5206
06 o75y	1.0	0.75	0.0	80.08	12.73	77.89	78.93	81	59.14	56.82	9.2	0.4725	0.454	0.6414
07 o88y	1.0	0.875	0.0	86.52	-1.05	82.98	82.99	91	65.14	69.03	11.22	0.448	0.4748	0.7793
08 y00l	1.0	1.0	0.0	94.11	-15.83	89.38	90.77	101	73.43	85.54	13.8	0.425	0.4951	0.9655
09 y13l	0.875	1.0	0.0	92.0	-27.1	86.39	90.55	108	64.07	80.71	13.54	0.4047	0.5098	0.911
10 y25l	0.75	1.0	0.0	90.22	-37.49	83.97	91.96	115	56.47	76.78	13.28	0.3854	0.524	0.8667
11 y38l	0.625	1.0	0.0	88.56	-48.25	81.77	94.94	122	49.55	73.23	13.01	0.3649	0.5393	0.8266
12 y50l	0.5	1.0	0.0	87.07	-58.61	79.85	99.06	128	43.6	70.14	12.75	0.3447	0.5545	0.7917
13 y63l	0.375	1.0	0.0	85.89	-67.53	78.43	103.5	132	39.02	67.76	12.51	0.3271	0.568	0.7649
14 y75l	0.25	1.0	0.0	84.97	-74.95	77.13	107.56	136	35.55	65.95	12.4	0.3121	0.579	0.7444
15 y88l	0.125	1.0	0.0	84.37	-79.89	76.36	110.52	138	33.36	64.77	12.3	0.3021	0.5865	0.7312
16 l00c	0.0	1.0	0.0	84.21	-81.1	76.13	111.24	138	32.83	64.47	12.29	0.2996	0.5883	0.7278
17 l13c	0.0	1.0	0.125	84.25	-80.71	73.57	109.22	139	32.98	64.54	13.31	0.2976	0.5823	0.7285
18 l25c	0.0	1.0	0.25	84.35	-78.62	63.95	101.35	143	33.71	64.74	17.66	0.2903	0.5576	0.7308
19 l38c	0.0	1.0	0.375	84.61	-75.49	51.46	91.37	148	34.93	65.24	24.72	0.2797	0.5224	0.7365
20 l50c	0.0	1.0	0.5	84.97	-71.46	38.14	81.01	154	36.59	65.95	34.2	0.2676	0.4823	0.7444
21 l63c	0.0	1.0	0.625	85.43	-66.43	24.55	70.83	163	38.75	66.85	46.23	0.2552	0.4403	0.7546
22 l75c	0.0	1.0	0.75	85.97	-61.24	11.9	62.39	173	41.15	67.93	59.93	0.2435	0.4019	0.7668
23 l88c	0.0	1.0	0.875	86.54	-56.04	0.7	56.06	183	43.7	69.07	74.31	0.2336	0.3692	0.7796
24 c00v	0.0	1.0	1.0	87.18	-51.1	-9.41	51.97	195	46.37	70.38	89.45	0.2249	0.3413	0.7944
25 c13v	0.0	0.875	1.0	78.68	-38.63	-22.32	44.62	213	38.35	54.38	86.97	0.2134	0.3026	0.6138
26 c25v	0.0	0.75	1.0	71.08	-26.3	-33.97	42.97	233	32.33	42.3	84.93	0.2026	0.2651	0.4775
27 c38v	0.0	0.625	1.0	63.12	-11.97	-46.39	47.92	254	27.09	31.73	83.16	0.1908	0.2235	0.3582
28 c50v	0.0	0.5	1.0	54.95	4.19	-59.11	59.26	272	22.65	22.88	81.29	0.1786	0.1804	0.2582
29 c63v	0.0	0.375	1.0	47.37	21.46	-71.55	74.71	284	19.44	16.3	80.45	0.1673	0.1403	0.184
30 c75v	0.0	0.25	1.0	40.2	39.44	-83.05	91.95	294	16.99	11.37	79.32	0.1578	0.1056	0.1284
31 c88v	0.0	0.125	1.0	34.57	55.15	-92.53	107.73	299	15.49	8.29	79.02	0.1507	0.0806	0.0935
32 v00m	0.0	0.0	1.0	33.09	59.26	-94.9	111.9	301	15.11	7.58	78.79	0.1489	0.0747	0.0856
33 v13m	0.125	0.0	1.0	33.6	60.17	-94.39	111.95	301	15.63	7.82	79.26	0.1522	0.0761	0.0882
34 v25m	0.25	0.0	1.0	35.64	62.25	-90.58	109.92	303	17.57	8.82	78.88	0.1669	0.0838	0.0996
35 v38m	0.375	0.0	1.0	38.78	65.67	-85.41	107.74	306	20.9	10.53	79.21	0.1889	0.0952	0.1189
36 v50m	0.5	0.0	1.0	42.38	69.54	-79.14	105.36	310	25.19	12.75	79.11	0.2152	0.1089	0.1439
37 v63m	0.625	0.0	1.0	46.58	74.48	-72.19	103.73	315	31.01	15.7	79.49	0.2457	0.1244	0.1772
38 v75m	0.75	0.0	1.0	50.83	79.05	-64.9	102.28	320	37.61	19.12	79.55	0.276	0.1403	0.2158
39 v88m	0.875	0.0	1.0	54.98	83.66	-57.89	101.74	324	44.97	22.91	79.74	0.3046	0.1552	0.2586
40 m00o	1.0	0.0	1.0	59.56	89.09	-50.27	102.3	329	54.26	27.64	80.12	0.3349	0.1706	0.312
41 m13o	1.0	0.0	0.875	58.35	87.39	-40.57	96.35	334	51.59	26.33	65.42	0.3599	0.1837	0.2972
42 m25o	1.0	0.0	0.75	57.23	85.38	-29.34	90.29	340	49.04	25.16	51.28	0.3908	0.2005	0.284
43 m38o	1.0	0.0	0.625	56.14	83.38	-16.14	84.93	348	46.62	24.05	37.77	0.4299	0.2218	0.2715
44 m50o	1.0	0.0	0.5	55.19	81.22	-0.89	81.23	359	44.43	23.11	25.72	0.4764	0.2478	0.2609
45 m63o	1.0	0.0	0.375	54.35	79.62	15.44	81.1	11	42.67	22.31	16.14	0.526	0.275	0.2518
46 m75o	1.0	0.0	0.25	53.75	78.41	33.44	85.24	24	41.41	21.74	8.91	0.5747	0.3017	0.2454
47 m88o	1.0	0.0	0.125	53.35	77.5	51.81	93.22	34	40.55	21.37	4.23	0.613	0.323	0.2412
48 o00y	1.0	0.0	0.0	54.21	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503
49 n00w	0.0	0.0	0.0	10.76	5.51	-3.96	6.79	0	1.34	1.23	1.71	0.3134	0.2867	0.0139
50 n13w	0.125	0.125	0.125	16.56	4.87	-3.31	5.9	169	2.33	2.21	2.86	0.3146	0.2988	0.025
51 n25w	0.25	0.25	0.25	30.75	4.15	-2.76	4.99	269	6.61	6.54	7.89	0.3142	0.311	0.0739
52 n38w	0.375	0.375	0.375	43.53	4.11	-2.65	4.9	292	13.48	13.52	15.89	0.3142	0.3152	0.1526
53 n50w	0.5	0.5	0.5	55.06	4.06	-2.42	4.73	297	22.73	22.99	26.55	0.3145	0.3181	0.2595
54 n63w	0.625	0.625	0.625	66.15	3.69	-1.8	4.11	298	34.83	35.52	40.18	0.3151	0.3214	0.401
55 n75w	0.75	0.75	0.75	76.28	3.24	-0.77	3.34	301	49.03	50.35	55.64	0.3163	0.3248	0.5683
56 n88w	0.875	0.875	0.875	85.51	2.1	0.82	2.26	299	64.62	67.02	71.95	0.3174	0.3292	0.7565
57 n99w	1.0	1.0	1.0	95.41	-0.21	4.78	4.79	0	84.08	88.59	89.43	0.3208	0.338	1.0

TUB-test chart KE41; Hue circle and colorimetric data
Measurement of LCD display and for display reflectioninput: $olv^* setrgbcolor$
output: no change compared to inputTUB registration: 20100601-KE41/KE41L0NA.TXT /PS
application for measurement of printer or monitor systems

TUB material: code=rha4ta