

Interpretation *rgb* $\rightarrow$ *olv**- und CIELAB-Daten

sRGB-Display mit der Leuchtdichte-Reflexion $L_r=5\%$

Buntonkreis mit 6 Geräte-Bunttönen *OYLCVM*:

$h_{ab,a} = 31.9, 103.6, 137.6, 196.5, 302.7, 327.8$

Elementar-Bunttöne *RJGB*: $h_{ab,a} = 25.4, 92.3, 162.2, 271.7$

<i>Code</i>	L^*	a^*_a	b^*_a	C^*_{ab}	$h_{ab,a}$	<i>rgb</i> $\rightarrow$ <i>olv*</i>
<i>m00o=M</i>	60.6	84.6	-53.1	99.9	327.8	1.00 0.00 1.00
<i>m12o</i>	59.2	80.4	-39.3	89.5	333.9	1.00 0.00 0.87
<i>m25o</i>	57.9	76.8	-25.2	80.8	341.7	1.00 0.00 0.75
<i>m37o</i>	56.9	73.6	-10.8	74.4	351.6	1.00 0.00 0.62
<i>m50o</i>	56.1	71.1	3.4	71.2	2.7	1.00 0.00 0.50
<i>m62o</i>	55.5	69.2	17.2	71.3	13.9	1.00 0.00 0.37
<i>m75o</i>	55.1	67.9	29.1	73.9	23.2	1.00 0.00 0.25
<i>m87o</i>	54.9	67.1	37.7	77.0	29.3	1.00 0.00 0.12

R