


See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1 Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
Mean lightness difference (16 steps)													ΔE* _{CIELAB} = 0.0	
Mean lightness difference (5 steps)													ΔL* _{CIELAB} = 0.0	
Mean colour reproduction index:													R* _{ab,m} = 100	

OE740-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^{*}/Y_{intended}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$w^{*}w^{*}w^{*}$ setrgb $g_P=1.0$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}$ _{CIELAB, r} (relative)																
$w^{*}_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^{*}_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OE740-7N, Picture A7-130-2: 16 visual equidistant L^{*} -grey steps; PS operator: $w^{*}w^{*}w^{*}$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46


input: 000n/w/cmy0/rgb(->rgb*d)
output 130-2: $g_P=1.0$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
2	11.67 0.0 0.0	0.08 13.02 0.0	0.0 0.0 0.0	1.35 0.0 0.0	1.35
3	17.65 0.0 0.0	0.16 19.6 0.0	0.0 0.0 0.0	1.95 0.0 0.0	1.95
4	23.63 0.0 0.0	0.23 25.94 0.0	0.0 0.0 0.0	2.3 0.0 0.0	2.3
5	29.62 0.0 0.0	0.29 32.11 0.0	0.0 0.0 0.0	2.49 0.0 0.0	2.49
6	35.6 0.0 0.0	0.36 38.17 0.0	0.0 0.0 0.0	2.57 0.0 0.0	2.57
7	41.58 0.0 0.0	0.43 44.13 0.0	0.0 0.0 0.0	2.55 0.0 0.0	2.55
8	47.56 0.0 0.0	0.49 50.02 0.0	0.0 0.0 0.0	2.46 0.0 0.0	2.46
9	53.54 0.0 0.0	0.56 55.85 0.0	0.0 0.0 0.0	2.31 0.0 0.0	2.31
10	59.52 0.0 0.0	0.62 61.62 0.0	0.0 0.0 0.0	2.1 0.0 0.0	2.1
11	65.5 0.0 0.0	0.69 67.35 0.0	0.0 0.0 0.0	1.85 0.0 0.0	1.85
12	71.48 0.0 0.0	0.75 73.03 0.0	0.0 0.0 0.0	1.55 0.0 0.0	1.55
13	77.47 0.0 0.0	0.81 78.68 0.0	0.0 0.0 0.0	1.21 0.0 0.0	1.21
14	83.45 0.0 0.0	0.88 84.29 0.0	0.0 0.0 0.0	0.84 0.0 0.0	0.84
15	89.43 0.0 0.0	0.94 89.86 0.0	0.0 0.0 0.0	0.43 0.0 0.0	0.43
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
18	28.12 0.0 0.0	0.28 30.58 0.0	0.0 0.0 0.0	2.46 0.0 0.0	2.46
19	50.55 0.0 0.0	0.53 52.94 0.0	0.0 0.0 0.0	2.39 0.0 0.0	2.39
20	72.98 0.0 0.0	0.77 74.45 0.0	0.0 0.0 0.0	1.47 0.0 0.0	1.47
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 1.6
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 1.3
Mean colour reproduction index:					R* _{ab,m} = 93

OE740-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_P=0.92$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{\text{CIELAB}, r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,082	0,155	0,226	0,295	0,362	0,428	0,494	0,559	0,623	0,688	0,75	0,814	0,876	0,938	1,0

OE740-7N, Picture A7-131-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93


input: 000n/w/cmy0/rgb(->rgb*d)
output 131-2: $g_P=0.92$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	16.62 0.0 0.0	0.1 19.44 0.0	0.0 0.0 0.0	2.82 0.0 0.0	2.82
3	22.25 0.0 0.0	0.18 26.22 0.0	0.0 0.0 0.0	3.97 0.0 0.0	3.97
4	27.88 0.0 0.0	0.25 32.49 0.0	0.0 0.0 0.0	4.61 0.0 0.0	4.61
5	33.5 0.0 0.0	0.33 38.44 0.0	0.0 0.0 0.0	4.94 0.0 0.0	4.94
6	39.13 0.0 0.0	0.39 44.17 0.0	0.0 0.0 0.0	5.04 0.0 0.0	5.04
7	44.76 0.0 0.0	0.46 49.73 0.0	0.0 0.0 0.0	4.98 0.0 0.0	4.98
8	50.39 0.0 0.0	0.52 55.16 0.0	0.0 0.0 0.0	4.77 0.0 0.0	4.77
9	56.02 0.0 0.0	0.59 60.47 0.0	0.0 0.0 0.0	4.45 0.0 0.0	4.45
10	61.64 0.0 0.0	0.65 65.68 0.0	0.0 0.0 0.0	4.03 0.0 0.0	4.03
11	67.27 0.0 0.0	0.71 70.8 0.0	0.0 0.0 0.0	3.53 0.0 0.0	3.53
12	72.9 0.0 0.0	0.77 75.85 0.0	0.0 0.0 0.0	2.95 0.0 0.0	2.95
13	78.53 0.0 0.0	0.83 80.83 0.0	0.0 0.0 0.0	2.3 0.0 0.0	2.3
14	84.15 0.0 0.0	0.89 85.74 0.0	0.0 0.0 0.0	1.59 0.0 0.0	1.59
15	89.78 0.0 0.0	0.94 90.6 0.0	0.0 0.0 0.0	0.82 0.0 0.0	0.82
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	32.1 0.0 0.0	0.31 36.98 0.0	0.0 0.0 0.0	4.88 0.0 0.0	4.88
19	53.2 0.0 0.0	0.55 57.83 0.0	0.0 0.0 0.0	4.62 0.0 0.0	4.62
20	74.31 0.0 0.0	0.78 77.1 0.0	0.0 0.0 0.0	2.79 0.0 0.0	2.79
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					$\Delta E^*_{\text{CIELAB}} = 3.2$
Mean lightness difference (5 steps)					$\Delta L^*_{\text{CIELAB}} = 2.5$
Mean colour reproduction index:					$R^*_{ab,m} = 86$

OE740-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=0.85$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{intended} w^*_{out}	0.000 0.0	0.067 0.1	0.133 0.18	0.200 0.255	0.267 0.325	0.333 0.393	0.400 0.459	0.467 0.524	0.533 0.586	0.600 0.648	0.667 0.709	0.733 0.768	0.800 0.827	0.867 0.886	0.933 0.943	1.000 1.0

OE740-7N, Picture A7-132-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87

input: 000n/w/cmy0/rgb(->rgb*d)
output 132-2: $g_P=0.85$; $g_N=1.0$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			L*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	18.01	0.0	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G	
2	23.17	0.0	0.0	0.12	27.5	0.0	0.0	4.33	0.0	0.0	4.33			
3	28.33	0.0	0.0	0.21	34.25	0.0	0.0	5.92	0.0	0.0	5.92			
4	33.49	0.0	0.0	0.29	40.24	0.0	0.0	6.76	0.0	0.0	6.76			
5	38.65	0.0	0.0	0.36	45.8	0.0	0.0	7.15	0.0	0.0	7.15			
6	43.81	0.0	0.0	0.43	51.04	0.0	0.0	7.23	0.0	0.0	7.23			
7	48.97	0.0	0.0	0.49	56.06	0.0	0.0	7.09	0.0	0.0	7.09			
8	54.13	0.0	0.0	0.55	60.89	0.0	0.0	6.76	0.0	0.0	6.76			
9	59.29	0.0	0.0	0.61	65.56	0.0	0.0	6.27	0.0	0.0	6.27			
10	64.45	0.0	0.0	0.67	70.11	0.0	0.0	5.66	0.0	0.0	5.66			
11	69.61	0.0	0.0	0.73	74.54	0.0	0.0	4.93	0.0	0.0	4.93			
12	74.77	0.0	0.0	0.79	78.87	0.0	0.0	4.1	0.0	0.0	4.1			
13	79.93	0.0	0.0	0.84	83.12	0.0	0.0	3.19	0.0	0.0	3.19			
14	85.09	0.0	0.0	0.9	87.28	0.0	0.0	2.19	0.0	0.0	2.2			
15	90.25	0.0	0.0	0.95	91.38	0.0	0.0	1.13	0.0	0.0	1.13	Mean lightness difference (16 steps)		
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔE* _{CIELAB} = 4.5		
17	18.01	0.0	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.0	0.01			
18	37.36	0.0	0.0	0.34	44.44	0.0	0.0	7.08	0.0	0.0	7.08			
19	56.71	0.0	0.0	0.58	63.24	0.0	0.0	6.53	0.0	0.0	6.53			
20	76.06	0.0	0.0	0.8	79.94	0.0	0.0	3.88	0.0	0.0	3.88	Mean lightness difference (5 steps)		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔL* _{CIELAB} = 3.5		
Mean colour reproduction index:												R* _{ab,m} = 80		

OE740-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=0.78$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ C_{IELAB}, r (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{intended} w^*_{out}	0.0	0.123	0.209	0.287	0.359	0.426	0.492	0.554	0.614	0.673	0.731	0.786	0.841	0.895	0.948	1.0

OE740-7N, Picture A7-133-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75


input: 000n/w/cmy0/rgb(->rgb*d)
output 133-2: $g_P=0.77$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	31.42 0.0 0.0	0.15 37.15 0.0	0.0 0.0 0.0	5.73 0.0 0.0	5.73
3	35.99 0.0 0.0	0.24 43.58 0.0	0.0 0.0 0.0	7.59 0.0 0.0	7.59
4	40.56 0.0 0.0	0.32 49.07 0.0	0.0 0.0 0.0	8.51 0.0 0.0	8.51
5	45.13 0.0 0.0	0.4 54.03 0.0	0.0 0.0 0.0	8.9 0.0 0.0	8.9
6	49.7 0.0 0.0	0.46 58.62 0.0	0.0 0.0 0.0	8.92 0.0 0.0	8.92
7	54.27 0.0 0.0	0.53 62.95 0.0	0.0 0.0 0.0	8.68 0.0 0.0	8.68
8	58.84 0.0 0.0	0.59 67.06 0.0	0.0 0.0 0.0	8.22 0.0 0.0	8.22
9	63.41 0.0 0.0	0.64 71.0 0.0	0.0 0.0 0.0	7.59 0.0 0.0	7.59
10	67.99 0.0 0.0	0.7 74.8 0.0	0.0 0.0 0.0	6.81 0.0 0.0	6.81
11	72.56 0.0 0.0	0.75 78.47 0.0	0.0 0.0 0.0	5.91 0.0 0.0	5.91
12	77.13 0.0 0.0	0.8 82.03 0.0	0.0 0.0 0.0	4.9 0.0 0.0	4.9
13	81.7 0.0 0.0	0.86 85.5 0.0	0.0 0.0 0.0	3.8 0.0 0.0	3.8
14	86.27 0.0 0.0	0.9 88.87 0.0	0.0 0.0 0.0	2.61 0.0 0.0	2.61
15	90.84 0.0 0.0	0.95 92.18 0.0	0.0 0.0 0.0	1.34 0.0 0.0	1.34
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	43.99 0.0 0.0	0.38 52.83 0.0	0.0 0.0 0.0	8.84 0.0 0.0	8.84
19	61.13 0.0 0.0	0.62 69.05 0.0	0.0 0.0 0.0	7.92 0.0 0.0	7.92
20	78.27 0.0 0.0	0.82 82.9 0.0	0.0 0.0 0.0	4.64 0.0 0.0	4.64
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 5.6
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 4.3
Mean colour reproduction index:					R* _{ab,m} = 76

OE740-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^{*}/Y_{\text{intended}}$ (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^{*}w^{*}w^{*}$ setrgb $g_P=0.7$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}$ _{CIELAB, r} (relative)																
w^{*}_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^{*}_{out}	0.0	0.151	0.244	0.324	0.397	0.463	0.527	0.587	0.644	0.699	0.753	0.805	0.855	0.905	0.953	1.0

OE740-7N, Picture A7-134-2: 16 visual equidistant L^{*} -grey steps; PS operator: $w^{*}w^{*}w^{*}$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5


input: 000n/w/cmy0/rgb(->rgb*d)
output 134-2: $g_P=0.7$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	37.99	0.0	0.0	0.0	37.99	0.0	0.0	0.0	0.0	0.0	0.01	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G	
2	41.81	0.0	0.0	0.18	48.55	0.0	0.0	6.74	0.0	0.0	6.74	6.74		
3	45.64	0.0	0.0	0.28	54.29	0.0	0.0	8.64	0.0	0.0	8.64	8.64		
4	49.47	0.0	0.0	0.37	58.99	0.0	0.0	9.52	0.0	0.0	9.52	9.52		
5	53.3	0.0	0.0	0.44	63.12	0.0	0.0	9.82	0.0	0.0	9.82	9.82		
6	57.13	0.0	0.0	0.5	66.89	0.0	0.0	9.76	0.0	0.0	9.76	9.76		
7	60.96	0.0	0.0	0.56	70.37	0.0	0.0	9.42	0.0	0.0	9.42	9.42		
8	64.78	0.0	0.0	0.62	73.65	0.0	0.0	8.87	0.0	0.0	8.87	8.87		
9	68.61	0.0	0.0	0.68	76.75	0.0	0.0	8.14	0.0	0.0	8.14	8.14		
10	72.44	0.0	0.0	0.73	79.71	0.0	0.0	7.27	0.0	0.0	7.27	7.27		
11	76.27	0.0	0.0	0.78	82.56	0.0	0.0	6.29	0.0	0.0	6.29	6.29		
12	80.1	0.0	0.0	0.82	85.29	0.0	0.0	5.19	0.0	0.0	5.19	5.19		
13	83.93	0.0	0.0	0.87	87.93	0.0	0.0	4.01	0.0	0.0	4.01	4.01		
14	87.75	0.0	0.0	0.91	90.5	0.0	0.0	2.74	0.0	0.0	2.74	2.74		
15	91.58	0.0	0.0	0.96	92.99	0.0	0.0	1.4	0.0	0.0	1.4	1.4		
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	0.01		
17	37.99	0.0	0.0	0.0	37.99	0.0	0.0	0.0	0.0	0.0	0.01	0.01		
18	52.34	0.0	0.0	0.42	62.13	0.0	0.0	9.79	0.0	0.0	9.79	9.79		
19	66.7	0.0	0.0	0.65	75.22	0.0	0.0	8.52	0.0	0.0	8.52	8.52		
20	81.05	0.0	0.0	0.84	85.96	0.0	0.0	4.91	0.0	0.0	4.91	4.91		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	0.01		
Mean colour reproduction index:													R* _{ab,m} = 73	

OE740-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=0.63$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.185	0.283	0.366	0.438	0.503	0.564	0.621	0.675	0.727	0.776	0.824	0.87	0.915	0.958	1.0

OE740-7N, Picture A7-135-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15


input: 000n/w/cmy0/rgb(->rgb*d)
output 135-2: $g_P=0.62$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

Start output S1											
i	LAB*ref			L*out			LAB*out/c-ref			ΔE*	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
1	52.02	0.0	0.0	0.0	52.02	0.0	0.0	0.0	0.0	0.01	
2	54.91	0.0	0.0	0.23	61.8	0.0	0.0	6.89	0.0	0.0	6.89
3	57.8	0.0	0.0	0.33	66.34	0.0	0.0	8.54	0.0	0.0	8.54
4	60.7	0.0	0.0	0.41	69.92	0.0	0.0	9.23	0.0	0.0	9.23
5	63.59	0.0	0.0	0.48	72.99	0.0	0.0	9.4	0.0	0.0	9.4
6	66.48	0.0	0.0	0.55	75.73	0.0	0.0	9.25	0.0	0.0	9.25
7	69.37	0.0	0.0	0.6	78.23	0.0	0.0	8.86	0.0	0.0	8.86
8	72.27	0.0	0.0	0.66	80.55	0.0	0.0	8.28	0.0	0.0	8.28
9	75.16	0.0	0.0	0.71	82.73	0.0	0.0	7.57	0.0	0.0	7.57
10	78.05	0.0	0.0	0.76	84.78	0.0	0.0	6.73	0.0	0.0	6.73
11	80.95	0.0	0.0	0.8	86.74	0.0	0.0	5.79	0.0	0.0	5.79
12	83.84	0.0	0.0	0.84	88.6	0.0	0.0	4.77	0.0	0.0	4.77
13	86.73	0.0	0.0	0.88	90.4	0.0	0.0	3.67	0.0	0.0	3.67
14	89.62	0.0	0.0	0.92	92.13	0.0	0.0	2.5	0.0	0.0	2.5
15	92.52	0.0	0.0	0.96	93.79	0.0	0.0	1.28	0.0	0.0	1.28
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01
Mean lightness difference (16 steps)											
17	52.02	0.0	0.0	0.0	52.02	0.0	0.0	0.0	0.0	0.0	0.01
18	62.87	0.0	0.0	0.47	72.26	0.0	0.0	9.4	0.0	0.0	9.4
19	73.71	0.0	0.0	0.68	81.66	0.0	0.0	7.94	0.0	0.0	7.94
20	84.56	0.0	0.0	0.85	89.06	0.0	0.0	4.5	0.0	0.0	4.5
Mean lightness difference (5 steps)											
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01
ΔL* _{CIELAB} = 4.4											
Mean colour reproduction index:								R* _{ab,m} = 75			

OE740-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^{*}/Y_{\text{intended}}$ (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^{*}w^{*}w^{*}$ setrgb $g_P=0.55$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}_{\text{CIELAB},r}$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^{*}_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^{*}_{out}	0.0	0.226	0.33	0.413	0.484	0.546	0.604	0.658	0.707	0.755	0.8	0.843	0.885	0.925	0.963	1.0

OE740-7N, Picture A7-136-2: 16 visual equidistant L^{*} -grey steps; PS operator: $w^{*}w^{*}w^{*}$ setrgbcolor

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30

input: 000n/w/cmy0/rgb(->rgb*d)
output 136-2: $g_P=0.55$; $g_N=1.0$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	69.7 0.0 0.0	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01
2	71.41 0.0 0.0	0.28 76.8 0.0	0.0 0.0 0.0	5.39 0.0 0.0	5.39
3	73.13 0.0 0.0	0.38 79.57 0.0	0.0 0.0 0.0	6.45 0.0 0.0	6.45
4	74.84 0.0 0.0	0.47 81.67 0.0	0.0 0.0 0.0	6.83 0.0 0.0	6.83
5	76.55 0.0 0.0	0.53 83.42 0.0	0.0 0.0 0.0	6.87 0.0 0.0	6.87
6	78.27 0.0 0.0	0.59 84.96 0.0	0.0 0.0 0.0	6.69 0.0 0.0	6.69
7	79.98 0.0 0.0	0.65 86.34 0.0	0.0 0.0 0.0	6.35 0.0 0.0	6.35
8	81.7 0.0 0.0	0.7 87.6 0.0	0.0 0.0 0.0	5.9 0.0 0.0	5.9
9	83.41 0.0 0.0	0.74 88.77 0.0	0.0 0.0 0.0	5.36 0.0 0.0	5.36
10	85.12 0.0 0.0	0.78 89.87 0.0	0.0 0.0 0.0	4.75 0.0 0.0	4.75
11	86.84 0.0 0.0	0.82 90.91 0.0	0.0 0.0 0.0	4.07 0.0 0.0	4.07
12	88.55 0.0 0.0	0.86 91.89 0.0	0.0 0.0 0.0	3.33 0.0 0.0	3.33
13	90.27 0.0 0.0	0.9 92.82 0.0	0.0 0.0 0.0	2.56 0.0 0.0	2.56
14	91.98 0.0 0.0	0.93 93.72 0.0	0.0 0.0 0.0	1.74 0.0 0.0	1.74
15	93.7 0.0 0.0	0.97 94.58 0.0	0.0 0.0 0.0	0.89 0.0 0.0	0.89
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	69.7 0.0 0.0	0.0 69.7 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	76.13 0.0 0.0	0.52 83.01 0.0	0.0 0.0 0.0	6.88 0.0 0.0	6.88
19	82.55 0.0 0.0	0.72 88.2 0.0	0.0 0.0 0.0	5.64 0.0 0.0	5.64
20	88.98 0.0 0.0	0.87 92.13 0.0	0.0 0.0 0.0	3.14 0.0 0.0	3.14
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01


Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps) $\Delta E^*_{CIELAB} = 4.2$

Mean lightness difference (5 steps) $\Delta L^*_{CIELAB} = 3.1$

Mean colour reproduction index: $R^*_{ab,m} = 82$

OE740-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE741-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=0.48$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*$ $CIELAB, r$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
$w^*_{intended}$ w^*_{out}	0.000	0.277	0.384	0.466	0.534	0.593	0.647	0.697	0.742	0.785	0.825	0.863	0.899	0.934	0.968	1.0

OE740-7N, Picture A7-137-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^* setrgbcolor$

OE74: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60

input: 000n/w/cmy0/rgb(->rgb*d)
output 137-2: $g_P=0.47$; $g_N=1.0$

TUB registration: 20110801-OE74/OE74L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta