


See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIE LAB




OE810-7N-130-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-0: $g_P=1.0$; $g_N=1.0$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1 Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mean lightness difference (16 steps)
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	ΔE* _{CIELAB} = 0.0
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mean lightness difference (5 steps)
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	ΔL* _{CIELAB} = 0.0
Mean colour reproduction index:													R* _{ab,m} = 100	

OE810-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



L*/Y _{intended} (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
w* w* w* setrgb g _P =1.0																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* CIELAB, r (relative)																
w* _{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w* _{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OE810-7N, Picture A7-130-2: 16 visual equidistant L*-grey steps; PS operator: w* w* w* setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast Y_W:Y_N=88,9:0,31; Y_N range 0,0 to <0,46


input: cmy0 (->cmy0*_{de}) setcmyk
output 130-2: g_P=1.0; g_N=1.0

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta




OE810-7N-131-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-0: $g_P=1.0$; $g_N=1.08$






See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
2	11.67 0.0 0.0	0.04 0.0 0.0	9.36 0.0 0.0	-2.3 0.0 0.0	2.31
3	17.65 0.0 0.0	0.09 0.0 0.0	14.01 0.0 0.0	-3.63 0.0 0.0	3.64
4	23.63 0.0 0.0	0.15 0.0 0.0	19.12 0.0 0.0	-4.5 0.0 0.0	4.51
5	29.62 0.0 0.0	0.21 0.0 0.0	24.55 0.0 0.0	-5.06 0.0 0.0	5.07
6	35.6 0.0 0.0	0.27 0.0 0.0	30.23 0.0 0.0	-5.36 0.0 0.0	5.37
7	41.58 0.0 0.0	0.34 0.0 0.0	36.12 0.0 0.0	-5.45 0.0 0.0	5.46
8	47.56 0.0 0.0	0.41 0.0 0.0	42.19 0.0 0.0	-5.36 0.0 0.0	5.37
9	53.54 0.0 0.0	0.48 0.0 0.0	48.42 0.0 0.0	-5.11 0.0 0.0	5.12
10	59.52 0.0 0.0	0.55 0.0 0.0	54.79 0.0 0.0	-4.72 0.0 0.0	4.73
11	65.5 0.0 0.0	0.62 0.0 0.0	61.29 0.0 0.0	-4.2 0.0 0.0	4.21
12	71.48 0.0 0.0	0.69 0.0 0.0	67.91 0.0 0.0	-3.56 0.0 0.0	3.57
13	77.47 0.0 0.0	0.77 0.0 0.0	74.64 0.0 0.0	-2.82 0.0 0.0	2.83
14	83.45 0.0 0.0	0.84 0.0 0.0	81.47 0.0 0.0	-1.97 0.0 0.0	1.98
15	89.43 0.0 0.0	0.92 0.0 0.0	88.4 0.0 0.0	-1.02 0.0 0.0	1.03
16	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 3.4
17	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
18	28.12 0.0 0.0	0.19 0.0 0.0	23.17 0.0 0.0	-4.94 0.0 0.0	4.95
19	50.55 0.0 0.0	0.44 0.0 0.0	45.29 0.0 0.0	-5.25 0.0 0.0	5.26
20	72.98 0.0 0.0	0.71 0.0 0.0	69.58 0.0 0.0	-3.39 0.0 0.0	3.4
21	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 2.7
Mean colour reproduction index:					R* _{ab,m} = 85

OE810-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.18$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.041	0.093	0.15	0.211	0.273	0.339	0.407	0.476	0.547	0.62	0.693	0.769	0.845	0.921	1.0


OE810-7N, Picture A7-131-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93

input: $cmy0$ (-> $cmy0^*_{de}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.08$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB




OE810-7N-132-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-0: $g_P=1.0$; $g_N=1.17$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	16.62 0.0 0.0	0.03 13.12 0.0	0.0 0.0 -3.49	0.0 0.0 0.0	3.5
3	22.25 0.0 0.0	0.06 16.44 0.0	0.0 0.0 -5.8	0.0 0.0 0.0	5.81
4	27.88 0.0 0.0	0.11 20.45 0.0	0.0 0.0 -7.41	0.0 0.0 0.0	7.42
5	33.5 0.0 0.0	0.17 24.98 0.0	0.0 0.0 -8.51	0.0 0.0 0.0	8.52
6	39.13 0.0 0.0	0.22 29.94 0.0	0.0 0.0 -9.18	0.0 0.0 0.0	9.19
7	44.76 0.0 0.0	0.29 35.27 0.0	0.0 0.0 -9.48	0.0 0.0 0.0	9.49
8	50.39 0.0 0.0	0.35 40.93 0.0	0.0 0.0 -9.44	0.0 0.0 0.0	9.45
9	56.02 0.0 0.0	0.43 46.9 0.0	0.0 0.0 -9.11	0.0 0.0 0.0	9.12
10	61.64 0.0 0.0	0.5 53.13 0.0	0.0 0.0 -8.5	0.0 0.0 0.0	8.51
11	67.27 0.0 0.0	0.58 59.63 0.0	0.0 0.0 -7.63	0.0 0.0 0.0	7.64
12	72.9 0.0 0.0	0.66 66.36 0.0	0.0 0.0 -6.53	0.0 0.0 0.0	6.54
13	78.53 0.0 0.0	0.74 73.31 0.0	0.0 0.0 -5.2	0.0 0.0 0.0	5.21
14	84.15 0.0 0.0	0.82 80.48 0.0	0.0 0.0 -3.66	0.0 0.0 0.0	3.67
15	89.78 0.0 0.0	0.91 87.85 0.0	0.0 -1.92	0.0 0.0 1.93	Mean lightness difference (16 steps)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.01	ΔE* _{CIELAB} = 6.0
17	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.01	
18	32.1 0.0 0.0	0.15 23.81 0.0	0.0 -8.28	0.0 0.0 8.29	
19	53.2 0.0 0.0	0.39 43.88 0.0	0.0 -9.31	0.0 0.0 9.32	
20	74.31 0.0 0.0	0.68 68.08 0.0	0.0 -6.22	0.0 0.0 6.23	Mean lightness difference (5 steps)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.01	ΔL* _{CIELAB} = 4.8
Mean colour reproduction index:					R* _{ab,m} = 74

OE810-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y_{intended}$ (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.36$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.025	0.064	0.112	0.166	0.224	0.288	0.355	0.425	0.499	0.577	0.655	0.738	0.824	0.91	1.0


OE810-7N, Picture A7-132-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.17$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta






See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1 Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
1	18.01 0.0 0.0	0.0 0.0	18.01 0.0 0.0	0.0 0.0 0.0	0.01	
2	23.17 0.0 0.0	0.02 19.2 0.0 0.0	-3.95 0.0 0.0	3.96		
3	28.33 0.0 0.0	0.04 21.49 0.0 0.0	-6.83 0.0 0.0	6.84		
4	33.49 0.0 0.0	0.08 24.5 0.0 0.0	-8.98 0.0 0.0	8.99		
5	38.65 0.0 0.0	0.13 28.12 0.0 0.0	-10.52 0.0 0.0	10.53		
6	43.81 0.0 0.0	0.18 32.26 0.0 0.0	-11.53 0.0 0.0	11.54		
7	48.97 0.0 0.0	0.24 36.89 0.0 0.0	-12.07 0.0 0.0	12.08		
8	54.13 0.0 0.0	0.31 41.94 0.0 0.0	-12.18 0.0 0.0	12.19		
9	59.29 0.0 0.0	0.38 47.41 0.0 0.0	-11.87 0.0 0.0	11.88		
10	64.45 0.0 0.0	0.46 53.25 0.0 0.0	-11.19 0.0 0.0	11.2		
11	69.61 0.0 0.0	0.54 59.46 0.0 0.0	-10.14 0.0 0.0	10.15		
12	74.77 0.0 0.0	0.62 66.02 0.0 0.0	-8.74 0.0 0.0	8.75		
13	79.93 0.0 0.0	0.71 72.9 0.0 0.0	-7.02 0.0 0.0	7.03		
14	85.09 0.0 0.0	0.8 80.1 0.0 0.0	-4.98 0.0 0.0	4.99		
15	90.25 0.0 0.0	0.9 87.61 0.0 0.0	-2.63 0.0 0.0	2.64		
16	95.41 0.0 0.0	1.0 95.41 0.0 0.0	0.0 0.0 0.0	0.01		
17	18.01 0.0 0.0	0.0 18.01 0.0 0.0	0.0 0.0 0.0	0.01		
18	37.36 0.0 0.0	0.12 27.16 0.0 0.0	-10.19 0.0 0.0	10.2		
19	56.71 0.0 0.0	0.34 44.63 0.0 0.0	-12.07 0.0 0.0	12.08		
20	76.06 0.0 0.0	0.64 67.71 0.0 0.0	-8.34 0.0 0.0	8.35		
21	95.41 0.0 0.0	1.0 95.41 0.0 0.0	0.0 0.0 0.0	0.01		
Mean colour reproduction index:					R* _{ab,m} = 66	Mean lightness difference (16 steps) ΔE* _{CIELAB} = 7.7
						Mean lightness difference (5 steps) ΔL* _{CIELAB} = 6.1

OE810-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


L^*/Y_{intended} (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.54$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,016	0,045	0,084	0,131	0,184	0,244	0,31	0,379	0,455	0,536	0,62	0,709	0,803	0,899	1,0

OE810-7N, Picture A7-133-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75

input: $cmy0$ (-> $cmy0^*_{\text{de}}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.29$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIE LAB




OE810-7N-134-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: *cmy0* ($\rightarrow cmy0^*_{de}$) *setcmyk*
output 130-0: $g_P=1.0$; $g_N=1.42$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	31.42 0.0 0.0	0.01 27.5 0.0	0.0 -3.91 0.0	0.0 0.0 0.0	3.92
3	35.99 0.0 0.0	0.03 28.99 0.0	0.0 -6.99 0.0	0.0 0.0 0.0	7.0
4	40.56 0.0 0.0	0.06 31.15 0.0	0.0 -9.4 0.0	0.0 0.0 0.0	9.41
5	45.13 0.0 0.0	0.1 33.91 0.0	0.0 -11.21 0.0	0.0 0.0 0.0	11.22
6	49.7 0.0 0.0	0.15 37.21 0.0	0.0 -12.48 0.0	0.0 0.0 0.0	12.49
7	54.27 0.0 0.0	0.21 41.03 0.0	0.0 -13.24 0.0	0.0 0.0 0.0	13.25
8	58.84 0.0 0.0	0.27 45.33 0.0	0.0 -13.5 0.0	0.0 0.0 0.0	13.51
9	63.41 0.0 0.0	0.34 50.1 0.0	0.0 -13.3 0.0	0.0 0.0 0.0	13.31
10	67.99 0.0 0.0	0.42 55.33 0.0	0.0 -12.65 0.0	0.0 0.0 0.0	12.66
11	72.56 0.0 0.0	0.5 60.98 0.0	0.0 -11.56 0.0	0.0 0.0 0.0	11.57
12	77.13 0.0 0.0	0.59 67.06 0.0	0.0 -10.05 0.0	0.0 0.0 0.0	10.06
13	81.7 0.0 0.0	0.68 73.56 0.0	0.0 -8.13 0.0	0.0 0.0 0.0	8.14
14	86.27 0.0 0.0	0.78 80.45 0.0	0.0 -5.81 0.0	0.0 0.0 0.0	5.82
15	90.84 0.0 0.0	0.89 87.74 0.0	0.0 -3.09 0.0	0.0 0.0 0.0	3.1
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	43.99 0.0 0.0	0.09 33.17 0.0	0.0 -10.81 0.0	0.0 0.0 0.0	10.82
19	61.13 0.0 0.0	0.3 47.66 0.0	0.0 -13.46 0.0	0.0 0.0 0.0	13.47
20	78.27 0.0 0.0	0.61 68.65 0.0	0.0 -9.61 0.0	0.0 0.0 0.0	9.62
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 63$					

OE810-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.72$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.01	0.031	0.063	0.103	0.151	0.207	0.27	0.339	0.415	0.498	0.586	0.681	0.782	0.888	1.0


OE810-7N, Picture A7-134-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5

input: $cmy0$ (-> $cmy0^*_{de}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.42$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIE LAB




OE810-7N-135-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-0: $g_P=1.0$; $g_N=1.6$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	41.81 0.0 0.0	0.01 38.32 0.0	0.0 -3.48 0.0	0.0 0.0 0.0	3.49
3	45.64 0.0 0.0	0.02 39.23 0.0	0.0 -6.4 0.0	0.0 0.0 0.0	6.41
4	49.47 0.0 0.0	0.05 40.68 0.0	0.0 -8.78 0.0	0.0 0.0 0.0	8.79
5	53.3 0.0 0.0	0.08 42.65 0.0	0.0 -10.64 0.0	0.0 0.0 0.0	10.65
6	57.13 0.0 0.0	0.12 45.11 0.0	0.0 -12.01 0.0	0.0 0.0 0.0	12.02
7	60.96 0.0 0.0	0.18 48.06 0.0	0.0 -12.89 0.0	0.0 0.0 0.0	12.9
8	64.78 0.0 0.0	0.24 51.48 0.0	0.0 -13.29 0.0	0.0 0.0 0.0	13.3
9	68.61 0.0 0.0	0.3 55.38 0.0	0.0 -13.22 0.0	0.0 0.0 0.0	13.23
10	72.44 0.0 0.0	0.38 59.74 0.0	0.0 -12.69 0.0	0.0 0.0 0.0	12.7
11	76.27 0.0 0.0	0.46 64.56 0.0	0.0 -11.69 0.0	0.0 0.0 0.0	11.7
12	80.1 0.0 0.0	0.55 69.84 0.0	0.0 -10.25 0.0	0.0 0.0 0.0	10.26
13	83.93 0.0 0.0	0.65 75.57 0.0	0.0 -8.35 0.0	0.0 0.0 0.0	8.36
14	87.75 0.0 0.0	0.76 81.74 0.0	0.0 -6.0 0.0	0.0 0.0 0.0	6.01
15	91.58 0.0 0.0	0.88 88.35 0.0	0.0 -3.22 0.0	0.0 0.0 0.0	3.23
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	52.34 0.0 0.0	0.07 42.11 0.0	0.0 -10.22 0.0	0.0 0.0 0.0	10.23
19	66.7 0.0 0.0	0.27 53.37 0.0	0.0 -13.32 0.0	0.0 0.0 0.0	13.33
20	81.05 0.0 0.0	0.58 71.23 0.0	0.0 -9.81 0.0	0.0 0.0 0.0	9.82
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 64$					

OE810-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.9$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.006	0.022	0.047	0.081	0.124	0.175	0.235	0.303	0.379	0.463	0.554	0.654	0.762	0.877	1.0


OE810-7N, Picture A7-135-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.6$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIE LAB




OE810-7N-136-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) $setcmyk$
output 130-0: $g_P=1.0$; $g_N=1.81$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	52.02 0.0 0.0	0.0 52.02 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	54.91 0.0 0.0	0.0 52.17 0.0	0.0 -2.73 0.0	0.0 0.0 0.0	2.74
3	57.8 0.0 0.0	0.02 52.67 0.0	0.0 -5.12 0.0	0.0 0.0 0.0	5.13
4	60.7 0.0 0.0	0.04 53.54 0.0	0.0 -7.14 0.0	0.0 0.0 0.0	7.15
5	63.59 0.0 0.0	0.06 54.79 0.0	0.0 -8.79 0.0	0.0 0.0 0.0	8.8
6	66.48 0.0 0.0	0.1 56.43 0.0	0.0 -10.04 0.0	0.0 0.0 0.0	10.05
7	69.37 0.0 0.0	0.15 58.47 0.0	0.0 -10.89 0.0	0.0 0.0 0.0	10.9
8	72.27 0.0 0.0	0.2 60.91 0.0	0.0 -11.35 0.0	0.0 0.0 0.0	11.36
9	75.16 0.0 0.0	0.27 63.75 0.0	0.0 -11.4 0.0	0.0 0.0 0.0	11.41
10	78.05 0.0 0.0	0.35 67.01 0.0	0.0 -11.03 0.0	0.0 0.0 0.0	11.04
11	80.95 0.0 0.0	0.43 70.69 0.0	0.0 -10.25 0.0	0.0 0.0 0.0	10.26
12	83.84 0.0 0.0	0.52 74.78 0.0	0.0 -9.05 0.0	0.0 0.0 0.0	9.06
13	86.73 0.0 0.0	0.63 79.3 0.0	0.0 -7.42 0.0	0.0 0.0 0.0	7.43
14	89.62 0.0 0.0	0.74 84.24 0.0	0.0 -5.38 0.0	0.0 0.0 0.0	5.39
15	92.52 0.0 0.0	0.87 89.61 0.0	0.0 -2.9 0.0	0.0 0.0 0.0	2.91
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	52.02 0.0 0.0	0.0 52.02 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	62.87 0.0 0.0	0.06 54.44 0.0	0.0 -8.41 0.0	0.0 0.0 0.0	8.42
19	73.71 0.0 0.0	0.24 62.28 0.0	0.0 -11.42 0.0	0.0 0.0 0.0	11.43
20	84.56 0.0 0.0	0.55 75.87 0.0	0.0 -8.68 0.0	0.0 0.0 0.0	8.69
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 7.1
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 5.7
Mean colour reproduction index:					R* _{ab,m} = 69

OE810-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=2.08$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ C_{IELAB}, r (relative)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.004	0.015	0.035	0.064	0.102	0.149	0.205	0.27	0.346	0.431	0.524	0.629	0.743	0.866	1.0


OE810-7N, Picture A7-136-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30

input: $cmy0$ ($\rightarrow cmy0^*_{\text{de}}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=1.81$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB




OE810-7N-137-0: Test chart with 24x17=408 colours and digital equidistant 17 step colour scales; compare ISO/IEC 15775:1999; rgb colour data, patch size and grey layout: 8mm x 8mm, 247mm x 170mm, Page 1/3

OE81: Test chart 2 according to DIN 33872-1; 1MR, DEH
17 step equally spaced colours and three hue circles

input: *cmy0* ($\rightarrow cmy0^*_{de}$) *setcmyk*
output 130-0: $g_P=1.0$; $g_N=2.1$


TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rha4ta



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	71.41 0.0 0.0	69.75 0.0 0.0	-1.65 0.0 0.0	0.0 0.0 0.0	1.66
3	73.13 0.0 0.0	69.97 0.0 0.0	-3.15 0.0 0.0	0.0 0.0 0.0	3.16
4	74.84 0.0 0.0	70.37 0.0 0.0	-4.46 0.0 0.0	0.0 0.0 0.0	4.47
5	76.55 0.0 0.0	70.99 0.0 0.0	-5.55 0.0 0.0	0.0 0.0 0.0	5.56
6	78.27 0.0 0.0	71.84 0.0 0.0	-6.41 0.0 0.0	0.0 0.0 0.0	6.42
7	79.98 0.0 0.0	72.94 0.0 0.0	-7.03 0.0 0.0	0.0 0.0 0.0	7.04
8	81.7 0.0 0.0	74.29 0.0 0.0	-7.4 0.0 0.0	0.0 0.0 0.0	7.41
9	83.41 0.0 0.0	75.91 0.0 0.0	-7.49 0.0 0.0	0.0 0.0 0.0	7.5
10	85.12 0.0 0.0	77.8 0.0 0.0	-7.31 0.0 0.0	0.0 0.0 0.0	7.32
11	86.84 0.0 0.0	79.98 0.0 0.0	-6.85 0.0 0.0	0.0 0.0 0.0	6.86
12	88.55 0.0 0.0	82.45 0.0 0.0	-6.09 0.0 0.0	0.0 0.0 0.0	6.1
13	90.27 0.0 0.0	85.23 0.0 0.0	-5.03 0.0 0.0	0.0 0.0 0.0	5.04
14	91.98 0.0 0.0	88.3 0.0 0.0	-3.67 0.0 0.0	0.0 0.0 0.0	3.68
15	93.7 0.0 0.0	91.7 0.0 0.0	-1.99 0.0 0.0	0.0 0.0 0.0	2.0
16	95.41 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	76.13 0.0 0.0	70.82 0.0 0.0	-5.3 0.0 0.0	0.0 0.0 0.0	5.31
19	82.55 0.0 0.0	75.07 0.0 0.0	-7.48 0.0 0.0	0.0 0.0 0.0	7.49
20	88.98 0.0 0.0	83.12 0.0 0.0	-5.85 0.0 0.0	0.0 0.0 0.0	5.86
21	95.41 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 4.6
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 3.7
Mean colour reproduction index:					R* _{ab,m} = 80

OE810-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE811-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^*w^*w^*$ setrgb																
$g_N=2.26$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ $CIELAB, r$ (relative)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.002	0.01	0.026	0.051	0.083	0.126	0.179	0.241	0.315	0.4	0.496	0.604	0.724	0.855	1.0

OE810-7N, Picture A7-137-2: 16 visual equidistant L^* -grey steps; PS operator: $w^*w^*w^*$ setrgbcolor

OE81: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60

input: $cmy0$ ($\rightarrow cmy0^*_{de}$) setcmyk
output 130-2: $g_P=1.0$; $g_N=2.1$

TUB registration: 20110801-OE81/OE81L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta