

ISO/IEC Vorlage nach ISO/IEC TR 24705	Original ²⁾ BAM-URL zum Download	Neue ²⁾ TUB-URL zum Download + FF_LM	1-Minus- Relation 1MR ¹⁾ + DEH		Device File Output DFO _i i/8 DG_PS		Whole De- vice Output WDO _i i/8 DG_PR	
			VG	PG	VG	PG	VG	PG
3n (000n)	A ₁ : B/DG86	A ₁ : T/OG60	● ¹⁾	–	●	–	●	–
3w (w)	A ₁ : B/DG87	A ₁ : T/OG61	● ¹⁾	–	●MG15	–	●MG16	–
3c (cmy0)	A ₁ : B/DG88	A ₁ : T/OG62	● ¹⁾	–	●	–	●	–
3r (rgb)	A ₁ : B/DG89	A ₁ : T/OG63	● ¹⁾	–	●	–	●	–
3a (all)	A ₄ : –	A ₄ : T/OG64	● ¹⁾	–	●	–	●	–
2C (cmy0)	C ₁ : B/FG96	C ₁ : T/OG65	● ¹⁾	● ¹⁾	●	●	●	●
2C (cmy0)	C ₁ : B/FG98	C ₁ : T/OG66	● ¹⁾	● ¹⁾	●	●	●	●
4R (rgb)	C ₁ : B/FG97	C ₁ : T/OG67	● ¹⁾	● ¹⁾	●	●	●	●
4R (rgb)	C ₁ : B/FG99	C ₁ : T/OG68	● ¹⁾	● ¹⁾	●	●	●	●
4r (rgb)	C ₁ : –	C ₁ : T/OG69	● ¹⁾	–	●	–	●	–

Abkürzungen: 1MR = 1-Minus-Relation; DG_PS/PR = Device Gamma PS/Profile
cmy0/000n setcmykcolor; rgb setrgbcolor; w setgray; DEH=Device to Elementary Hue
 VG = Vektorgrafik; PG = Pixelgrafik; ● = realisiert; O = möglich; – = keine PG

Remarks: 1) Realisiert: Mac OSX 10/10.1, Adobe FrameMaker 8, Unix, Ghostscript

2) BAM/ = B/ = <http://www.ps.bam.de/>; TUB/ = T/ = <http://130.149.60.45/~farbmetrik/>