


i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	0.0	0.0	0.0	0.0	0.0	Kennzeichnung nach
2	6.36	0.0	0.07	6.36	0.0	ISO/IEC 15775 Anhang G
3	12.72	0.0	0.13	12.72	0.0	und DIN 33866-1 Anhang G
4	19.08	0.0	0.2	19.08	0.0	
5	25.44	0.0	0.27	25.44	0.0	
6	31.8	0.0	0.33	31.8	0.0	
7	38.16	0.0	0.4	38.16	0.0	
8	44.52	0.0	0.47	44.52	0.0	
9	50.89	0.0	0.53	50.89	0.0	
10	57.25	0.0	0.6	57.25	0.0	
11	63.61	0.0	0.67	63.61	0.0	
12	69.97	0.0	0.73	69.97	0.0	
13	76.33	0.0	0.8	76.33	0.0	
14	82.69	0.0	0.87	82.69	0.0	
15	89.05	0.0	0.93	89.05	0.0	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	1.0	95.41	0.0	ΔE*CIELAB = 0.0
17	0.0	0.0	0.0	0.0	0.0	
18	23.85	0.0	0.25	23.85	0.0	
19	47.71	0.0	0.5	47.71	0.0	
20	71.56	0.0	0.75	71.56	0.0	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	1.0	95.41	0.0	ΔL*CIELAB = 0.0
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 100	

OG640-3N-130-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-130-11: File: Measure unknown; Device: Device unknown; Date: Date unknown


L^*/Y_{intended} (absolut)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=1.0$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = [L^*_{\text{CIELAB}, r}]$ (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OG640-7N, Bild A7-130-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle ($\rightarrow \text{rgb}^*_{\text{de}}$) setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:0,31$; Y_N -Bereich 0,0 to <0,46 Ausgabe 130-11: $g_P=1.0$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	11.67 0.0 0.0	0.1 14.73 0.0	11.67 0.0 0.0	3.06 0.0 0.0	3.06	ISO/IEC 15775 Anhang G
3	17.65 0.0 0.0	0.18 21.96 0.0	17.65 0.0 0.0	4.3 0.0 0.0	4.3	und DIN 33866-1 Anhang G
4	23.63 0.0 0.0	0.26 28.63 0.0	23.63 0.0 0.0	4.99 0.0 0.0	4.99	
5	29.62 0.0 0.0	0.33 34.96 0.0	29.62 0.0 0.0	5.34 0.0 0.0	5.34	
6	35.6 0.0 0.0	0.39 41.05 0.0	35.6 0.0 0.0	5.46 0.0 0.0	5.46	
7	41.58 0.0 0.0	0.46 46.96 0.0	41.58 0.0 0.0	5.38 0.0 0.0	5.38	
8	47.56 0.0 0.0	0.52 52.72 0.0	47.56 0.0 0.0	5.16 0.0 0.0	5.16	
9	53.54 0.0 0.0	0.59 58.36 0.0	53.54 0.0 0.0	4.82 0.0 0.0	4.82	
10	59.52 0.0 0.0	0.65 63.88 0.0	59.52 0.0 0.0	4.36 0.0 0.0	4.36	
11	65.5 0.0 0.0	0.71 69.32 0.0	65.5 0.0 0.0	3.82 0.0 0.0	3.82	
12	71.48 0.0 0.0	0.77 74.67 0.0	71.48 0.0 0.0	3.19 0.0 0.0	3.19	
13	77.47 0.0 0.0	0.83 79.95 0.0	77.47 0.0 0.0	2.49 0.0 0.0	2.49	
14	83.45 0.0 0.0	0.89 85.16 0.0	83.45 0.0 0.0	1.72 0.0 0.0	1.72	
15	89.43 0.0 0.0	0.94 90.31 0.0	89.43 0.0 0.0	0.89 0.0 0.0	0.89	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 3.4
17	5.69 0.0 0.0	0.0 5.69 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01	
18	28.12 0.0 0.0	0.31 33.4 0.0	28.12 0.0 0.0	5.28 0.0 0.0	5.28	
19	50.55 0.0 0.0	0.56 55.55 0.0	50.55 0.0 0.0	5.0 0.0 0.0	5.0	
20	72.98 0.0 0.0	0.78 76.0 0.0	72.98 0.0 0.0	3.02 0.0 0.0	3.02	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 2.7
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 85	

OG640-3N-131-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



L*/Y _{intended} (absolut)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
w* w* w* setrgb																
g _p =0.85																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* _{CIELAB, r} (relativ)																
w* _{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w* _{out}	0,0	0,101	0,181	0,256	0,327	0,394	0,46	0,525	0,587	0,649	0,71	0,769	0,828	0,886	0,943	1,0

OG640-7N, Bild A7-131-11: 16 visuell gleichabständige L*-Graustufen; PS-Operator: w* w* w* setrgbcolor

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle (->rgb*_{de}) setrgbcolo
Gesehener Y-Kontrast Y_W:Y_N=88,9:0,62; Y_N-Bereich 0,46 to <0,9 Ausgabe 131-11: g_p=0,92; g_N=1,0


i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	10.99	0.0	0.0	10.99	0.0	0.0
2	16.62	0.0	0.14	22.52	0.0	0.0
3	22.25	0.0	0.23	30.18	0.0	0.0
4	27.88	0.0	0.31	36.84	0.0	0.0
5	33.5	0.0	0.38	42.93	0.0	0.0
6	39.13	0.0	0.45	48.63	0.0	0.0
7	44.76	0.0	0.51	54.03	0.0	0.0
8	50.39	0.0	0.57	59.19	0.0	0.0
9	56.02	0.0	0.63	64.17	0.0	0.0
10	61.64	0.0	0.69	68.98	0.0	0.0
11	67.27	0.0	0.74	73.65	0.0	0.0
12	72.9	0.0	0.8	78.2	0.0	0.0
13	78.53	0.0	0.85	82.64	0.0	0.0
14	84.15	0.0	0.9	86.98	0.0	0.0
15	89.78	0.0	0.95	91.23	0.0	0.0
16	95.41	0.0	1.0	95.41	0.0	0.0
17	10.99	0.0	0.0	10.99	0.0	0.0
18	32.1	0.0	0.36	41.45	0.0	0.0
19	53.2	0.0	0.6	61.7	0.0	0.0
20	74.31	0.0	0.81	79.32	0.0	0.0
21	95.41	0.0	1.0	95.41	0.0	0.0

Mittlerer Helligkeitsabstand (16 Stufen) $\Delta E^*_{CIELAB} = 6.0$

Mittlerer Helligkeitsabstand (5 Stufen) $\Delta L^*_{CIELAB} = 4.6$

Mittlerer Farbwiedergabe-Index: $R^*_{ab,m} = 74$

OG640-3N-132-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-132-11: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y^*_{intended}$ (absolut)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_p=0.74$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = [L^*_{CIELAB, r}]$ (relativ)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.137	0.227	0.306	0.379	0.446	0.51	0.571	0.63	0.687	0.742	0.796	0.849	0.9	0.95	1.0

OG640-7N, Bild A7-132-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{ setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle ($\rightarrow \text{rgb}^*_{de}$) setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:1,25$; Y_N -Bereich 0,93 to <1,8 Ausgabe 132-11: $g_p=0.85$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	18.01 0.0 0.0	0.0 0.0 0.0	18.01 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	23.17 0.0 0.0	0.17 31.35 0.0	0.0 8.18 0.0	0.0 8.18 0.0	8.18	ISO/IEC 15775 Anhang G
3	28.33 0.0 0.0	0.27 38.93 0.0	0.0 10.6 0.0	0.0 10.6 0.0	10.6	und DIN 33866-1 Anhang G
4	33.49 0.0 0.0	0.35 45.23 0.0	0.0 11.74 0.0	0.0 11.74 0.0	11.74	
5	38.65 0.0 0.0	0.42 50.82 0.0	0.0 12.17 0.0	0.0 12.17 0.0	12.17	
6	43.81 0.0 0.0	0.49 55.93 0.0	0.0 12.12 0.0	0.0 12.12 0.0	12.12	
7	48.97 0.0 0.0	0.55 60.7 0.0	0.0 11.73 0.0	0.0 11.73 0.0	11.73	
8	54.13 0.0 0.0	0.61 65.2 0.0	0.0 11.07 0.0	0.0 11.07 0.0	11.07	
9	59.29 0.0 0.0	0.66 69.47 0.0	0.0 10.18 0.0	0.0 10.18 0.0	10.18	
10	64.45 0.0 0.0	0.72 73.56 0.0	0.0 9.11 0.0	0.0 9.11 0.0	9.11	
11	69.61 0.0 0.0	0.77 77.49 0.0	0.0 7.88 0.0	0.0 7.88 0.0	7.88	
12	74.77 0.0 0.0	0.82 81.29 0.0	0.0 6.52 0.0	0.0 6.52 0.0	6.52	
13	79.93 0.0 0.0	0.87 84.97 0.0	0.0 5.04 0.0	0.0 5.04 0.0	5.04	
14	85.09 0.0 0.0	0.91 88.54 0.0	0.0 3.45 0.0	0.0 3.45 0.0	3.45	
15	90.25 0.0 0.0	0.96 92.02 0.0	0.0 1.77 0.0	0.0 1.77 0.0	1.77	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 7.6
17	18.01 0.0 0.0	0.0 18.01 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	37.36 0.0 0.0	0.41 49.47 0.0	0.0 12.11 0.0	0.0 12.11 0.0	12.11	
19	56.71 0.0 0.0	0.64 67.36 0.0	0.0 10.65 0.0	0.0 10.65 0.0	10.65	
20	76.06 0.0 0.0	0.83 82.22 0.0	0.0 6.16 0.0	0.0 6.16 0.0	6.16	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 5.8
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 67	

OG640-3N-133-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-133-11: File: Measure unknown; Device: Device unknown; Date: Date unknown


L^*/Y_{intended} (absolut)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_p=0.65$ Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relativ)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,173	0,27	0,352	0,424	0,49	0,552	0,61	0,665	0,718	0,769	0,817	0,865	0,911	0,956	1,0

OG640-7N, Bild A7-133-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle ($\rightarrow \text{rgb}^*_{\text{de}}$) setrgbcolo
Gesehener Y-Kontrast $Y_W:Y_N=88,9:2,5$; Y_N -Bereich 1,87 to <3,75Ausgabe 133-11: $g_p=0.77$; $g_N=1.0$

i	LAB*ref			l*out			LAB*out/c-ref			ΔE*	Start-Ausgabe S1
1	26.85	0.0	0.0	0.0	26.85	0.0	0.0	0.0	0.0	0.01	Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
2	31.42	0.0	0.0	0.21	41.05	0.0	0.0	9.63	0.0	9.63	
3	35.99	0.0	0.0	0.31	48.1	0.0	0.0	12.11	0.0	12.11	
4	40.56	0.0	0.0	0.39	53.75	0.0	0.0	13.18	0.0	13.18	
5	45.13	0.0	0.0	0.46	58.64	0.0	0.0	13.51	0.0	13.51	
6	49.7	0.0	0.0	0.53	63.05	0.0	0.0	13.34	0.0	13.34	
7	54.27	0.0	0.0	0.59	67.09	0.0	0.0	12.82	0.0	12.82	
8	58.84	0.0	0.0	0.64	70.87	0.0	0.0	12.02	0.0	12.02	
9	63.41	0.0	0.0	0.69	74.42	0.0	0.0	11.01	0.0	11.01	
10	67.99	0.0	0.0	0.74	77.79	0.0	0.0	9.81	0.0	9.81	
11	72.56	0.0	0.0	0.79	81.01	0.0	0.0	8.46	0.0	8.46	
12	77.13	0.0	0.0	0.84	84.1	0.0	0.0	6.97	0.0	6.97	
13	81.7	0.0	0.0	0.88	87.07	0.0	0.0	5.37	0.0	5.37	
14	86.27	0.0	0.0	0.92	89.94	0.0	0.0	3.67	0.0	3.67	
15	90.84	0.0	0.0	0.96	92.71	0.0	0.0	1.88	0.0	1.88	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	ΔE*CIELAB = 8.4
17	26.85	0.0	0.0	0.0	26.85	0.0	0.0	0.0	0.0	0.01	
18	43.99	0.0	0.0	0.45	57.47	0.0	0.0	13.48	0.0	13.48	
19	61.13	0.0	0.0	0.67	72.67	0.0	0.0	11.54	0.0	11.54	
20	78.27	0.0	0.0	0.85	84.85	0.0	0.0	6.58	0.0	6.58	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	ΔL*CIELAB = 6.3
Mittlerer Farbwiedergabe-Index:								R* _{ab,m} = 64			

OG640-3N-134-11: File: Measure unknown; Device: Device unknown; Date: Date unknown




L^*/Y_{intended} (absolut)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_p=0.58$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = [L^*_{\text{CIELAB}, r}]$ (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.208	0.309	0.392	0.464	0.528	0.587	0.642	0.694	0.743	0.79	0.835	0.878	0.92	0.96	1.0

OG640-7N, Bild A7-134-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle ($\rightarrow \text{rgb}^*_{\text{de}}$) setrgbcolo
Gesehener Y-Kontrast $Y_W:Y_N=88,9:5$; Y_N -Bereich 3,75 to <7,5 Ausgabe 134-11: $g_p=0.7$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	37.99 0.0 0.0	0.0 0.0 0.0	37.99 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	41.81 0.0 0.0	0.24 51.79 0.0	0.0 0.0 9.98	0.0 0.0 9.98	9.98	ISO/IEC 15775 Anhang G
3	45.64 0.0 0.0	0.35 57.87 0.0	0.0 0.0 12.23	0.0 0.0 12.23	12.23	und DIN 33866-1 Anhang G
4	49.47 0.0 0.0	0.43 62.6 0.0	0.0 0.0 13.13	0.0 0.0 13.13	13.13	
5	53.3 0.0 0.0	0.5 66.63 0.0	0.0 0.0 13.33	0.0 0.0 13.33	13.33	
6	57.13 0.0 0.0	0.56 70.19 0.0	0.0 0.0 13.07	0.0 0.0 13.07	13.07	
7	60.96 0.0 0.0	0.62 73.44 0.0	0.0 0.0 12.48	0.0 0.0 12.48	12.48	
8	64.78 0.0 0.0	0.67 76.44 0.0	0.0 0.0 11.65	0.0 0.0 11.65	11.65	
9	68.61 0.0 0.0	0.72 79.23 0.0	0.0 0.0 10.62	0.0 0.0 10.62	10.62	
10	72.44 0.0 0.0	0.76 81.87 0.0	0.0 0.0 9.43	0.0 0.0 9.43	9.43	
11	76.27 0.0 0.0	0.81 84.37 0.0	0.0 0.0 8.11	0.0 0.0 8.11	8.11	
12	80.1 0.0 0.0	0.85 86.76 0.0	0.0 0.0 6.66	0.0 0.0 6.66	6.66	
13	83.93 0.0 0.0	0.89 89.05 0.0	0.0 0.0 5.12	0.0 0.0 5.12	5.12	
14	87.75 0.0 0.0	0.93 91.24 0.0	0.0 0.0 3.49	0.0 0.0 3.49	3.49	
15	91.58 0.0 0.0	0.96 93.36 0.0	0.0 0.0 1.78	0.0 0.0 1.78	1.78	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 8.2
17	37.99 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	52.34 0.0 0.0	0.48 65.67 0.0	0.0 0.0 13.33	0.0 0.0 13.33	13.33	
19	66.7 0.0 0.0	0.69 77.86 0.0	0.0 0.0 11.16	0.0 0.0 11.16	11.16	
20	81.05 0.0 0.0	0.86 87.34 0.0	0.0 0.0 6.29	0.0 0.0 6.29	6.29	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 6.2
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 65	

OG640-3N-135-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-135-11: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^{*}/Y_{intended}$ (absolut)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^{*} w^{*} w^{*}$ setrgb																
$g_p=0.53$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}$ CIELAB, r (relativ)																
$w^{*}_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^{*}_{out}	0.0	0.241	0.346	0.429	0.499	0.561	0.617	0.67	0.718	0.764	0.808	0.849	0.889	0.928	0.964	1.0

OG640-7N, Bild A7-135-11: 16 visuell gleichabständige L^{*} -Graustufen; PS-Operator: $w^{*} w^{*} w^{*}$ setrgbcolor

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle (->rgb*_{de}) setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:10$; Y_N -Bereich 7,5 to <15 Ausgabe 135-11: $g_p=0.62$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	54.91 0.0 0.0	0.27 63.82 0.0	0.0 0.0 8.91	0.0 0.0 8.91	8.91	ISO/IEC 15775 Anhang G
3	57.8 0.0 0.0	0.38 68.49 0.0	0.0 0.0 10.69	0.0 0.0 10.69	10.69	und DIN 33866-1 Anhang G
4	60.7 0.0 0.0	0.46 72.03 0.0	0.0 0.0 11.34	0.0 0.0 11.34	11.34	
5	63.59 0.0 0.0	0.53 75.0 0.0	0.0 0.0 11.41	0.0 0.0 11.41	11.41	
6	66.48 0.0 0.0	0.59 77.61 0.0	0.0 0.0 11.12	0.0 0.0 11.12	11.12	
7	69.37 0.0 0.0	0.64 79.95 0.0	0.0 0.0 10.57	0.0 0.0 10.57	10.57	
8	72.27 0.0 0.0	0.69 82.1 0.0	0.0 0.0 9.83	0.0 0.0 9.83	9.83	
9	75.16 0.0 0.0	0.74 84.09 0.0	0.0 0.0 8.93	0.0 0.0 8.93	8.93	
10	78.05 0.0 0.0	0.78 85.96 0.0	0.0 0.0 7.91	0.0 0.0 7.91	7.91	
11	80.95 0.0 0.0	0.82 87.72 0.0	0.0 0.0 6.78	0.0 0.0 6.78	6.78	
12	83.84 0.0 0.0	0.86 89.4 0.0	0.0 0.0 5.56	0.0 0.0 5.56	5.56	
13	86.73 0.0 0.0	0.9 91.0 0.0	0.0 0.0 4.26	0.0 0.0 4.26	4.26	
14	89.62 0.0 0.0	0.93 92.53 0.0	0.0 0.0 2.9	0.0 0.0 2.9	2.9	
15	92.52 0.0 0.0	0.97 93.99 0.0	0.0 0.0 1.48	0.0 0.0 1.48	1.48	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 7.0
17	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.0	
18	62.87 0.0 0.0	0.51 74.3 0.0	0.0 0.0 11.43	0.0 0.0 11.43	11.43	
19	73.71 0.0 0.0	0.72 83.11 0.0	0.0 0.0 9.4	0.0 0.0 9.4	9.4	
20	84.56 0.0 0.0	0.87 89.81 0.0	0.0 0.0 5.24	0.0 0.0 5.24	5.24	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 5.2
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 70	

OG640-3N-136-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-136-11: File: Measure unknown; Device: Device unknown; Date: Date unknown


L^*/Y_{intended} (absolut)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_p=0.48$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=I^*$ CIELAB, r (relativ)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,273	0,379	0,461	0,53	0,589	0,644	0,693	0,739	0,782	0,823	0,861	0,898	0,934	0,967	1,0

OG640-7N, Bild A7-136-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle ($\rightarrow \text{rgb}^*_{\text{de}}$) setrgbcolo
Gesehener Y-Kontrast $Y_W:Y_N=88,9:20$; Y_N -Bereich 15 to <30 Ausgabe 136-11: $g_p=0.55$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	69.7 0.0 0.0	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	71.41 0.0 0.0	0.3 77.46 0.0 0.0	6.04 0.0 0.0	6.04	0.0	ISO/IEC 15775 Anhang G
3	73.13 0.0 0.0	0.41 80.24 0.0 0.0	7.11 0.0 0.0	7.11	0.0	und DIN 33866-1 Anhang G
4	74.84 0.0 0.0	0.49 82.31 0.0 0.0	7.47 0.0 0.0	7.47	0.0	
5	76.55 0.0 0.0	0.56 84.02 0.0 0.0	7.47 0.0 0.0	7.47	0.0	
6	78.27 0.0 0.0	0.62 85.51 0.0 0.0	7.24 0.0 0.0	7.24	0.0	
7	79.98 0.0 0.0	0.67 86.84 0.0 0.0	6.86 0.0 0.0	6.86	0.0	
8	81.7 0.0 0.0	0.71 88.05 0.0 0.0	6.35 0.0 0.0	6.35	0.0	
9	83.41 0.0 0.0	0.76 89.17 0.0 0.0	5.76 0.0 0.0	5.76	0.0	
10	85.12 0.0 0.0	0.8 90.21 0.0 0.0	5.08 0.0 0.0	5.08	0.0	
11	86.84 0.0 0.0	0.84 91.19 0.0 0.0	4.35 0.0 0.0	4.35	0.0	
12	88.55 0.0 0.0	0.87 92.11 0.0 0.0	3.56 0.0 0.0	3.56	0.0	
13	90.27 0.0 0.0	0.91 92.99 0.0 0.0	2.73 0.0 0.0	2.73	0.0	
14	91.98 0.0 0.0	0.94 93.83 0.0 0.0	1.85 0.0 0.0	1.85	0.0	
15	93.7 0.0 0.0	0.97 94.64 0.0 0.0	0.94 0.0 0.0	0.94	0.0	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 4.6	
17	69.7 0.0 0.0	0.0 69.7 0.0 0.0	0.0 0.0 0.0	0.01	0.0	
18	76.13 0.0 0.0	0.54 83.62 0.0 0.0	7.5 0.0 0.0	7.5	0.0	
19	82.55 0.0 0.0	0.74 88.62 0.0 0.0	6.06 0.0 0.0	6.06	0.0	
20	88.98 0.0 0.0	0.88 92.34 0.0 0.0	3.35 0.0 0.0	3.35	0.0	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 3.4	
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 80	

OG640-3N-137-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG641-3N-137-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolut)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^* w^* w^*$ setrgb $g_p=0.44$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.302	0.41	0.491	0.557	0.615	0.667	0.714	0.757	0.798	0.836	0.872	0.906	0.939	0.97	1.0

OG640-7N, Bild A7-137-11: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG64: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DEH Eingabe: alle (->rgb*_{de}) setrgbcolo
Gesehener Y-Kontrast $Y_W:Y_N=88,9:40$; Y_N -Bereich 30 to <60 Ausgabe 137-11: $g_p=0.47$; $g_N=1.0$