

| i  | LAB*ref |     | l*out |      | LAB*out |     | LAB*out/c-ref |     |     | ΔE*  | <b>Start-Ausgabe S1</b><br><b>Kennzeichnung nach</b><br><b>ISO/IEC 15775 Anhang G</b><br><b>und DIN 33866-1 Anhang G</b> |  |
|----|---------|-----|-------|------|---------|-----|---------------|-----|-----|------|--------------------------------------------------------------------------------------------------------------------------|--|
| 1  | 0.0     | 0.0 | 0.0   | 0.0  | 0.0     | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 2  | 6.36    | 0.0 | 0.0   | 0.07 | 6.36    | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 | <b>Mittlerer Helligkeitsabstand (16 Stufen)</b><br><br><b>ΔE*<sub>CIELAB</sub> = 0.0</b>                                 |  |
| 3  | 12.72   | 0.0 | 0.0   | 0.13 | 12.72   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 4  | 19.08   | 0.0 | 0.0   | 0.2  | 19.08   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 5  | 25.44   | 0.0 | 0.0   | 0.27 | 25.44   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 6  | 31.8    | 0.0 | 0.0   | 0.33 | 31.8    | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 7  | 38.16   | 0.0 | 0.0   | 0.4  | 38.16   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 8  | 44.52   | 0.0 | 0.0   | 0.47 | 44.52   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 9  | 50.89   | 0.0 | 0.0   | 0.53 | 50.89   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 10 | 57.25   | 0.0 | 0.0   | 0.6  | 57.25   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 11 | 63.61   | 0.0 | 0.0   | 0.67 | 63.61   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 12 | 69.97   | 0.0 | 0.0   | 0.73 | 69.97   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 13 | 76.33   | 0.0 | 0.0   | 0.8  | 76.33   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 14 | 82.69   | 0.0 | 0.0   | 0.87 | 82.69   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 15 | 89.05   | 0.0 | 0.0   | 0.93 | 89.05   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 | <b>Mittlerer Helligkeitsabstand (5 Stufen)</b><br><br><b>ΔL*<sub>CIELAB</sub> = 0.0</b>                                  |  |
| 16 | 95.41   | 0.0 | 0.0   | 1.0  | 95.41   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 17 | 0.0     | 0.0 | 0.0   | 0.0  | 0.0     | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 18 | 23.85   | 0.0 | 0.0   | 0.25 | 23.85   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 19 | 47.71   | 0.0 | 0.0   | 0.5  | 47.71   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 20 | 71.56   | 0.0 | 0.0   | 0.75 | 71.56   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 |                                                                                                                          |  |
| 21 | 95.41   | 0.0 | 0.0   | 1.0  | 95.41   | 0.0 | 0.0           | 0.0 | 0.0 | 0.01 | <b>Mittlerer Farbwiedergabe-Index: R*<sub>ab,m</sub> = 100</b>                                                           |  |