

see similar files: <http://130.149.60.45/~farbmeterik/QE66/QE66.HTM>
technical information: <http://www.ps.bam.de> or <http://130.149.60.45/~farbmeterik>

Input and Output: Offset Reflective System ORS18a for relative CIELAB hue $h_{ab,a,rel} = h_{ab}/360 = 136/360 = 0.37$

$H^*_d = Y75G_d$


Data for any device (d) or elementary (e) colour:

HIC^*_d

hue text for the colours of this page:

$H^*_d = Y75G_d$

triangle lightness T^*



ORS20a; adapted (a) CIELAB data

name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _{d,Ma}	45.4	70.9	44.8	83.9	32
Y _{d,Ma}	87.8	-10.2	95.4	96.0	96
G _{d,Ma}	50.0	-65.0	29.6	71.4	155
C _{d,Ma}	56.8	-25.5	-41.5	48.7	238
B _{d,Ma}	25.0	29.5	-40.4	50.0	306
M _{d,Ma}	46.1	79.3	-0.2	79.3	359
N _{d,Ma}	24.3	0.0	0.0	0.0	0
W _{d,Ma}	95.6	0.0	0.0	0.0	0
R _{d,CIE}	39.9	58.7	27.9	65.0	25
Y _{d,CIE}	81.2	-2.8	71.5	71.6	92
G _{d,CIE}	52.2	-42.4	13.6	44.5	162
B _{d,CIE}	30.5	1.4	-46.4	46.4	271

Data for maximum colour (Ma):

$LabCh^*_{d,Ma}$: 57 -48 45 66 136

$HIC^*_{d,Ma}$: Y75G_100_100d

$rgbic^*_{d,Ma}$:

0.23 1.0 0.0 1.0 1.0

triangle lightness T^*

% Gamut

$u^*_{rel} = 92$



% Regularity

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

ORS20a; adapted (a) CIELAB data

H^*_d	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100d	45.4	70.9	44.8	83.9	32
R25Y_100_100d	53.0	53.4	54.8	76.5	45
R50Y_100_100d	64.9	28.9	68.6	74.5	67
R75Y_100_100d	78.6	4.3	84.7	84.8	87
Y00G_100_100d	87.8	-10.2	95.4	96.0	96
Y25G_100_100d	81.2	-17.0	84.3	86.0	101
Y50G_100_100d	70.6	-29.7	66.5	72.8	114
Y75G_100_100d	57.9	-48.3	45.8	66.5	136
G00B_100_100d	50.0	-65.0	29.6	71.4	155
G25B_100_100d	52.9	-48.6	-8.0	49.3	189
G50B_100_100d	56.8	-25.5	-41.5	48.7	238
G75B_100_100d	41.7	-1.2	-40.6	40.6	268
B00R_100_100d	25.0	29.5	-40.4	50.0	306
B25R_100_100d	35.6	58.6	-20.7	62.1	340
B50R_100_100d	46.1	79.3	-0.2	79.3	359
B75R_100_100d	45.9	74.2	21.1	77.1	15



TUB-test chart QE66; hue code: $H^*_d=Y75G_d$
Test chart according to DIN 33872, 3D=0, de=0, cmy0

input: $rgb/cmyk \rightarrow rgb_d$
output: transfer to $cmy0_d$

TUB registration: 20130201-QE66/QE66L0NA.TXT /.PS
application for measurement of offset print output, separation cmy0 (CMY0)

TUB material: code=rha4ta

http://130.149.60.45/~farbmeterik/QE66/QE66L0NA.TXT /.PS; start output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 1/2

Input and Output: Offset Reflective System ORS18a for relative CIELAB hue $h_{ab,a,rel} = h_{ab}/360 = 139/360 = 0.38$


Data for any device (d) or elementary (e) colour:

HIC^*

hue text for the colours of this page:

$H^*_- = Y75G_-$

triangle lightness T^*



ORS18a; adapted (a) CIELAB data

name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _{-,Ma}	47.9	65.3	50.5	82.6	37
Y _{-,Ma}	90.3	-10.2	91.7	92.3	96
G _{-,Ma}	50.9	-62.8	34.9	71.9	150
C _{-,Ma}	58.6	-30.3	-45.0	54.2	236
B _{-,Ma}	25.7	31.0	-44.4	54.2	305
M _{-,Ma}	48.1	75.2	-8.3	75.7	353
N _{-,Ma}	18.0	0.0	0.0	0.0	0
W _{-,Ma}	95.4	0.0	0.0	0.0	0
R _{-,CIE}	39.9	58.7	27.9	65.0	25
Y _{-,CIE}	81.2	-2.8	71.5	71.6	92
G _{-,CIE}	52.2	-42.4	13.6	44.5	162
B _{-,CIE}	30.5	1.4	-46.4	46.4	271

Data for maximum colour (Ma):

$LabCh^*_{-,Ma}$: 62 -49 43 65 139

$HIC^*_{-,Ma}$: Y75G_100_100-

$rgbic^*_{-,Ma}$:

0.23 1.0 0.0 1.0 1.0

triangle lightness T^*

% Gamut

$u^*_{rel} = 92$



% Regularity

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

ORS20a; adapted (a) CIELAB data

H^*_-	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100-	48.4	66.1	40.2	77.3	31
R25Y_100_100-	56.8	48.0	50.5	69.6	46
R50Y_100_100-	68.6	25.0	63.9	68.6	68
R75Y_100_100-	80.6	4.8	77.2	77.3	86
Y00G_100_100-	90.2	-9.6	88.2	88.7	96
Y25G_100_100-	83.2	-18.4	79.9	81.9	102
Y50G_100_100-	73.3	-31.7	62.7	70.2	116
Y75G_100_100-	62.0	-49.7	43.2	65.8	139
G00B_100_100-	55.8	-65.2	33.8	73.4	152
G25B_100_100-	59.3	-50.3	-9.0	51.0	190
G50B_100_100-	63.0	-30.5	-42.0	51.9	234
G75B_100_100-	45.7	-5.7	-44.6	44.9	262
B00R_100_100-	27.5	25.9	-47.3	53.9	298
B25R_100_100-	38.3	52.6	-28.5	59.8	331
B50R_100_100-	49.5	73.5	-9.0	74.0	353
B75R_100_100-	48.9	69.3	12.9	70.4	10



TUB-test chart QE66; hue code: $H^*_- = Y75G_-$
Test chart according to DIN 33872, 3D=0, de=1, cmy0

input: $rgb/cmyk \rightarrow rgb/cmyk$
output: no change

Input and Output: Offset Reflective System ORS18a for relative CIELAB hue $h_{ab,a,rel} = h_{ab}/360 = 145/360 = 0.4$

$H^*_e = Y75G_e$


Data for any device (d) or elementary (e) colour:

HIC^*_e

hue text for the colours of this page:

$H^*_e = Y75G_e$

triangle lightness T^*



ORS20a; adapted (a) CIELAB data

name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _e ,Ma	45.6	72.2	34.4	80.0	25
Y _e ,Ma	83.6	-3.6	90.4	90.4	92
G _e ,Ma	50.6	-62.1	19.9	65.2	162
C _e ,Ma	55.0	-36.2	-27.2	45.3	216
B _e ,Ma	40.2	1.2	-40.6	40.6	271
M _e ,Ma	31.1	47.7	-29.1	55.9	328
N _e ,Ma	24.3	0.0	0.0	0.0	0
W _e ,Ma	95.6	0.0	0.0	0.0	0
R _e ,CIE	39.9	58.7	27.9	65.0	25
Y _e ,CIE	81.2	-2.8	71.5	71.6	92
G _e ,CIE	52.2	-42.4	13.6	44.5	162
B _e ,CIE	30.5	1.4	-46.4	46.4	271

Data for maximum colour (Ma):

$LabCh^*_{e,Ma}$: 54 -55 37 67 145

$HIC^*_{e,Ma}$: Y75G_100_100_e

$rgbic^*_{e,Ma}$:

0.1 1.0 0.0 1.0 1.0

triangle lightness T^*

% Gamut

$u^*_{rel} = 92$



% Regularity

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

ORS20a; adapted (a) CIELAB data

H^*_e	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100 _e	45.6	72.2	34.4	80.0	25
R25Y_100_100 _e	50.5	59.2	51.6	78.6	41
R50Y_100_100 _e	60.2	38.2	63.4	74.1	58
R75Y_100_100 _e	70.9	17.9	75.9	77.9	76
Y00G_100_100 _e	83.6	-3.6	90.4	90.4	92
Y25G_100_100 _e	74.5	-25.0	74.3	78.4	108
Y50G_100_100 _e	62.6	-40.9	53.8	67.6	127
Y75G_100_100 _e	54.1	-55.5	37.5	67.0	145
G00B_100_100 _e	50.6	-62.1	19.9	65.2	162
G25B_100_100 _e	53.0	-48.6	-8.2	49.2	189
G50B_100_100 _e	55.0	-36.2	-27.2	45.3	216
G75B_100_100 _e	53.3	-19.8	-41.3	45.9	244
B00R_100_100 _e	40.2	1.2	-40.6	40.6	271
B25R_100_100 _e	28.1	23.4	-40.3	46.7	300
B50R_100_100 _e	31.1	47.7	-29.1	55.9	328
B75R_100_100 _e	41.4	70.4	-9.8	71.1	352



1-013131-L0 QE660-71

TUB-test chart QE66; hue code: $H^*_e = Y75G_e$
Test chart according to DIN 33872, 3D=0, de=1, cmy0

input: $rgb/cmyk \rightarrow rgb_e$
output: transfer to $cmy0_e$