

Ein- und Ausgabe: Laser-Reflektiv-System LRS18a


Daten für jede Geräte- (d) oder
Elementarfarbe (e):

HIC^*

Bunttextext für die Farben
dieser Seite:

$H^*_e = R00Y_e, R25Y_e, \dots, B75R_e$

ORS20a; adaptierte CIELAB-Daten						
H^*	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$	
R00Y_100_100	48.4	66.1	40.2	77.3	31	
R25Y_100_100	56.8	48.0	50.5	69.6	46	
R50Y_100_100	68.6	25.0	63.9	68.6	68	
R75Y_100_100	80.6	4.8	77.2	77.3	86	
Y00G_100_100	90.2	-9.6	88.2	88.7	96	
Y25G_100_100	83.2	-18.4	79.9	81.9	102	
Y50G_100_100	73.3	-31.7	62.7	70.2	116	
Y75G_100_100	62.0	-49.7	43.2	65.8	139	
G00B_100_100	55.8	-65.2	33.8	73.4	152	
G25B_100_100	59.3	-50.3	-9.0	51.0	190	
G50B_100_100	63.0	-30.5	-42.0	51.9	234	
G75B_100_100	45.7	-5.7	-44.6	44.9	262	
B00R_100_100	27.5	25.9	-47.3	53.9	298	
B25R_100_100	38.3	52.6	-28.5	59.8	331	
B50R_100_100	49.5	73.5	-9.0	74.0	353	
B75R_100_100	48.9	69.3	12.9	70.4	10	



%Umfang



$u^*_{rel} = 114$

%Regularität

$g^*_{H,rel} = 28$

$g^*_{C,rel} = 38$

LRS18a; adaptierte CIELAB-Daten					
Name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R_Ma	32.5	62.3	46.4	77.7	36
Y_Ma	82.7	-3.1	113.9	114.0	91
G_Ma	39.4	-61.8	45.8	76.9	143
B_Ma	47.8	-26.8	-34.2	43.4	231
R_Ma	10.1	55.1	-61.0	82.2	312
M_Ma	34.5	80.6	-33.9	87.5	337
N_Ma	6.2	0.0	0.0	0.0	0
W_Ma	91.9	0.0	0.0	0.0	0
R_CIE	39.9	58.7	27.9	65.0	25
Y_CIE	81.2	-2.8	71.5	71.6	92
G_CIE	52.2	-42.4	13.6	44.5	162
B_CIE	30.5	1.4	-46.4	46.4	271



RG820-7N RGB 0-003030-L0

TUB-Prüfvorlage RG82; 16 Bunttöne, $cf=1$
Prüfvorlage nach DIN 33872

Eingabe: rgb/cmyk -> rgb/cmyk
Ausgabe: keine Änderung