


Entrada i salida: Laser Reflective System LRS18a

Datos del dispositivo (d) o elemental (e) color:

HIC^*_d
código de tono para les colores
esta página:
 $H^*_d = R00Y_d, R25Y_d, ..., B75R_d$

LRS18a; datos adaptados CIELAB (a)					
H^*_d	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100_d	45.9	61.7	29.3	68.3	25
R25Y_100_100_d	57.6	45.4	48.7	66.6	47
R50Y_100_100_d	69.5	24.3	57.8	62.8	67
R75Y_100_100_d	81.1	5.7	61.4	61.7	84
Y00G_100_100_d	89.4	-7.1	66.3	66.7	96
Y25G_100_100_d	88.3	-14.2	73.9	75.3	100
Y50G_100_100_d	72.6	-32.8	51.9	61.5	122
Y75G_100_100_d	60.9	-49.3	34.9	60.4	144
G00B_100_100_d	54.1	-59.5	24.4	64.3	157
G25B_100_100_d	55.4	-44.3	-11.3	45.7	194
G50B_100_100_d	52.1	-22.8	-47.0	52.2	244
G75B_100_100_d	45.3	-5.0	-54.6	54.9	264
B00R_100_100_d	32.3	25.6	-44.5	51.4	299
B25R_100_100_d	35.4	50.1	-32.6	59.8	326
B50R_100_100_d	46.8	70.7	-17.3	72.8	346
B75R_100_100_d	44.4	64.5	5.3	64.7	4



%Gama
 $u^*_{rel} = 114$
%Regularidad
 $g^*_{H,rel} = 28$
 $g^*_{C,rel} = 38$

LRS18a; datos adaptados CIELAB (a)					
name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _d ,Ma	45.9	61.7	29.3	68.3	25
Y _d ,Ma	89.4	-7.1	66.3	66.7	96
G _d ,Ma	54.1	-59.5	24.4	64.3	157
C _d ,Ma	52.1	-22.8	-47.0	52.2	244
B _d ,Ma	32.3	25.6	-44.5	51.4	299
M _d ,Ma	46.8	70.7	-17.3	72.8	346
N _d ,Ma	20.0	0.0	0.0	0.0	0
W _d ,Ma	94.2	0.0	0.0	0.0	0
R _d ,CIE	39.9	58.7	27.9	65.0	25
Y _d ,CIE	81.2	-2.8	71.5	71.6	92
G _d ,CIE	52.2	-42.4	13.6	44.5	162
B _d ,CIE	30.5	1.4	-46.4	46.4	271

