

Device colours $RYGCBM_d$ of maximum (m) C_{AB} for D65, $Y_w=100$

Code	X	Y	Z	x	y	z	h_{xy}	id_m	λ_d	i_c	λ_c
R _{ARECS}	30.96	17.2	4.58	0.5869	0.3261	0.0868	359.4	41	607	17	486
Y _{ARECS}	68.17	76.74	10.96	0.4373	0.4923	0.0703	52.6	33	568	13	467
G _{ARECS}	11.05	23.64	9.47	0.2501	0.5352	0.2145	106.8	25	527	-1	527 ^c
C _{ARECS}	22.6	31.61	75.13	0.1747	0.2444	0.5808	211.5	15	478	35	578
B _{ARECS}	7.38	5.26	24.41	0.1992	0.1419	0.6587	238.7	11	459	33	565
M _{ARECS}	34.22	18.04	23.89	0.4493	0.2369	0.3137	326.0	-1	494	18	494
R _{ARECS}	31.41	17.44	6.62	0.5662	0.3143	0.1193	356.7	43	615	17	487
Y _{ARECS}	63.12	68.2	10.32	0.4456	0.4815	0.0728	48.9	34	570	14	470
G _{ARECS}	12.32	24.86	15.72	0.2328	0.4699	0.2971	119.4	22	510	-1	510 ^c
B _{ARECS}	11.61	12.05	39.53	0.1838	0.1906	0.6254	227.0	14	472	34	570

Device colours $RYGCBM_d$ of maximum (m) C_{AB} for D65, $Y_w=100$

Code	Y	A	B	C _{AB}	a	b	h_{AB}	id_m	λ_d	i_c	λ_c
R _{ARECS}	17.2	14.61	5.66	15.66	1.7994	-0.1064	21.1	41	607	17	486
Y _{ARECS}	76.74	-4.76	29.04	29.43	0.8883	-0.0571	99.3	33	568	14	472
G _{ARECS}	23.64	-11.42	6.5	13.14	0.4674	-0.1803	150.3	26	531	-1	531 ^c
C _{ARECS}	31.61	-7.44	-16.28	17.9	0.715	-0.9506	245.4	15	478	35	578
B _{ARECS}	5.26	2.38	-7.47	7.84	1.4041	-1.8565	287.7	11	455	32	561
M _{ARECS}	18.04	17.07	-1.69	17.15	1.8965	-0.5296	354.3	-1	492	18	492
R _{ARECS}	17.44	14.83	4.94	15.63	1.8009	-0.1518	18.4	42	614	17	486
Y _{ARECS}	68.2	-1.7	25.58	25.63	0.9254	-0.0605	93.8	34	570	14	474
G _{ARECS}	24.86	-11.31	4.54	12.18	0.4955	-0.2529	158.1	23	516	-1	516 ^c
B _{ARECS}	12.05	0.16	-10.56	10.56	0.9642	-1.3122	270.9	14	471	33	567

Device colours $RYGCBM_d$ of maximum (m) C_{AB} for D65, $Y_w=100$

Code	L*	a*	b*	C _{AB}	a'	b'	h_{AB}	id_m	λ_d	i_c	λ_c
R _{ARECS}	48.53	65.92	41.65	77.97	0.2664	-0.0538	32.2	-1	480	16	480
Y _{ARECS}	90.2	-10.19	90.05	90.62	0.2106	-0.0437	96.4	33	566	14	471
G _{ARECS}	55.74	-65.11	35.02	73.93	0.17	-0.0617	151.7	24	521	-1	521 ^c
C _{ARECS}	63.03	-30.81	-40.49	50.86	0.1959	-0.1117	232.7	15	477	40	604
B _{ARECS}	27.49	26.0	-46.53	53.3	0.2452	-0.1396	299.1	13	465	30	550
M _{ARECS}	49.56	73.14	-7.61	73.54	0.2711	-0.0919	354.0	-1	499	19	499
R _{ARECS}	48.82	66.31	33.06	74.1	0.2665	-0.0606	26.5	-1	481	16	481
Y _{ARECS}	86.11	-3.88	84.83	84.92	0.2135	-0.0446	92.6	33	569	14	471
G _{ARECS}	56.95	-61.32	20.83	64.77	0.1733	-0.0718	161.2	22	512	-1	512 ^c
B _{ARECS}	41.31	1.19	-43.87	43.89	0.2164	-0.1244	271.5	14	472	34	570

Device colours $RYGCBM_d$ of maximum (m) C_{AB} for D65, $Y_w=100$

CodeD65	L*	a*	b*	C _{AB}	a'	b'	h_{AB}	id_m	λ_d	i_c	λ_c
R _{ARECS}	48.53	65.93	41.68	78.01	0.2665	-0.0538	32.2	-1	480	16	480
Y _{ARECS}	90.2	-10.19	90.07	90.65	0.2106	-0.0437	96.4	33	566	14	471
G _{ARECS}	55.74	-65.14	35.04	73.97	0.17	-0.0617	151.7	24	521	-1	521 ^c
C _{ARECS}	63.03	-30.81	-40.48	50.87	0.1959	-0.1117	232.7	15	477	40	604
B _{ARECS}	27.49	26.02	-46.56	53.34	0.2453	-0.1396	299.2	13	465	30	550
M _{ARECS}	49.56	73.16	-7.61	73.56	0.2711	-0.0919	354.0	-1	499	19	499
R _{ARECS}	48.82	66.33	33.08	74.12	0.2665	-0.0606	26.5	-1	481	16	481
Y _{ARECS}	86.11	-3.88	84.86	84.95	0.2135	-0.0446	92.6	33	569	14	472
G _{ARECS}	56.95	-61.35	20.84	64.79	0.1733	-0.0718	161.2	22	512	-1	512 ^c
B _{ARECS}	41.31	1.19	-43.88	43.9	0.2164	-0.1244	271.5	14	472	34	570

