



http://130.149.60.45/~farbmetrik/TE76/TE76L0NP.PDF /.PS; transfer output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 2/2


see similar files: http://130.149.60.45/~farbmetrik/TE76/TE76L0NP.PDF /.PS
technical information: http://www.ps.bam.de or http://130.149.60.45/~farbmetrik




radial gratings (Siemens-stars) N-W



radial gratings (Siemens-stars) W-N



radial gratings (Siemens-stars) N-Z



radial gratings (Siemens-stars) W-Z

TE760-3, Picture C1Wd: Element A: radial gratings N-W, W-N, N-Z and W-Z; PS operator: rgb/cmy0

L^*/Y_{input} (absolute)	18.0/2.5	37.3/9.7	56.7/24.6	76.1/49.9	95.4/88.6	N_0 (min.)	W_1 (max.)
$w^* = L^*_{CIELAB, r}$ (relative)							
w^*_{input}	0,000	0,250	0,500	0,750	1,000	N_0 (min.)	W_1 (max.)

TE760-5, Picture C2Wd: Element B: 5 visual equidistant L^* -grey steps + N_0 + W_1 ; PS operator: rgb/cmy0

L^*/Y_{input} (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.3	69.6/40.2	74.8/47.9	79.9/56.5	85.1/66.2	90.2/76.8	95.4/88.6
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = L^*_{CIELAB, r}$ (relative)																
w^*_{input}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000

TE760-7, Picture C3Wd: Element C: 16 visual equidistant L^* -grey steps; PS operator: rgb/cmy0

test chart TE76; ME16(ISO 9241-306), 3(ISO/IEC 15775)
achromatic test chart N, 3D=0, de=0, cmyk

input: rgb/cmyk -> rgb_d
output: transfer to $cmyk_d$



<i>background step</i>	0									1	<i>ring step</i>	0-1
<i>Hex code</i>	7									8	<i>Hex code</i>	7-8
	E									F		E-F
	2									0		2-0
	8									6		8-6
	F									D		F-D
		Landolt-rings W-N									<i>code: background-ring</i>	

TE761-1, Picture C4Wd: Element D: Landolt-rings W-N; PS operator: rgb/cmy0

	120	128	136	144	152	160	168	176	184	192	200	208	216	224	232	240	
120 (+8)																	240
60 (+4)																	120
30 (+2)																	60
15 (+1)																	30
	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	
line raster diameter in lpi																	

TE761-3, Picture C5Wd: Element E: Line raster under 45° (or 135°); PS operator: rgb/cmy0

	120	128	136	144	152	160	168	176	184	192	200	208	216	224	232	240		
120 (+8)																		240
60 (+4)																		120
30 (+2)																		60
15 (+1)																		30
	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30		
line raster diameter in lpi																		

TE761-5, Picture C6Wd: Element F: Line raster under 90° (or 0°); PS operator: rgb/cmy0