









CIE data for all optimal colours of maximum (m) C_{AB}, D65 and Y_w=88.6, Y_m=520, 770

i ₁	λ ₁	i ₂	λ ₂	X _{88.6}	Y _{88.6}	Z _{88.6}	x	y	z	x _{xy}	i ₄	i ₄	i ₄	i ₄	i ₄	i ₄	Code
0	405	32	561	28.85	51.56	95.79	0.1637	0.2926	0.5436	193.7	16	483	37	589	37	589	Cm
6	435	32	562	25.77	52.08	78.6	0.1647	0.3328	0.5023	178.4	17	486	42	610			
10	450	32	563	20.31	52.64	46.4	0.1702	0.441	0.3887	141.8	19	496	-1	496c			
12	460	33	565	18.49	53.43	30.14	0.1812	0.5234	0.2952	124.0	21	505	-1	505c			
12	465	33	567	19.45	54.62	30.14	0.1866	0.5241	0.2892	122.8	21	506	-1	506c			
14	470	33	569	19.02	55.56	17.7	0.206	0.604	0.1918	111.3	24	520	-1	520c			
15	475	34	573	21.05	57.84	13.21	0.2285	0.6279	0.1434	105.6	25	528	-1	528c			
16	480	36	580	25.69	61.97	9.79	0.2636	0.6358	0.1005	99.0	27	537	-1	537c			
17	485	39	595	37.3	69.76	7.29	0.3261	0.6099	0.0638	87.2	29	548	-1	548c			
18	490	-1	490c	68.29	83.1	5.43	0.4354	0.5298	0.0346	58.5	33	565	11	459	max		
19	495	-1	495c	68.25	81.77	4.0	0.4431	0.5308	0.026	57.1	33	566	12	462			
20	500	-1	500c	68.23	80.1	2.89	0.4511	0.5296	0.0191	55.3	33	567	12	464			
22	510	-1	510c	68.12	75.54	1.45	0.4694	0.5205	0.01	50.7	33	569	13	469			
23	520	-1	519c	67.91	72.63	1.03	0.4797	0.513	0.0072	47.7	34	570	14	471	Ym		
25	530	-1	529c	66.91	65.59	0.51	0.503	0.4931	0.0038	40.7	34	573	15	475			
27	540	-1	539c	64.9	57.49	0.23	0.5292	0.4688	0.0019	32.8	35	577	15	478			
28	545	-1	544c	63.48	53.27	0.16	0.5429	0.4556	0.0014	28.7	35	579	15	479			
29	550	-1	549c	61.75	48.96	0.11	0.5571	0.4417	0.001	24.7	36	582	16	480			
30	555	-1	554c	59.71	44.65	0.08	0.5716	0.4274	0.0008	20.8	36	584	16	481			
32	560	-1	560c	54.73	36.33	0.05	0.6007	0.3987	0.0005	13.6	37	589	16	483			
32	561	0	405	66.18	48.43	13.1	0.5182	0.3792	0.1025	13.7	37	589	16	483	Rm		
32	562	6	435	69.27	47.91	30.28	0.4697	0.3249	0.2053	35.4	42	610	17	486			
32	563	10	450	74.73	47.33	62.49	0.4048	0.2565	0.3385	32.18	-1	496c	19	496			
32	565	10	460	76.54	46.56	78.74	0.3792	0.2306	0.3901	30.41	-1	505c	21	505			
33	567	12	465	75.59	45.37	78.74	0.3785	0.2271	0.3942	30.29	-1	506c	21	506			
33	569	14	470	76.02	44.43	91.18	0.3592	0.2099	0.4308	29.13	-1	520c	24	520			
34	573	15	475	73.98	42.15	95.67	0.3492	0.199	0.4516	28.57	-1	528c	25	528	Mm		
36	580	16	480	69.34	38.02	99.09	0.3358	0.1841	0.4799	27.91	-1	537c	27	537			
39	595	17	485	57.73	30.23	101.59	0.3045	0.1594	0.5359	26.72	-1	548c	29	548			
-1	490c	18	490	26.74	16.89	103.45	0.1818	0.1148	0.7032	238.5	11	459	33	565	min		
-1	495c	19	495	26.79	18.22	104.88	0.1787	0.1215	0.6996	237.1	12	462	33	566			
-1	500c	20	500	26.81	19.89	105.99	0.1755	0.1302	0.6941	235.4	12	464	33	567			
-1	510c	22	510	26.92	24.45	107.43	0.1695	0.1539	0.6765	230.7	13	469	33	569			
-1	519c	23	520	27.12	27.36	107.85	0.167	0.1685	0.6643	227.7	14	471	34	570	Bm		
-1	529c	25	530	28.12	34.4	108.38	0.1645	0.2012	0.6341	220.7	15	475	34	573			
-1	539c	27	540	30.13	42.5	108.65	0.1662	0.2344	0.5993	212.8	15	478	35	577			
-1	544c	28	545	31.55	46.72	108.72	0.1687	0.2498	0.5813	208.8	15	479	35	579			
-1	549c	29	550	33.29	51.03	108.77	0.1723	0.2643	0.5632	204.7	16	480	36	582			
-1	554c	30	555	35.32	55.34	108.8	0.1771	0.2774	0.5454	200.6	16	481	36	584			
-1	560c	32	560	40.31	63.66	108.84	0.1894	0.2991	0.5114	193.6	16	483	37	589			
380	770	84.19	88.59	96.46	0.3127	0.329	0.3582	0.0									



TUB-test graphique TF17; maximum C_{AB}, Y_m=520, 770
 XYZ, xyz, h data for illuminant D65, Y_w=100

entrée: w/rbg/cmyk -> w/rbg/cmyk-
 sortie: aucun changement