

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/TG03/TG03L0NA.TXT> /PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

Cod.	i	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C*, h _{ab} , a', b', c', a _b] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c, a _B] ₁₀₀	[X, Y, Z] ₈₉	[L*, a*, b*, C*, h _{ab} , a', b', c', a _b] ₈₉	[Y, A, B, C _{AB} , h _{AB}] ₈₉	
0099-R00B	00	27.2 11.6 1.4	0.677 0.289	40.6 85.6 50.8 99.6 30.7 0.291	-0.102 0.136	11.6 16.2 4.5 16.8 15.5 2.342	-0.047 1.446	46 17 631 487
0099-Y95R	01	29.8 13.2 0.4	0.687 0.305	43.1 85.0 69.3 109.6 39.2 0.287	-0.061 0.169	13.2 17.2 5.6 18.1 18.0 2.253	-0.01 1.371	43 17 617 487
0099-Y90R	02	32.3 15.0 0.0	0.683 0.317	45.6 83.2 78.7 114.5 43.4 0.283	0.0 0.226	15.0 18.0 6.5 19.2 19.9 2.151	0.0 1.278	42 17 610 486
0099-Y85R	03	34.4 16.9 0.0	0.671 0.329	48.1 80.2 82.9 115.4 46.0 0.278	0.0 0.225	16.9 18.4 7.3 19.8 21.8 2.039	0.0 1.173	41 17 606 486
0099-Y80R	04	36.3 18.8 0.0	0.659 0.341	50.5 76.4 86.7 115.6 48.6 0.273	-0.02 0.203	18.8 18.4 8.2 20.2 23.9 1.93	0.0 1.073	40 17 602 486
0099-Y75R	05	38.2 20.7 0.1	0.647 0.352	52.7 73.0 89.5 115.5 50.8 0.269	-0.033 0.189	20.7 18.5 9.0 20.5 25.9 1.84	-0.001 0.99	39 17 599 485
0099-Y70R	06	40.0 22.7 0.0	0.638 0.362	54.8 69.8 94.4 117.4 53.5 0.265	0.0 0.221	22.7 18.4 9.9 20.9 28.2 1.762	0.0 0.922	39 17 597 485
0099-Y65R	07	41.7 24.7 0.0	0.628 0.372	56.8 66.5 97.8 118.3 55.8 0.261	0.0 0.22	24.7 18.3 10.7 21.2 30.4 1.69	0.0 0.859	39 16 595 484
0099-Y60R	08	43.2 26.7 0.0	0.618 0.382	58.7 62.7 101.2 119.0 58.2 0.257	0.0 0.22	26.7 17.9 11.6 21.3 33.0 1.619	0.0 0.799	38 16 592 484
0099-Y55R	09	44.6 28.9 0.1	0.607 0.392	60.6 58.4 103.9 119.2 60.6 0.254	-0.024 0.194	28.9 17.2 12.5 21.3 36.0 1.547	0.0 0.739	38 16 590 483
0099-Y50R	10	46.2 31.2 0.1	0.596 0.403	62.7 54.1 107.1 119.9 63.2 0.25	-0.026 0.191	31.2 16.5 13.5 21.4 39.3 1.48	0.0 0.685	37 16 588 483
0099-Y45R	11	48.1 33.9 0.1	0.586 0.413	64.9 50.0 110.8 121.6 65.7 0.246	-0.026 0.192	33.9 15.9 14.7 21.7 42.8 1.419	0.0 0.64	37 16 586 482
0099-Y40R	12	50.4 37.0 0.1	0.576 0.423	67.3 46.0 115.3 124.1 68.3 0.243	-0.022 0.195	37.0 15.3 16.1 22.2 46.4 1.363	0.0 0.6	37 16 585 482
0099-Y35R	13	53.3 40.7 0.1	0.566 0.433	70.0 41.9 119.3 126.5 70.7 0.24	-0.026 0.19	40.7 14.6 17.7 22.9 50.4 1.309	0.0 0.564	36 16 583 481
0099-Y30R	14	56.3 44.8 0.1	0.557 0.443	72.8 37.5 124.3 129.8 73.2 0.237	-0.024 0.191	44.8 13.8 19.5 23.8 54.7 1.257	0.0 0.532	36 16 581 480
0099-Y25R	15	59.4 49.3 0.1	0.546 0.453	75.6 32.6 128.7 132.8 75.8 0.233	-0.027 0.188	49.3 12.6 21.4 24.8 59.6 1.204	0.0 0.503	36 15 580 479
0099-Y20R	16	63.0 54.8 0.1	0.534 0.465	78.9 27.0 134.9 137.6 78.7 0.23	-0.023 0.192	54.8 11.0 23.8 26.2 65.3 1.15	0.0 0.478	35 15 578 478
0099-Y15R	17	67.3 61.6 0.2	0.522 0.477	82.7 20.5 140.1 141.6 81.7 0.226	-0.028 0.187	61.6 8.8 26.7 28.1 71.7 1.093	0.0 0.457	35 15 576 477
0099-Y10R	18	70.7 68.0 0.3	0.508 0.489	86.0 13.5 143.8 144.5 84.7 0.222	-0.034 0.181	68.0 6.1 29.5 30.1 78.3 1.039	-0.001 0.443	34 15 574 476
0099-Y05R	19	71.8 72.4 0.5	0.496 0.5	88.2 6.5 144.9 145.0 87.4 0.219	-0.039 0.176	72.4 3.0 31.3 31.5 84.5 0.991	-0.002 0.434	34 14 572 474
0099-Y00R	20	70.8 74.5 0.7	0.485 0.51	89.2 0.1 147.7 143.7 90.3 0.215	-0.039 0.172	75.5 0.5 32.1 32.1 89.9 0.95	-0.003 0.431	34 14 571 472
0099-G95Y	21	68.0 74.4 0.8	0.475 0.519	89.1 -5.5 141.7 141.8 92.3 0.213	-0.046 0.169	74.4 -2.5 32.0 32.1 94.6 0.915	-0.003 0.432	33 14 569 470
0099-G90Y	22	64.7 73.1 0.8	0.467 0.527	88.5 -10.0 140.5 140.9 94.3 0.21	-0.046 0.169	73.1 -4.6 31.5 31.8 98.6 0.885	-0.004 0.435	33 13 568 468
0099-G85Y	23	61.7 71.8 0.9	0.459 0.534	87.9 -14.6 138.5 139.2 96.1 0.208	-0.048 0.167	71.8 -6.4 30.9 31.5 101.9 0.859	-0.004 0.44	33 13 567 465
0099-G80Y	24	58.8 70.3 0.8	0.453 0.541	87.1 -18.3 138.4 139.6 97.6 0.207	-0.047 0.168	70.3 -7.8 30.3 31.3 104.7 0.836	-0.004 0.445	33 12 566 463
0099-G75Y	25	55.8 68.4 0.6	0.447 0.548	86.2 -21.6 140.2 141.8 98.8 0.205	-0.042 0.173	68.4 -9.0 29.5 30.9 107.2 0.816	-0.002 0.452	33 12 565 460
0099-G70Y	26	52.6 66.0 0.6	0.441 0.554	85.0 -24.5 138.4 140.6 100.1 0.203	-0.042 0.173	66.0 -10.0 28.5 30.2 109.4 0.797	-0.002 0.458	32 11 564 456
0099-G65Y	27	49.2 63.2 0.6	0.435 0.559	83.6 -27.4 135.8 138.5 101.4 0.202	-0.043 0.172	63.2 -10.7 27.3 29.3 111.6 0.778	-0.003 0.461	32 10 563 451
0099-G60Y	28	45.5 60.0 0.7	0.429 0.565	81.8 -30.2 131.8 135.2 103.0 0.2	-0.045 0.17	60.0 -11.3 25.8 28.3 113.8 0.759	-0.003 0.471	32 8 563 443
0099-G55Y	29	41.5 56.2 0.5	0.422 0.573	79.8 -33.3 130.1 134.3 104.4 0.198	-0.043 0.173	56.2 -11.8 24.3 27.0 116.2 0.737	-0.003 0.481	32 5 562 427
0099-G50Y	30	37.1 52.2 0.4	0.414 0.582	77.4 -36.8 127.4 132.7 106.2 0.196	-0.041 0.175	52.2 -12.3 22.5 25.7 118.9 0.71	-0.002 0.493	32 -1 560 560c
0099-G45Y	31	32.8 48.2 0.4	0.403 0.592	75.0 -40.1 123.4 130.0 108.4 0.193	-0.042 0.174	48.2 -12.9 20.8 24.5 121.9 0.681	-0.002 0.509	31 -1 559 559c
0099-G40Y	32	28.6 44.5 0.4	0.389 0.606	72.6 -46.4 119.8 128.5 111.2 0.189	-0.041 0.175	44.5 -13.5 19.2 23.6 125.4 0.643	-0.002 0.529	31 -1 557 557c
0099-G35Y	33	24.6 41.3 0.3	0.372 0.624	70.4 -53.4 117.7 129.3 114.4 0.184	-0.037 0.18	41.3 -14.5 17.8 23.0 129.2 0.596	-0.001 0.559	30 -1 554 554c
0099-G30Y	34	20.9 38.5 0.3	0.35 0.645	68.4 -61.8 113.3 129.1 118.6 0.179	-0.041 0.177	38.5 -15.6 16.6 22.8 133.3 0.543	-0.002 0.593	30 -1 551 551c
0099-G25Y	35	17.5 36.2 0.6	0.322 0.667	66.7 -71.9 106.1 128.2 124.2 0.172	-0.053 0.168	35.2 -16.8 15.5 22.9 137.5 0.482	-0.006 0.634	29 -1 547 547c
0099-G20Y	36	13.9 34.3 0.6	0.285 0.703	65.2 -86.4 103.7 135.0 129.9 0.162	-0.054 0.17	34.3 -18.6 14.7 23.8 141.8 0.405	-0.006 0.693	28 -1 542 542c
0099-G15Y	37	10.0 32.8 0.6	0.231 0.755	64.0 -138.2 102.0 148.8 136.7 0.148	-0.054 0.175	32.8 -21.0 14.0 25.3 146.4 0.306	-0.006 0.773	27 -1 535 535c
0099-G10Y	38	6.7 31.5 2.2	0.166 0.781	62.9 -103.6 82.0 156.8 148.5 0.131	-0.085 0.155	31.5 -23.1 12.8 26.5 150.1 0.212	-0.026 0.842	25 -1 525 525c
0099-G05Y	39	4.6 30.4 6.0	0.113 0.741	62.0 -153.5 58.4 164.3 159.2 0.117	-0.121 0.136	30.4 -24.2 10.8 26.6 155.9 0.152	-0.078 0.873	22 -1 514 514c
0099-G00Y	40	3.7 29.5 11.7	0.083 0.658	61.2 -163.1 38.2 167.6 166.8 0.11	-0.153 0.123	29.5 -24.2 8.2 25.6 161.4 0.126	-0.157 0.869	21 -1 505 505c
0099-B95G	41	3.7 28.8 18.4	0.073 0.565	60.0 -159.9 21.3 161.4 172.4 0.111	-0.18 0.111	28.8 -23.5 5.1 24.1 167.7 0.13	-0.255 0.839	19 -1 499 499c
0099-B90G	42	4.6 28.2 24.5	0.08 0.492	60.1 -145.6 9.4 146.0 176.3 0.12	-0.199 0.098	28.2 -22.1 2.5 22.3 173.7 0.163	-0.347 0.792	19 -1 495 495c
0099-B85G	43	5.2 27.9 28.5	0.085 0.452	59.8 -136.2 2.7 136.3 178.9 0.126	-0.21 0.091	27.9 -21.1 0.7 21.2 178.0 0.188	-0.408 0.762	18 -1 493 493c
0099-B80G	44	5.4 27.7 31.3	0.084 0.43	59.6 -123.4 1.6 133.5 180.7 0.127	-0.217 0.089	27.7 -20.8 0.4 20.9 181.3 0.195	-0.451 0.754	18 -1 491 491c
0099-B75G	45	5.7 27.6 34.0	0.085 0.41	59.5 -129.7 1.5 129.9 182.5 0.13	-0.224 0.087	27.6 -20.4 0.1 20.6 184.5 0.206	-0.492 0.745	18 -1 490 490c
0099-B70G	46	6.2 27.5 36.7	0.088 0.391	59.4 -123.7 1.1 124.1 184.3 0.133	-0.23 0.084	27.5 -19.8 0.2 20.1 187.8 0.225	-0.533 0.731	17 -1 489 489c
0099-B65G	47	6.6 27.5 39.5	0.09 0.373	59.4 -110.9 12.6 119.8 186.1 0.136	-0.236 0.082	27.5 -19.3 0.3 19.8 191.2 0.241	-0.575 0.722	17 -1 488 488c
0099-B60G	48	7.1 27.4 42.4	0.092 0.356	59.3 -114.0 16.1 115.2 188.1 0.14	-0.241 0.081	27.4 -18.8 0.4 19.6 194.9 0.259	-0.617 0.714	17 47 488 637
0099-B55G	49	7.5 27.3 45.3	0.094 0.341	59.2 -109.3 19.5 111.2 190.2 0.143	-0.247 0.08	27.3 -18.3 0.6 19.4 198.8 0.276	-0.663 0.711	17 42 487 614
0099-B50G	50	8.0 27.0 48.1	0.096 0.325	59.0 -104.3 23.0 106.9 192.5 0.146	-0.253 0.08	27.0 -17.6 0.7 19.2 202.9 0.294	-0.711 0.711	17 40 486 604
0099-B45G	51	8.4 26.6 50.7	0.098 0.31	58.9 -98.9 26.4 102.5 195.0 0.149	-0.259 0.08	26.6 -16.8 0.8 19.0 207.4 0.315	-0.763 0.715	17 39 485 598
0099-B40G	52	8.8 26.0 53.3	0.099 0.295	58.0 -93.2 29.9 98.0 197.9 0.152	-0.265 0.081	26.0 -15.8 0.9 18.8 212.1 0.337	-0.819 0.724	16 38 484 593
0099-B35G	53	9.1 25.4 56.1	0.1 0.28	57.4 -87.7 33.7 94.1 201.1 0.156	-0.272 0.084	25.4 -14.9 11.3 18.8 217.3 0.358	-0.884 0.743	16 37 483 589
0099-B30G	54	9.4 24.6 59.0	0.101 0.264	56.7 -81.6 37.7 90.1 204.8 0.159	-0.279 0.086	24.6 -13.8 12.8 19.0 222.8 0.383	-0.	

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/TG03/TG03L0NA.TXT> /PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

Cod.	i	[X, Y, Z, x, y] ₁₀₀					[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c', c' _{ab}] ₁₀₀					[Y, A, B, C _{AB} , h _{AB} , a, b, c, c _{AB}] ₁₀₀					[i _a , i _c , λ _a , λ _c] ₁₀₀					[X, Y, Z] ₈₉					[L*, a*, b*, C* _{ab} , h _{ab}] ₈₉					[Y, A, B, C _{AB} , h _{AB}] ₈₉							
9900-W99N	80	0.7	0.8	0.9	0.312	0.329	7.0	0.0	0.0	0.0	227.8	0.215	-0.215	0.01	0.8	0.0	0.0	0.0	229.9	0.949	-0.435	0.01	16	36	481	583	0.7	0.7	0.8	6.2	0.0	0.0	0.0	227.8	0.7	0.0	0.0	0.0	229.7
9500-W95N	81	2.4	2.5	2.8	0.312	0.329	18.1	0.0	0.0	0.0	164.0	0.215	-0.214	0.01	2.5	0.0	0.0	0.0	160.6	0.949	-0.434	0.01	20	-1	504	504c	2.1	2.2	2.4	16.7	0.0	0.0	0.0	164.0	2.2	0.0	0.0	0.0	160.5
9000-W90N	82	4.2	4.4	4.8	0.313	0.329	25.0	0.0	0.0	0.0	329.0	0.215	-0.215	0.01	4.4	0.0	0.0	0.0	326.1	0.95	-0.434	0.01	-1	27	537c	537	3.7	3.9	4.2	23.3	0.0	0.0	0.0	329.0	3.9	0.0	0.0	0.0	326.2
8500-W85N	83	6.1	6.4	7.0	0.313	0.329	30.4	0.0	0.0	0.1	325.8	0.215	-0.215	0.01	6.4	0.0	0.0	0.0	322.4	0.95	-0.435	0.01	-1	28	542c	542	5.4	5.7	6.2	28.6	0.0	0.0	0.1	325.8	5.7	0.0	0.0	0.0	322.5
8000-W80N	84	8.1	8.6	9.3	0.313	0.329	35.1	0.0	0.0	0.0	318.5	0.215	-0.215	0.01	8.6	0.0	0.0	0.0	314.9	0.95	-0.434	0.01	-1	30	550c	550	7.2	7.6	8.3	33.1	0.0	0.0	0.0	318.5	7.6	0.0	0.0	0.0	315.0
7500-W75N	85	10.4	10.9	11.9	0.313	0.329	39.4	0.1	0.0	0.1	351.1	0.216	-0.214	0.01	10.9	0.0	0.0	0.0	350.1	0.95	-0.434	0.01	-1	19	497c	497	9.2	9.7	10.5	37.2	0.1	0.0	0.1	351.1	9.7	0.0	0.0	0.0	350.1
7000-W70N	86	12.8	13.4	14.6	0.313	0.329	43.4	0.1	0.0	0.1	331.0	0.215	-0.215	0.01	13.4	0.0	0.0	0.0	327.7	0.95	-0.434	0.01	-1	26	533c	533	11.3	11.9	12.9	41.0	0.1	0.0	0.1	331.0	11.9	0.0	0.0	0.0	327.8
6500-W65N	87	15.4	16.1	17.6	0.313	0.329	47.2	0.1	0.0	0.1	342.8	0.216	-0.215	0.01	16.1	0.0	0.0	0.0	340.6	0.95	-0.434	0.01	-1	21	506c	506	13.6	14.3	15.6	44.7	0.1	0.0	0.1	342.8	14.3	0.0	0.0	0.0	340.6
6000-W60N	88	18.2	19.1	20.8	0.313	0.329	50.8	0.1	0.0	0.1	334.8	0.216	-0.215	0.01	18.2	0.0	0.0	0.0	333.1	0.95	-0.434	0.01	-1	24	523c	523	16.1	16.9	18.5	48.2	0.1	0.0	0.1	334.8	16.9	0.0	0.0	0.0	342.1
5500-W55N	89	21.3	22.4	24.4	0.313	0.329	54.4	0.1	0.0	0.1	344.2	0.216	-0.214	0.01	22.4	0.0	0.0	0.0	342.1	0.95	-0.434	0.01	-1	20	504c	504	18.9	19.8	21.6	51.7	0.1	0.0	0.1	344.2	19.8	0.0	0.0	0.0	342.1
5000-W50N	90	24.7	26.0	28.3	0.313	0.329	58.0	0.1	0.0	0.2	339.5	0.216	-0.215	0.01	26.0	0.0	0.0	0.0	336.9	0.951	-0.435	0.01	-1	22	512c	512	21.9	23.0	25.0	55.1	0.1	0.0	0.1	339.5	23.0	0.0	0.0	0.0	336.9
4500-W45N	91	28.4	29.9	32.6	0.313	0.329	61.6	0.1	0.0	0.1	337.4	0.216	-0.215	0.01	29.9	0.0	0.0	0.0	334.6	0.951	-0.435	0.01	-1	23	517c	517	25.2	26.5	28.9	58.5	0.1	0.0	0.1	337.4	26.5	0.0	0.0	0.0	334.6
4000-W40N	92	32.6	34.3	37.3	0.313	0.329	65.2	0.1	0.0	0.1	340.2	0.216	-0.215	0.01	34.3	0.0	0.0	0.0	337.6	0.95	-0.434	0.01	-1	22	511c	511	28.9	30.4	33.1	62.0	0.1	0.0	0.1	340.2	30.4	0.0	0.0	0.0	337.6
3500-W35N	93	37.2	39.2	42.7	0.313	0.329	68.9	0.1	0.0	0.1	338.0	0.216	-0.215	0.01	39.2	0.0	0.0	0.0	335.2	0.95	-0.435	0.01	-1	23	515c	515	33.0	34.7	37.8	65.5	0.1	0.0	0.1	338.0	34.7	0.0	0.0	0.0	335.2
3000-W30N	94	42.4	44.7	48.6	0.313	0.329	72.7	0.1	0.0	0.2	341.0	0.216	-0.215	0.01	44.7	0.0	0.0	0.0	338.5	0.951	-0.434	0.01	-1	21	509c	509	37.6	39.6	43.1	69.2	0.1	0.0	0.2	341.0	39.6	0.0	0.0	0.0	338.5
2500-W25N	95	48.3	50.8	55.4	0.313	0.329	76.6	0.1	0.0	0.2	336.2	0.216	-0.215	0.01	50.8	0.1	0.0	0.0	333.2	0.95	-0.435	0.01	-1	24	520c	520	42.8	45.0	49.0	72.9	0.1	0.0	0.2	336.2	45.0	0.0	0.0	0.1	333.2
2000-W20N	96	55.0	57.9	63.1	0.313	0.329	80.7	0.2	0.0	0.2	338.8	0.216	-0.215	0.01	57.9	0.1	0.0	0.0	336.0	0.95	-0.435	0.01	-1	22	514c	514	48.8	51.3	55.9	76.9	0.1	0.0	0.2	338.8	51.3	0.1	0.0	0.1	336.0
1500-W15N	97	62.8	66.0	71.9	0.313	0.329	85.0	0.2	0.0	0.2	339.6	0.216	-0.215	0.01	66.0	0.1	0.0	0.0	336.9	0.95	-0.434	0.01	-1	22	512c	512	55.6	58.5	63.7	81.0	0.2	0.0	0.2	339.6	58.5	0.1	0.0	0.1	337.0
1000-W10N	98	71.7	75.5	82.2	0.313	0.329	89.6	0.2	0.0	0.2	338.8	0.216	-0.215	0.01	75.5	0.1	0.0	0.0	336.1	0.95	-0.435	0.01	-1	22	513c	513	63.6	66.9	72.8	85.4	0.2	0.0	0.2	338.8	66.9	0.1	0.0	0.1	336.1
0500-W05N	99	82.3	86.6	94.3	0.313	0.329	94.6	0.2	0.0	0.2	338.5	0.216	-0.215	0.01	86.6	0.1	0.0	0.0	335.7	0.95	-0.435	0.01	-1	22	514c	514	72.9	76.7	83.5	90.2	0.2	0.0	0.2	338.5	76.7	0.1	0.0	0.1	335.7
0000-W00N	100	94.9	99.9	108.8	0.313	0.329	100.0	0.2	0.0	0.2	338.2	0.216	-0.215	0.01	99.9	0.1	0.0	0.0	335.4	0.95	-0.435	0.01	-1	23	515c	515	84.1	88.5	96.4	95.4	0.2	0.0	0.2	338.2	88.5	0.1	0.0	0.1	335.4

TG030-7, NCS-Farben, normiert: Yn = Yw = 100