

vedere dei file simili: <http://130.149.60.45/~farbmetrik/TI03/TI03L0NP.PDF> / .PS
informazioni tecniche: <http://www.ps.bam.de> o <http://130.149.60.45/~farbmetrik>

Cod.	i	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c' _{ab}] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀
0099-R00B	00	27.2 11.6 1.4	0.677 0.289 40.6 85.6 50.8 99.6 30.7 0.291	-0.102 0.136 11.6 16.2 4.5 16.8 15.5 2.342 -0.047 1.446
0099-Y95R	01	29.8 13.2 0.4	0.687 0.305 43.1 85.0 69.3 109.6 39.2 0.287	-0.061 0.169 13.2 17.2 5.6 18.1 18.0 2.253 -0.01 1.371
0099-Y90R	02	32.3 15.0 0.0	0.683 0.317 45.6 83.2 78.7 114.5 43.4 0.283	0.0 0.226 15.0 18.0 6.5 19.2 19.9 2.151 0.0 1.278
0099-Y85R	03	34.4 16.9 0.0	0.671 0.329 48.1 80.2 82.9 115.4 46.0 0.278	0.0 0.225 16.9 18.4 7.3 19.8 21.8 2.039 0.0 1.173
0099-Y80R	04	36.3 18.8 0.0	0.659 0.341 50.5 76.4 86.7 115.6 48.6 0.273	-0.02 0.203 18.8 18.4 8.2 20.2 23.9 1.93 0.0 1.073
0099-Y75R	05	38.2 20.7 0.1	0.647 0.352 52.7 73.0 89.5 115.5 50.8 0.269	-0.033 0.189 20.7 18.5 9.0 20.5 25.9 1.84 -0.001 0.99
0099-Y70R	06	40.0 22.7 0.0	0.638 0.362 54.8 69.8 94.4 117.4 53.5 0.265	0.0 0.221 22.7 18.4 9.9 20.9 28.2 1.762 0.0 0.922
0099-Y65R	07	41.7 24.7 0.0	0.628 0.372 56.8 66.5 97.8 118.3 55.8 0.261	0.0 0.22 24.7 18.3 10.7 21.2 30.4 1.69 0.0 0.859
0099-Y60R	08	43.2 26.7 0.0	0.618 0.382 58.7 62.7 101.2 119.9 58.2 0.257	0.0 0.22 26.7 17.9 11.6 21.3 33.0 1.61 0.0 0.799
0099-Y55R	09	44.6 28.9 0.1	0.607 0.392 60.6 58.4 103.9 119.2 60.6 0.254	-0.024 0.194 28.9 17.2 12.5 21.3 36.0 1.547 0.0 0.739
0099-Y50R	10	46.2 31.2 0.1	0.596 0.403 62.7 54.1 107.1 119.9 63.2 0.25	-0.026 0.191 31.2 16.5 13.5 21.4 39.3 1.48 0.0 0.685
0099-Y45R	11	48.1 33.9 0.1	0.586 0.413 64.9 50.0 110.8 121.6 65.7 0.246	-0.026 0.192 33.9 15.9 14.7 21.7 42.8 1.419 0.0 0.64
0099-Y40R	12	50.4 37.0 0.1	0.576 0.423 67.3 46.0 115.3 124.1 68.3 0.243	-0.022 0.195 37.0 15.3 16.1 22.2 46.4 1.363 0.0 0.6
0099-Y35R	13	53.3 40.7 0.1	0.566 0.433 70.0 41.9 119.3 126.5 70.7 0.24	-0.026 0.19 40.7 14.6 17.7 22.9 50.4 1.309 0.0 0.564
0099-Y30R	14	56.3 44.8 0.1	0.557 0.443 72.8 37.5 124.3 129.8 73.2 0.237	-0.024 0.191 44.8 13.8 19.5 23.8 54.7 1.257 0.0 0.532
0099-Y25R	15	59.4 49.3 0.1	0.546 0.453 75.6 32.6 128.7 132.8 75.8 0.233	-0.027 0.188 49.3 12.6 21.4 24.8 59.6 1.204 0.0 0.503
0099-Y20R	16	63.0 54.8 0.1	0.534 0.465 78.9 27.0 134.9 137.6 78.7 0.23	-0.023 0.192 54.8 11.0 23.8 26.2 65.3 1.15 0.0 0.478
0099-Y15R	17	67.3 61.6 0.2	0.522 0.477 82.7 20.5 140.1 141.6 81.7 0.226	-0.020 0.187 61.6 8.8 26.7 28.1 71.7 1.093 0.0 0.457
0099-Y10R	18	70.7 68.0 0.3	0.508 0.489 86.0 13.5 143.8 144.5 84.7 0.222	-0.034 0.181 68.0 6.1 29.5 30.1 78.3 1.039 -0.001 0.443
0099-Y05R	19	71.8 72.4 0.5	0.496 0.5 88.2 6.5 144.9 145.0 87.4 0.219	-0.039 0.176 72.4 3.0 31.3 31.5 84.5 0.991 -0.002 0.434
0099-Y00R	20	70.8 74.5 0.7	0.485 0.51 90.2 0.1 143.7 143.7 90.2 0.217	-0.043 0.172 74.5 0.6 32.5 32.7 85.9 0.961 -0.003 0.431
0099-G95Y	21	68.0 74.4 0.8	0.475 0.519 89.1 -5.5 141.7 141.8 87.3 0.213	-0.046 0.169 74.4 2.5 32.0 32.1 94.6 0.915 -0.003 0.432
0099-G90Y	22	64.7 73.1 0.8	0.467 0.527 88.5 -10.0 140.5 140.9 84.3 0.21	-0.046 0.169 73.1 -4.6 31.5 31.8 98.6 0.885 -0.004 0.435
0099-G85Y	23	61.7 71.8 0.9	0.459 0.534 87.9 -14.6 138.5 139.2 81.6 0.208	-0.048 0.167 71.8 -6.4 30.9 31.5 101.9 0.859 -0.004 0.44
0099-G80Y	24	58.8 70.3 0.8	0.443 0.541 87.1 -18.3 138.4 139.6 79.6 0.207	-0.047 0.168 70.3 -7.8 30.3 31.3 104.7 0.836 -0.004 0.445
0099-G75Y	25	55.8 68.4 0.6	0.445 0.548 86.2 -21.6 140.2 141.8 98.8 0.205	-0.046 0.173 68.4 -9.0 29.5 30.9 107.2 0.816 -0.002 0.452
0099-G70Y	26	52.6 66.0 0.6	0.441 0.554 85.0 -24.5 138.4 140.6 100.1 0.203	-0.042 0.173 66.0 -10.0 28.5 30.2 109.4 0.797 -0.002 0.458
0099-G65Y	27	49.2 63.2 0.6	0.435 0.559 83.6 -27.4 135.8 138.5 101.4 0.202	-0.043 0.172 63.2 -10.7 27.3 29.3 111.6 0.778 -0.003 0.464
0099-G60Y	28	45.5 60.0 0.7	0.429 0.565 81.8 -30.2 131.8 135.2 103.0 0.2	-0.045 0.17 60.0 -11.3 25.8 28.3 113.8 0.759 -0.003 0.471
0099-G55Y	29	41.5 56.2 0.5	0.422 0.573 79.8 -33.3 130.1 134.3 104.4 0.198	-0.043 0.173 56.2 -11.8 24.3 27.0 116.2 0.737 -0.003 0.481
0099-G50Y	30	37.1 52.2 0.4	0.414 0.582 77.4 -36.8 127.4 132.7 106.2 0.196	-0.041 0.175 52.2 -12.3 22.5 25.7 118.9 0.711 -0.002 0.493
0099-G45Y	31	32.8 48.2 0.4	0.403 0.592 75.0 -40.1 123.4 130.0 108.4 0.193	-0.042 0.174 48.2 -12.9 20.8 24.5 121.9 0.681 -0.002 0.509
0099-G40Y	32	28.6 44.5 0.4	0.389 0.606 72.6 -46.4 119.8 128.5 111.2 0.189	-0.041 0.175 44.5 -13.5 19.2 23.6 125.4 0.643 -0.002 0.529
0099-G35Y	33	24.6 41.3 0.3	0.372 0.624 70.4 -53.4 117.7 129.3 114.4 0.184	-0.037 0.18 41.3 -14.5 17.8 23.0 129.2 0.596 -0.001 0.559
0099-G30Y	34	20.9 38.5 0.3	0.35 0.645 68.4 -61.8 113.3 129.1 118.6 0.179	-0.041 0.177 38.5 -15.6 16.6 22.8 133.3 0.543 -0.002 0.593
0099-G25Y	35	17.5 36.2 0.6	0.322 0.667 66.7 -71.9 106.1 128.2 124.2 0.172	-0.053 0.168 36.2 -16.8 15.5 22.9 137.5 0.482 -0.006 0.634
0099-G20Y	36	13.9 34.3 0.6	0.285 0.703 65.2 -86.4 103.7 135.0 129.9 0.162	-0.054 0.17 34.3 -18.6 14.7 23.8 141.8 0.405 -0.006 0.693
0099-G15Y	37	10.0 32.8 0.6	0.231 0.755 64.0 -102.8 102.0 148.8 136.7 0.148	-0.054 0.175 32.8 -21.0 14.0 25.3 146.4 0.306 -0.006 0.773
0099-G10Y	38	6.7 31.5 2.2	0.166 0.781 62.9 -133.6 82.0 156.8 148.5 0.131	-0.085 0.155 31.5 -23.1 12.8 26.5 150.1 0.212 -0.026 0.842
0099-G05Y	39	4.6 30.4 6.0	0.113 0.741 62.0 -153.5 58.4 164.3 159.2 0.117	-0.121 0.136 30.4 -24.2 10.8 26.6 155.9 0.152 -0.078 0.873
0099-G00Y	40	3.7 29.5 11.7	0.083 0.668 61.2 -163.1 38.2 167.6 166.8 0.11	-0.153 0.123 29.5 -24.2 8.2 25.6 161.4 0.126 -0.157 0.869
0099-B95G	41	3.7 28.8 18.4	0.073 0.565 60.6 -159.9 21.3 161.4 172.4 0.111	-0.18 0.111 28.8 -23.5 5.1 24.1 167.7 0.13 -0.255 0.839
0099-B90G	42	4.6 28.2 24.5	0.08 0.492 60.1 -145.6 9.4 146.0 176.3 0.12	-0.199 0.098 28.2 -22.1 2.5 22.3 173.7 0.163 -0.347 0.792
0099-B85G	43	5.2 27.9 28.5	0.085 0.452 59.8 -136.2 2.7 136.3 178.9 0.126	-0.21 0.091 27.9 -21.1 0.7 21.2 178.0 0.188 -0.408 0.762
0099-B80G	44	5.4 27.7 31.3	0.084 0.43 59.6 -133.4 1.6 133.5 180.7 0.127	-0.217 0.089 27.7 -20.8 0.4 20.9 181.3 0.195 -0.451 0.754
0099-B75G	45	5.7 27.6 34.0	0.085 0.41 59.5 -129.7 0.5 129.9 182.5 0.13	-0.224 0.087 27.6 -20.4 -1.5 20.6 184.5 0.206 -0.492 0.745
0099-B70G	46	6.2 27.5 36.7	0.088 0.391 59.4 -123.7 0.1 124.1 184.3 0.133	-0.23 0.084 27.5 -19.8 -2.6 20.1 187.8 0.225 -0.533 0.731
0099-B65G	47	6.6 27.5 39.5	0.09 0.373 59.4 -119.0 12.6 119.8 186.1 0.136	-0.236 0.082 27.5 -19.3 -3.8 19.8 191.2 0.241 -0.575 0.722
0099-B60G	48	7.1 27.4 42.4	0.092 0.356 59.3 -114.0 16.1 115.2 188.1 0.14	-0.241 0.081 27.4 -18.8 -4.9 19.6 194.9 0.259 -0.617 0.714
0099-B55G	49	7.5 27.3 45.3	0.094 0.341 59.2 -109.3 19.5 111.2 190.2 0.143	-0.247 0.08 27.3 -18.3 -6.1 19.4 198.8 0.276 -0.663 0.711
0099-B50G	50	8.0 27.0 48.1	0.096 0.325 59.0 -104.3 23.0 106.9 192.5 0.146	-0.253 0.08 27.0 -17.6 -7.4 19.2 202.9 0.294 -0.711 0.711
0099-B45G	51	8.4 26.6 50.7	0.098 0.31 58.9 -98.9 26.4 102.5 195.0 0.149	-0.259 0.08 26.6 -16.8 -8.6 19.0 207.4 0.315 -0.763 0.715
0099-B40G	52	8.8 26.0 53.3	0.099 0.295 58.0 -93.2 29.9 98.0 197.9 0.152	-0.265 0.081 26.0 -15.8 -9.9 18.8 212.1 0.337 -0.819 0.724
0099-B35G	53	9.1 25.4 56.1	0.1 0.28 57.4 -87.7 33.7 94.1 201.1 0.156	-0.272 0.084 25.4 -14.9 -11.3 18.8 217.3 0.358 -0.884 0.743
0099-B30G	54	9.4 24.6 59.0	0.101 0.264 56.7 -81.6 37.7 90.1 204.8 0.159	-0.279 0.086 24.6 -13.8 -12.8 19.0 222.8 0.383 -0.958 0.772
0099-B25G	55	9.8 23.8 62.0	0.103 0.248 55.8 -74.8 41.9 85.9 209.3 0.163	-0.288 0.09 23.8 -12.6 14.4 19.3 228.7 0.413 -1.044 0.812
0099-B20G	56	10.3 22.8 65.0	0.105 0.232 54.9 -66.7 46.2 81.3 214.8 0.168	-0.296 0.095 22.8 -11.2 16.0 19.7 234.9 0.453 -1.14 0.863
0099-B15G	57	10.9 21.8 68.6	0.107 0.217 54.0 -58.0 51.1 77.5 211.4 0.174	-0.305 0.1 21.8 -9.7 17.9 20.7 241.4 0.499 -1.259 0.941
0099-B10G	58	11.5 20.7 72.6	0.11 0.197 52.6 -48.1 56.5 74.4 229.6 0.18	-0.317 0.109 20.7 8.0 -20.0 21.7 248.0 0.557 -1.404 1.047
0099-B05G	59	12.3 19.5 77.4	0.113 0.179 51.3 -36.8 62.4 72.6 239.4 0.188	-0.33 0.12 19.5 -6.1 22.4 23.3 254.5 0.631 -1.583 1.192
0099-B00G	60	13.3 18.3 82.7	0.116 0.16 49.9 -24.1 68.9 73.1 250.7 0.197	-0.345 0.133 18.3 -4.0 25.0 25.4 260.8 0.727 -1.806 1.39
0099-R95B	61	14.4 17.0 89.4	0.119 0.141 48.2 -10.0 76.5 77.3 262.5 0.208	-0.363 0.15 17.0 -1.6 28.3 28.4 266.6 0.849 -2.105 1.674
0099-R90B	62	15.9 15.7 96.8	0.124 0.122 46.6 5.9 84.4 84.7 274.0 0.22	-0.383 0.169 15.7 0.1 -31.8 31.9 271.8 1.013 -2.465 2.032
0099-R85B	63	17.8 14.6 102.9	0.132 0.108 45.1 23.0 91.0 93.9 284.1 0.234	-0.401 0.188 14.6 3.9 34.7 35.0 276.5 1.22 -2.822 2.240
0099-R80B	64	20.0 13.6 106.8	0.140 0.097 43.7 40.2 95.8 104.0 292.7 0.249	-0.415 0.204 13.6 7.0 36.7 37.5 280.8 1.468 -3.139 2.754
0099-R75B	65	22.2 12.7 107.0	0.156 0.09 42.3 56.5 98.2 113.4 299.9 0.264	-0.425 0.216 12.7 10.1 37.2 38.6 285.2 1.744 -3.365 3.037
0099-R70B	66	24.5 11.9 106.2	0.172 0.083 41.1 72.6 99.9 123.6 306.0 0.279	-0.433 0.228 11.9 13.2 37.2 39.6 289.6 2.062 -3.567 3.325
0099-R65B	67	27.4 11.2 105.7	0.19 0.077 39.9 89.6 101.7 135.6 311.4 0.296	-0.442 0.24 11.2 16.8 37.3 41.0 294.2 2.453 -3.785 3.673
0099-R60B	68	30.8 10.5 102.1	0.215 0.073 38.7 107.5 101.4 147.9 316.7 0.314	-0.446 0.252 10.5 20.8 36.2 41.8 299.8 2.929 -3.889 3.982
0099-R55B	69	33.7 9.9 91.8	0.249 0.073 37.6 122.8 96.5 156.2 321.8 0.33	-0.44 0.253 9.9 24.3 32.3 40.5 306.8 3.409 -3.72 4.015
0099-R50B	70	33.5 9.3 73.2	0.289 0.08 36.6 126.8 84.6 152.4 326.3 0.336	-0.416 0.235 9.3 24.7 25.1 35.3 314.3 3.601 -3.147 3.794
0099-R45B	71	30.2 8.8 52.3	0.33 0.097 35.7 118.6 67.5 136.5 330.3 0.33	-0.378 0.2 8.8 21.8 17.0 21.7 321.9 3.417 -2.368 3.133
0099-R40B	72	26.9 8.4 36.4	0.376 0.117 34.8 109.5 51.1 120.9 334.9 0.323	-0.34 0.166 8.4 19.0 10.8 21.9 330.1 3.206 -1.731 2.605
0099-R35B	73	24.2 8.0 24.5	0.427 0.141 34.0 101.6 35.4 107.6 340.8 0.317	-0.303 0.135 8.0 16.6 6.2 17.8 339.2 3.026 -1.223 2.222
0099-R30B	74	22.3 7.8 16.4	0.468 0.168 33.6 94.8 20.9 97.1 347.5 0.311	-0.267 0.11 7.8 14.9 4.3 15.2 348.0 2.856 -0.839 1.95
0099-R25B	75	21.6 8.0 11.5	0.526 0.193 33.9 90.4 8.6 90.8 354.5 0.306	-0.236 0.094 8.0 14.1 1.1 14.1 355.3 2.722 -0.501 1.779
0099-R20B	76	21.9 8.3 8.4	0.568 0.216 34.6 88.4 2.2 88.4 35.1 0.303	-0.209 0.088 8.3 14.0 0.3 14.0 1.1 2.634 -0.48 1.685
0099-R15B	77	22.3 8.7 6.2	0.6 0.234 35.4 87.1 22.8 87.9 7.7 0.3	-0.186 0.09 8.7 14.1 1.3 14.1 5.3 2.568 -0.283 1.625
0099-R10B	78	23.1 9.3 4.2	0.631 0.254 36.6 85.7 11.9 88.7 15.0 0.297	-0.16 0.099 9.3 14.3 2.4 14.5 9.4 2.486 -0.181 1.557
0099-R05B	79	24.8 10.3 2.7	0.657 0.272 38.3 85.4 35.5 92.5 22.6 0.294	-0.133 0.114 10.3 15.0 3.4 15.4 12.7 2.414 -0.103 1.501

TI030-7N Yn = Yw = 100

vedere dei file simili: <http://130.149.60.45/~farbmetrik/TI03/TI03.HTM>
informazioni tecniche: <http://www.ps.bam.de> o <http://130.149.60.45/~farbmetrik>

TUB iscrizione: 20130201-TI03/TI03L0NP.PDF /.PS
la domanda per la misura di stampa di display, nessuna separazione
TUB materiale: code=rha4ta

Cod.	i	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c', c' _{ab}] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀	[i _a ', i _c ', λ _a ', λ _c '] ₁₀₀	[X, Y, Z] ₈₉	[L*, a*, b*, C* _{ab} , h _{ab}] ₈₉	[Y, A, B, C _{AB} , h _{AB}] ₈₉
9900-W99N	80	0.7 0.8 0.9	0.312 0.329 7.0 0.0 0.0 0.0 227.8 0.215 -0.215 0.01	0.8 0.0 0.0 0.0 229.9 0.949 -0.435 0.01	16 36 481 583	0.7 0.7 0.8	6.2 0.0 0.0 0.0 227.8	0.7 0.0 0.0 0.0 229.7
9500-W95N	81	2.4 2.5 2.8	0.312 0.329 18.1 0.0 0.0 0.0 164.0 0.215 -0.214 0.01	2.5 0.0 0.0 0.0 160.6 0.949 -0.434 0.01	20 -1 504 504c	2.1 2.2 2.4	16.7 0.0 0.0 0.0 164.0	2.2 0.0 0.0 0.0 160.5
9000-W90N	82	4.2 4.4 4.8	0.313 0.329 25.0 0.0 0.0 0.0 329.0 0.215 -0.215 0.01	4.4 0.0 0.0 0.0 326.1 0.95 -0.434 0.01	-1 27 537c 537	3.7 3.9 4.2	23.3 0.0 0.0 0.0 329.0	3.9 0.0 0.0 0.0 326.2
8500-W85N	83	6.1 6.4 7.0	0.313 0.329 30.4 0.0 0.0 0.1 325.8 0.215 -0.215 0.01	6.4 0.0 0.0 0.0 322.4 0.95 -0.435 0.01	-1 28 542c 542	5.4 5.7 6.2	28.6 0.0 0.0 0.1 325.8	5.7 0.0 0.0 0.0 322.5
8000-W80N	84	8.1 8.6 9.3	0.313 0.329 35.1 0.0 0.0 0.0 318.5 0.215 -0.215 0.01	8.6 0.0 0.0 0.0 314.9 0.95 -0.434 0.01	-1 30 550c 550	7.2 7.6 8.3	33.1 0.0 0.0 0.0 318.5	7.6 0.0 0.0 0.0 315.0
7500-W75N	85	10.4 10.9 11.9	0.313 0.329 39.4 0.1 0.0 0.1 351.1 0.216 -0.214 0.01	10.9 0.0 0.0 0.0 350.1 0.95 -0.434 0.01	-1 19 497c 497	9.2 9.7 10.5	37.2 0.1 0.0 0.1 351.1	9.7 0.0 0.0 0.0 350.1
7000-W70N	86	12.8 13.4 14.6	0.313 0.329 43.4 0.1 0.0 0.1 331.0 0.215 -0.215 0.01	13.4 0.0 0.0 0.0 327.7 0.95 -0.434 0.01	-1 26 533c 533	11.3 11.9 12.9	41.0 0.1 0.0 0.1 331.0	11.9 0.0 0.0 0.0 327.8
6500-W65N	87	15.4 16.1 17.6	0.313 0.329 47.2 0.1 0.0 0.1 342.8 0.216 -0.215 0.01	16.1 0.0 0.0 0.0 340.6 0.95 -0.434 0.01	-1 21 506c 506	13.6 14.3 15.6	44.7 0.1 0.0 0.1 342.8	14.3 0.0 0.0 0.0 340.6
6000-W60N	88	18.2 19.1 20.8	0.313 0.329 50.8 0.1 0.0 0.1 334.8 0.216 -0.215 0.01	19.1 0.0 0.0 0.0 331.8 0.95 -0.435 0.01	-1 24 523c 523	16.1 16.9 18.5	48.2 0.1 0.0 0.1 334.8	16.9 0.0 0.0 0.0 331.8
5500-W55N	89	21.3 22.4 24.4	0.313 0.329 54.4 0.1 0.0 0.1 344.2 0.216 -0.214 0.01	22.4 0.0 0.0 0.0 342.1 0.95 -0.434 0.01	-1 20 504c 504	18.9 19.8 21.6	51.7 0.1 0.0 0.1 344.2	19.8 0.0 0.0 0.0 342.1
5000-W50N	90	24.7 26.0 28.3	0.313 0.329 58.0 0.1 0.0 0.2 339.5 0.216 -0.215 0.01	26.0 0.0 0.0 0.0 336.9 0.951 -0.435 0.01	-1 22 512c 512	21.9 23.0 25.0	55.1 0.1 0.0 0.1 339.5	23.0 0.0 0.0 0.0 336.9
4500-W45N	91	28.4 29.9 32.6	0.313 0.329 61.6 0.1 0.0 0.1 337.4 0.216 -0.215 0.01	29.9 0.0 0.0 0.0 334.6 0.951 -0.435 0.01	-1 23 517c 517	25.2 26.5 28.9	58.5 0.1 0.0 0.1 337.4	26.5 0.0 0.0 0.0 334.6
4000-W40N	92	32.6 34.3 37.3	0.313 0.329 65.2 0.1 0.0 0.1 340.2 0.216 -0.215 0.01	34.3 0.0 0.0 0.0 337.6 0.95 -0.434 0.01	-1 22 511c 511	28.9 30.4 33.1	62.0 0.1 0.0 0.1 340.2	30.4 0.0 0.0 0.0 337.6
3500-W35N	93	37.2 39.2 42.7	0.313 0.329 68.9 0.1 0.0 0.1 338.0 0.216 -0.215 0.01	39.2 0.0 0.0 0.0 335.2 0.95 -0.435 0.01	-1 23 515c 515	33.0 34.7 37.8	65.5 0.1 0.0 0.1 338.0	34.7 0.0 0.0 0.0 335.2
3000-W30N	94	42.4 44.7 48.6	0.313 0.329 72.7 0.1 0.0 0.2 341.0 0.216 -0.215 0.01	44.7 0.0 0.0 0.1 338.5 0.951 -0.434 0.01	-1 21 509c 509	37.6 39.6 43.1	69.2 0.1 0.0 0.2 341.0	39.6 0.0 0.0 0.0 338.5
2500-W25N	95	48.3 50.8 55.4	0.313 0.329 76.6 0.1 0.0 0.2 336.2 0.216 -0.215 0.01	50.8 0.1 0.0 0.1 333.2 0.95 -0.435 0.01	-1 24 520c 520	42.8 45.0 49.0	72.9 0.1 0.0 0.2 336.2	45.0 0.0 0.0 0.1 333.2
2000-W20N	96	55.0 57.9 63.1	0.313 0.329 80.7 0.2 0.0 0.2 338.8 0.216 -0.215 0.01	57.9 0.1 0.0 0.1 336.0 0.95 -0.435 0.01	-1 22 514c 514	48.8 51.3 55.9	76.9 0.1 0.0 0.2 338.8	51.3 0.1 0.0 0.1 336.0
1500-W15N	97	62.8 66.0 71.9	0.313 0.329 85.0 0.2 0.0 0.2 339.6 0.216 -0.215 0.01	66.0 0.1 0.0 0.1 336.9 0.95 -0.434 0.01	-1 22 512c 512	55.6 58.5 63.7	81.0 0.2 0.0 0.2 339.6	58.5 0.1 0.0 0.1 337.0
1000-W10N	98	71.7 75.5 82.2	0.313 0.329 89.6 0.2 0.0 0.2 338.8 0.216 -0.215 0.01	75.5 0.1 0.0 0.1 336.1 0.95 -0.435 0.01	-1 22 513c 513	63.6 66.9 72.8	85.4 0.2 0.0 0.2 338.8	66.9 0.1 0.0 0.1 336.1
0500-W05N	99	82.3 86.6 94.3	0.313 0.329 94.6 0.2 0.0 0.2 338.5 0.216 -0.215 0.01	86.6 0.1 0.0 0.1 335.7 0.95 -0.435 0.01	-1 22 514c 514	72.9 76.7 83.5	90.2 0.2 0.0 0.2 338.5	76.7 0.1 0.0 0.1 335.7
0000-W00N	100	94.9 99.9 108.8	0.313 0.329 100.0 0.2 0.0 0.2 338.2 0.216 -0.215 0.01	99.9 0.1 0.0 0.1 335.4 0.95 -0.435 0.01	-1 23 515c 515	84.1 88.5 96.4	95.4 0.2 0.0 0.2 338.2	88.5 0.1 0.0 0.1 335.4

TI030-7 Yn = Yw = 100

grafico TUB-TI03; ; CIE data: hue circle and greys
Calculated from XYZ of NCS-Standard SS019104:1998, 3D=0 da trasf. a RGB
immettere: w/rgb/cmyk -> rgb
uscita di trasferimento a rgb