

vedere dei file simili: <http://130.149.60.45/~farbmetrik/TI11/TI11L0NP.PDF> / .PS
informazioni tecniche: <http://www.ps.dam.de> o <http://130.149.60.45/~farbmetrik>

Cod.	i	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c' _{ab}] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀	[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c' _{ab}] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀
0005-R00B	00	90.8 93.9 98.6	0.321 0.331	97.6 3.0 2.3	3.8 37.5 0.217	-0.212 0.01
0010-R00B	01	87.2 88.1 90.0	0.329 0.332	95.2 6.7 4.0	7.8 30.7 0.218	-0.21 0.011
0015-R00B	02	83.9 82.6 82.3	0.337 0.332	92.8 10.7 5.3	12.0 26.5 0.22	-0.208 0.013
0020-R00B	03	80.7 77.2 75.3	0.346 0.331	90.4 14.9 6.6	16.3 23.8 0.222	-0.207 0.014
0025-R00B	04	77.4 72.0 68.5	0.355 0.33	88.0 18.8 7.8	20.4 22.5 0.225	-0.205 0.016
0030-R00B	05	74.2 67.0 62.3	0.365 0.329	85.5 23.0 8.9	24.7 21.2 0.227	-0.203 0.019
0035-R00B	06	70.8 62.2 56.3	0.374 0.328	83.0 26.7 10.1	28.6 20.7 0.229	-0.202 0.021
0040-R00B	07	67.5 57.5 50.7	0.384 0.327	80.5 30.6 11.3	32.6 20.3 0.231	-0.2 0.024
0045-R00B	08	64.1 53.0 45.3	0.395 0.326	77.9 34.1 12.5	36.3 20.2 0.234	-0.198 0.027
0050-R00B	09	60.8 48.6 40.1	0.407 0.325	75.2 37.8 13.9	40.3 20.2 0.236	-0.195 0.03
0055-R00B	10	57.5 44.4 35.1	0.42 0.324	72.5 41.7 15.4	44.4 20.3 0.239	-0.193 0.034
0060-R00B	11	54.3 40.3 30.4	0.435 0.322	69.7 45.8 17.0	48.8 20.4 0.242	-0.19 0.038
0065-R00B	12	51.1 36.3 25.9	0.451 0.32	66.7 50.0 18.7	53.3 20.5 0.246	-0.186 0.043
0070-R00B	13	47.9 32.5 21.7	0.469 0.318	63.7 54.4 20.6	58.2 20.7 0.25	-0.182 0.048
0075-R00B	14	44.5 28.7 17.8	0.489 0.316	60.5 58.4 22.6	62.6 21.1 0.254	-0.178 0.054
0080-R00B	15	40.9 25.1 14.2	0.51 0.313	57.2 62.2 24.6	66.9 21.6 0.258	-0.172 0.061
0085-R00B	16	37.3 21.5 10.8	0.535 0.309	53.5 66.5 27.2	71.8 22.2 0.263	-0.166 0.069
0090-R00B	17	33.8 18.1 7.6	0.568 0.305	49.7 71.4 30.8	77.8 23.4 0.27	-0.156 0.081
0095-R00B	18	30.3 14.8 4.5	0.611 0.298	45.4 77.4 36.7	85.6 25.4 0.278	-0.14 0.098
0099-R00B	19	27.2 11.6 1.4	0.677 0.289	40.6 85.6 50.8	99.6 30.7 0.291	-0.102 0.136
0010-B00G	20	82.5 94.5 106.8	0.305 0.326	97.8 -2.2 -2.4	71.4 22.1 0.21	0.21 0.011
0015-B00G	21	85.5 89.3 104.8	0.298 0.323	95.7 -4.2 -4.9	66.9 22.2 0.214	0.22 0.012
0020-B00G	22	76.9 84.2 103.1	0.291 0.319	93.5 -6.0 -7.5	58.9 23.1 0.213	0.223 0.014
0025-B00G	23	71.5 79.3 101.5	0.283 0.314	91.4 -7.9 -10.3	53.1 23.4 0.212	0.226 0.016
0030-B00G	24	66.4 74.6 99.9	0.276 0.31	89.2 -9.4 -12.9	48.1 23.9 0.211	0.23 0.019
0035-B00G	25	61.7 70.0 97.9	0.269 0.305	87.0 -10.6 -15.5	43.9 24.3 0.21	0.233 0.022
0040-B00G	26	57.3 65.5 95.8	0.262 0.3	84.8 -11.8 -17.9	40.1 24.6 0.21	0.237 0.025
0045-B00G	27	52.8 61.2 94.6	0.253 0.293	82.5 -13.3 -21.0	37.6 25.0 0.209	0.241 0.029
0050-B00G	28	48.6 57.1 93.5	0.244 0.287	80.2 -14.7 -24.2	34.9 25.8 0.208	0.246 0.034
0055-B00G	29	44.4 53.0 92.9	0.233 0.279	77.9 -16.3 -27.8	32.4 26.9 0.207	0.252 0.039
0060-B00G	30	40.5 49.1 92.2	0.223 0.27	75.5 -17.8 -31.4	30.3 28.0 0.206	0.258 0.045
0065-B00G	31	36.8 45.3 91.1	0.212 0.261	73.1 -19.1 -35.1	28.1 29.4 0.205	0.264 0.052
0070-B00G	32	33.3 41.5 90.4	0.202 0.251	70.6 -20.2 -38.7	26.1 30.8 0.204	0.271 0.058
0075-B00G	33	30.1 37.9 89.2	0.191 0.241	68.0 -21.1 -42.3	24.4 32.4 0.203	0.278 0.065
0080-B00G	34	26.9 34.4 88.1	0.18 0.23	65.3 -21.8 -46.1	22.4 34.6 0.202	0.285 0.073
0085-B00G	35	23.9 31.0 87.3	0.168 0.218	62.5 -22.6 -50.4	20.5 36.9 0.201	0.295 0.082
0090-B00G	36	21.1 27.7 86.4	0.156 0.205	59.6 -23.1 -54.8	18.9 39.6 0.201	0.305 0.093
0095-B00G	37	18.3 24.5 85.0	0.142 0.19	56.6 -23.7 -59.8	17.4 42.4 0.199	0.318 0.105
0099-B00G	38	15.7 21.3 82.1	0.128 0.175	53.3 -24.3 -64.7	15.9 45.9 0.198	0.331 0.119
0005-G00Y	39	13.3 18.3 85.7	0.116 0.16	49.9 -24.1 -68.9	14.1 48.1 0.197	0.345 0.133
0010-G00Y	40	89.8 96.7 101.6	0.312 0.336	98.7 -3.6 2.2	4.3 148.6 0.214	-0.212 0.01
0015-G00Y	41	84.5 93.4 95.1	0.31 0.342	97.4 -7.7 4.3	8.9 151.3 0.212	-0.21 0.012
0020-G00Y	42	79.3 90.1 89.1	0.307 0.349	96.0 -11.9 6.1	13.5 153.3 0.21	-0.208 0.013
0025-G00Y	43	74.3 86.8 83.5	0.304 0.355	94.7 -16.2 7.6	18.0 154.9 0.208	-0.206 0.015
0030-G00Y	44	69.4 83.5 78.3	0.3 0.361	93.2 -20.3 9.1	22.3 156.0 0.206	-0.204 0.017
0035-G00Y	45	64.6 80.1 73.3	0.296 0.367	91.7 -24.4 10.4	26.6 157.1 0.204	-0.202 0.019
0040-G00Y	46	59.8 76.7 68.3	0.292 0.374	90.2 -28.9 11.8	31.3 157.9 0.202	-0.201 0.022
0045-G00Y	47	55.3 73.2 63.7	0.288 0.381	88.6 -33.2 13.0	35.7 158.7 0.2	-0.199 0.024
0050-G00Y	48	50.7 69.8 58.9	0.283 0.389	86.9 -37.8 14.4	40.6 159.2 0.197	-0.197 0.027
0055-G00Y	49	46.3 66.3 54.3	0.277 0.407	85.1 -42.4 15.7	45.3 159.7 0.194	-0.195 0.03
0060-G00Y	50	41.9 62.8 49.7	0.272 0.407	83.3 -47.2 17.2	50.4 160.0 0.192	-0.193 0.034
0065-G00Y	51	37.8 59.2 45.3	0.266 0.416	81.4 -52.0 18.6	55.3 160.3 0.189	-0.191 0.037
0070-G00Y	52	33.5 55.6 40.8	0.258 0.428	79.4 -57.8 20.3	61.3 160.7 0.185	-0.188 0.042
0075-G00Y	53	29.1 52.0 36.2	0.248 0.443	77.3 -64.6 22.1	68.4 161.1 0.181	-0.185 0.047
0080-G00Y	54	24.9 48.3 31.9	0.237 0.459	75.0 -72.1 24.0	76.1 161.6 0.176	-0.181 0.053
0085-G00Y	55	20.9 44.6 27.8	0.224 0.478	72.6 -80.1 25.9	84.3 162.1 0.171	-0.178 0.059
0090-G00Y	56	16.6 40.8 23.6	0.205 0.503	70.1 -91.0 28.1	95.4 162.8 0.163	-0.174 0.068
0095-G00Y	57	12.6 37.1 19.7	0.182 0.535	67.3 -10.0 13.6	108.6 163.6 0.153	-0.169 0.078
0099-G00Y	58	8.2 33.5 15.7	0.143 0.583	64.4 -125.6 33.8	130.2 165.0 0.137	-0.162 0.095
0005-Y00R	59	93.7 99.0 91.7	0.083 0.658	61.2 -163.3 18.2	167.6 166.8 0.11	-0.153 0.123
0010-Y00R	60	92.7 99.0 92.7	0.326 0.348	99.6 -2.2 9.7	10.0 103.5 0.214	-0.204 0.015
0015-Y00R	61	91.1 98.1 90.7	0.338 0.364	99.3 -3.5 17.7	18.1 101.6 0.214	-0.195 0.022
0020-Y00R	62	89.9 97.2 71.6	0.347 0.376	98.9 -4.2 24.1	24.5 100.1 0.214	-0.188 0.028
0025-Y00R	63	88.8 96.2 63.7	0.357 0.387	98.5 -4.5 30.1	30.4 98.7 0.213	-0.182 0.034
0030-Y00R	64	87.7 95.2 56.8	0.366 0.397	98.1 -4.7 35.7	36.0 97.7 0.213	-0.175 0.04
0035-Y00R	65	86.8 94.2 50.7	0.375 0.407	97.7 -4.8 41.0	41.3 96.8 0.213	-0.169 0.046
0040-Y00R	66	85.8 93.1 44.9	0.383 0.416	97.3 -4.8 46.4	46.6 96.0 0.213	-0.163 0.052
0045-Y00R	67	84.8 92.0 39.6	0.392 0.425	96.8 -4.6 51.6	51.9 95.2 0.213	-0.157 0.058
0050-Y00R	68	83.8 90.8 35.0	0.4 0.433	96.3 -4.5 56.7	56.9 94.6 0.213	-0.151 0.064
0055-Y00R	69	82.8 89.6 30.6	0.408 0.441	95.8 -4.3 61.7	61.9 94.1 0.213	-0.145 0.07
0060-Y00R	70	81.7 88.3 26.6	0.416 0.449	95.3 -4.1 66.9	67.0 93.6 0.214	-0.139 0.076
0065-Y00R	71	80.6 87.0 23.1	0.423 0.456	94.8 -3.8 71.7	71.8 93.1 0.214	-0.134 0.082
0070-Y00R	72	79.5 85.7 19.8	0.43 0.463	94.2 -3.6 76.6	76.7 92.8 0.214	-0.128 0.087
0075-Y00R	73	78.3 84.3 16.5	0.437 0.471	93.6 -3.3 82.3	82.4 92.4 0.214	-0.121 0.094
0080-Y00R	74	77.1 82.8 13.3	0.445 0.478	92.9 -2.9 88.5	88.6 92.0 0.214	-0.113 0.102
0085-Y00R	75	75.8 81.7 10.0	0.453 0.485	92.2 -2.6 95.2	95.2 91.6 0.214	-0.105 0.11
0090-Y00R	76	74.6 79.7 7.7	0.461 0.492	91.5 -1.9 102.7	102.7 91.1 0.215	-0.095 0.12
0095-Y00R	77	73.4 78.0 5.2	0.469 0.498	90.8 -1.2 111.5	111.5 90.7 0.215	-0.084 0.13
0099-Y00R	78	72.1 76.2 2.9	0.477 0.504	90.0 -0.5 123.1	123.1 90.3 0.215	-0.069 0.146
	79	70.8 74.5 0.7	0.485 0.51	89.2 0.1 143.7	143.7 90.0 0.215	-0.043 0.172

TI110-7N, NCS colours, normalized: Yn = Yw = 100 & 89, pagina 1/2

grafico TUB-TI11; ; CIE data: 4 elementary colours
Calculated from XYZ of NCS-Standard SS019104:1998

immettere: w/rgb/cmyk -> w/rgb/cmyk-
uscita: nessun cambiamento

TUB iscrizione: 20130201-TI11/TI11L0NP.PDF /.PS
la domanda per la misura di stampa di display
TUB materiale: code=rha4ta

vedere dei file simili: <http://130.149.60.45/~farbmetrik/TI11/TI11.HTM>
informazioni tecniche: <http://www.ps.bam.de> o <http://130.149.60.45/~farbmetrik>

Cod.	i	[X, Y, Z, x, y] ₁₀₀	[L*, a*, b*, C* _{ab} , h _{ab} , a', b', c' _{ab}] ₁₀₀	[Y, A, B, C _{AB} , h _{AB} , a, b, c _{AB}] ₁₀₀	[i _a ', i _c ', λ _a ', λ _c '] ₁₀₀	[X, Y, Z] ₈₉	[L*, a*, b*, C* _{ab} , h _{ab}] ₈₉	[Y, A, B, C _{AB} , h _{AB}] ₈₉
9900-W99N	80	0.7 0.8 0.9	0.312 0.329 7.0 0.0 0.0 0.0	227.8 0.215 -0.215 0.01	16 36 481 583	0.7 0.7 0.8	6.2 0.0 0.0 0.0	227.8 0.7 0.0 0.0 0.0
9500-W95N	81	2.4 2.5 2.8	0.312 0.329 18.1 0.0 0.0 0.0	164.0 0.215 -0.214 0.01	20 -1 504 504c	2.1 2.2 2.4	16.7 0.0 0.0 0.0	164.0 2.2 0.0 0.0 0.0
9000-W90N	82	4.2 4.4 4.8	0.313 0.329 25.0 0.0 0.0 0.0	329.0 0.215 -0.215 0.01	-1 27 537c 537	3.7 3.9 4.2	23.3 0.0 0.0 0.0	329.0 3.9 0.0 0.0 0.0
8500-W85N	83	6.1 6.4 7.0	0.313 0.329 30.4 0.0 0.0 0.1	325.8 0.215 -0.215 0.01	-1 28 542c 542	5.4 5.7 6.2	28.6 0.0 0.0 0.1	325.8 5.7 0.0 0.0 0.0
8000-W80N	84	8.1 8.6 9.3	0.313 0.329 35.1 0.0 0.0 0.0	318.5 0.215 -0.215 0.01	-1 30 550c 550	7.2 7.6 8.3	33.1 0.0 0.0 0.0	318.5 7.6 0.0 0.0 0.0
7500-W75N	85	10.4 10.9 11.9	0.313 0.329 39.4 0.1 0.0 0.1	351.1 0.216 -0.214 0.01	-1 19 497c 497	9.2 9.7 10.5	37.2 0.1 0.0 0.1	351.1 9.7 0.0 0.0 0.0
7000-W70N	86	12.8 13.4 14.6	0.313 0.329 43.4 0.1 0.0 0.1	331.0 0.215 -0.215 0.01	-1 26 533c 533	11.3 11.9 12.9	41.0 0.1 0.0 0.1	331.0 11.9 0.0 0.0 0.0
6500-W65N	87	15.4 16.1 17.6	0.313 0.329 47.2 0.1 0.0 0.1	342.8 0.216 -0.215 0.01	-1 21 506c 506	13.6 14.3 15.6	44.7 0.1 0.0 0.1	342.8 14.3 0.0 0.0 0.0
6000-W60N	88	18.2 19.1 20.8	0.313 0.329 50.8 0.1 0.0 0.1	334.8 0.216 -0.215 0.01	-1 24 523c 523	16.1 16.9 18.5	48.2 0.1 0.0 0.1	334.8 16.9 0.0 0.0 0.0
5500-W55N	89	21.3 22.4 24.4	0.313 0.329 54.4 0.1 0.0 0.1	344.2 0.216 -0.214 0.01	-1 20 504c 504	18.9 19.8 21.6	51.7 0.1 0.0 0.1	344.2 19.8 0.0 0.0 0.0
5000-W50N	90	24.7 26.0 28.3	0.313 0.329 58.0 0.1 0.0 0.2	339.5 0.216 -0.215 0.01	-1 22 512c 512	21.9 23.0 25.0	55.1 0.1 0.0 0.1	339.5 23.0 0.0 0.0 0.0
4500-W45N	91	28.4 29.9 32.6	0.313 0.329 61.6 0.1 0.0 0.1	337.4 0.216 -0.215 0.01	-1 23 517c 517	25.2 26.5 28.9	58.5 0.1 0.0 0.1	337.4 26.5 0.0 0.0 0.0
4000-W40N	92	32.6 34.3 37.3	0.313 0.329 65.2 0.1 0.0 0.1	340.2 0.216 -0.215 0.01	-1 22 511c 511	28.9 30.4 33.1	62.0 0.1 0.0 0.1	340.2 30.4 0.0 0.0 0.0
3500-W35N	93	37.2 39.2 42.7	0.313 0.329 68.9 0.1 0.0 0.1	338.0 0.216 -0.215 0.01	-1 23 515c 515	33.0 34.7 37.8	65.5 0.1 0.0 0.1	338.0 34.7 0.0 0.0 0.0
3000-W30N	94	42.4 44.7 48.6	0.313 0.329 72.7 0.1 0.0 0.2	341.0 0.216 -0.215 0.01	-1 21 509c 509	37.6 39.6 43.1	69.2 0.1 0.0 0.2	341.0 39.6 0.0 0.0 0.0
2500-W25N	95	48.3 50.8 55.4	0.313 0.329 76.6 0.1 0.0 0.2	336.2 0.216 -0.215 0.01	-1 24 520c 520	42.8 45.0 49.0	72.9 0.1 0.0 0.2	336.2 45.0 0.0 0.1 0.0
2000-W20N	96	55.0 57.9 63.1	0.313 0.329 80.7 0.2 0.0 0.2	338.8 0.216 -0.215 0.01	-1 22 514c 514	48.8 51.3 55.9	76.9 0.1 0.0 0.2	338.8 51.3 0.1 0.0 0.1
1500-W15N	97	62.8 66.0 71.9	0.313 0.329 85.0 0.2 0.0 0.2	339.6 0.216 -0.215 0.01	-1 22 512c 512	55.6 58.5 63.7	81.0 0.2 0.0 0.2	339.6 58.5 0.1 0.0 0.1
1000-W10N	98	71.7 75.5 82.2	0.313 0.329 89.6 0.2 0.0 0.2	338.8 0.216 -0.215 0.01	-1 22 513c 513	63.6 66.9 72.8	85.4 0.2 0.0 0.2	338.8 66.9 0.1 0.0 0.1
0500-W05N	99	82.3 86.6 94.3	0.313 0.329 94.6 0.2 0.0 0.2	338.5 0.216 -0.215 0.01	-1 22 514c 514	72.9 76.7 83.5	90.2 0.2 0.0 0.2	338.5 76.7 0.1 0.0 0.1
0000-W00N	100	94.9 99.9 108.8	0.313 0.329 100.0 0.2 0.0 0.2	338.2 0.216 -0.215 0.01	-1 23 515c 515	84.1 88.5 96.4	95.4 0.2 0.0 0.2	338.2 88.5 0.1 0.0 0.1

TI110-7N, NCS colours, normalized: Yn = Yw = 100 & 89, pagina 2/2

grafico TUB-TI11; ; CIE data: 4 elementary colours
Calculated from XYZ of NCS-Standard SS019104:1998

immettere: w/rgb/cmyk -> rgb_d
uscita: trasferire a rgb_d